

# The role and status of hydrogen and fuel cells across the global energy system

Iain Staffell<sup>(a)</sup>, Daniel Scamman<sup>(b)</sup>, Anthony Velazquez Abad<sup>(b)</sup>, Paul Balcombe<sup>(c)</sup>,  
Paul E. Dodds<sup>(b)</sup>, Paul Ekins<sup>(b)</sup>, Nilay Shah<sup>(d)</sup> and Kate R. Ward<sup>(a)</sup>.

(a) Centre for Environmental Policy, Imperial College London, London SW7 1NE.

(b) UCL Institute for Sustainable Resources, University College London, London WC1H 0NN.

(c) Sustainable Gas Institute, Imperial College London, SW7 1NA.

(d) Centre for Process Systems Engineering, Dept of Chemical Engineering,  
Imperial College London, London SW7 2AZ.

## Abstract

---

Hydrogen technologies have experienced cycles of excessive expectations followed by disillusion. Nonetheless, a growing body of evidence suggests these technologies form an attractive option for the deep decarbonisation of global energy systems, and that recent improvements in their cost and performance point towards economic viability as well. This paper is a comprehensive review of the potential role that hydrogen could play in the provision of electricity, heat, industry, transport and energy storage in a low-carbon energy system, and an assessment of the status of hydrogen in being able to fulfil that potential. The picture that emerges is one of qualified promise: hydrogen is well established in certain niches such as forklift trucks, while mainstream applications are now forthcoming. Hydrogen vehicles are available commercially in several countries, and 225,000 fuel cell home heating systems have been sold. This represents a step change from the situation of only five years ago. This review shows that challenges around cost and performance remain, and considerable improvements are still required for hydrogen to become truly competitive. But such competitiveness in the medium-term future no longer seems an unrealistic prospect, which fully justifies the growing interest and policy support for these technologies around the world.

### Highlights:

- Reviews the status and prospects of H<sub>2</sub>FC across transport, heat and power sectors
- Presents comparison between hydrogen and the prevailing low-carbon technologies
- H<sub>2</sub>FC can ease the low-carbon transition, supporting renewables and electric heating
- Infrastructure is a major challenge, but lower-cost incremental routes exist
- Hydrogen and fuel cells are moving towards maturity and cost competitiveness

**Keywords:** hydrogen; fuel cells; electric vehicles; CHP; energy storage; infrastructure;

# Contents

---

<b>Abstract</b> .....	<b>1</b>
<b>1 Introduction</b> .....	<b>3</b>
<b>2 Transportation</b> .....	<b>5</b>
2.1 Hydrogen powertrains.....	6
2.2 Passenger cars .....	7
2.3 Refuelling stations.....	8
2.4 Other road transport .....	9
2.5 Off-road transport.....	11
<b>3 Heat and industry</b> .....	<b>13</b>
3.1 Options for low-carbon heat.....	15
3.2 Hydrogen and fuel cell technologies.....	17
3.3 Residential and commercial heating.....	20
3.4 Industry .....	20
<b>4 The power system</b> .....	<b>22</b>
4.1 Electricity generation .....	23
4.2 Electricity storage .....	25
<b>5 Hydrogen infrastructure</b> .....	<b>27</b>
5.1 Hydrogen production .....	28
5.2 Hydrogen compression .....	29
5.3 Hydrogen purity.....	32
5.4 Hydrogen distribution .....	34
5.5 Hydrogen storage .....	37
<b>6 Policy challenges</b> .....	<b>39</b>
6.1 International policy context.....	39
6.2 Current market size .....	40
6.3 Policy drivers for hydrogen and fuel cells .....	42
<b>7 Conclusions</b> .....	<b>43</b>
<b>8 Acknowledgements</b> .....	<b>44</b>
<b>9 References</b> .....	<b>44</b>

# 1 Introduction

Thirty years ago, NREL identified hydrogen as “a critical and indispensable element of a decarbonised, sustainable energy system” to provide secure, cost-effective and non-polluting energy [1]. Today, energy leaders see hydrogen as the lowest impact and least certain issue facing the global energy system [2]. “Hydrogen, as a viable alternative fuel, continues to promise much and deliver precious little” [3].

Yet hydrogen could play a significant role in low-carbon future [4-8]: counterbalancing electricity as a zero-carbon energy carrier that can be easily stored and transported [9, 10]; enabling a more secure energy system with reduced fossil fuel dependence [11, 12]; with the versatility to operate across transport [13, 14], heat [15, 16], industry [17] and electricity generation [18, 19]. Together, these sectors account for two-thirds of global CO<sub>2</sub> emissions (Figure 1).




Figure 1: Global greenhouse gas emissions in 2012, broken down by sector and by major countries. Data from CAIT [20].

Whilst electricity is proving comparatively easy to decarbonise thanks to the dramatic cost reductions and uptake of renewables [21], these other sectors must not be forgotten. In the UK for example, heat and transport are expected to decarbonise at just one-third the rate of electricity production, with emissions falling 24% compared to 68% over the coming 15 years [22, 23]. Solutions are desperately needed to make transport and buildings sustainable that are cost-effective and appealing to consumers. Hydrogen and fuel cell technologies offer greater personal choice in the transition to a low-carbon economy, given their similar performance, operation and consumer experience to fossil-fuelled technologies. They also provide valuable insurance against the possibility of other vaunted technologies failing to deliver, such as carbon capture and storage, bioenergy and hybrid heat pumps.

Hydrogen and fuel cells are seeing a resurgence in interest: large-scale production of fuel cell vehicles has begun, and hundreds of thousands of homes are now heated and powered by fuel cells [5]. Thirteen international corporations recently formed the Hydrogen Council “to position hydrogen

among the key solutions of the energy transition” [6]. Doing so involves challenges around its complexity and diversity:

1. Hydrogen can be produced from many feedstocks and processes, with varying greenhouse gas and other emissions, costs and infrastructural requirements;
2. Hydrogen can be used in many ways, including without fuel cells, whilst fuel cells can operate using fuels other than hydrogen;
3. Hydrogen and fuel cells can contribute in many ways spanning the whole energy system
4. Hydrogen infrastructure may be costly, but pathways include several low-cost incremental routes that ‘piggy-back’ off established networks, which are often neglected.


In March 2017, the UK’s Hydrogen and Fuel Cell Supergen Hub published a White Paper that systematically assessed the current status and future prospects of hydrogen and fuel cells in future energy systems [24]. This article synthesises and updates that white paper, broadening its scope to a global focus. It builds upon previous holistic reviews of hydrogen and fuel cells [25-27], and takes the novel approach of considering how they might be integrated together across the energy system.

This article is structured as follows:

- Section 2: The transport sector, both personal vehicles and larger heavy-duty freight and public transit vehicles;
- Section 3: Heat production for residential, commercial and industrial users;
- Section 4: Electricity sector integration, balancing intermittent renewable energy;
- Section 5: Infrastructure needs, options for using existing gas grids, compression and purity requirements;
- Section 6: Policy challenges, global support and targets for hydrogen and fuel cells;
- Section 7: Conclusions.

## 2 Transportation

60 The suitability of hydrogen and fuel cells varies between transport modes and reflects the diverse nature of the transport sector, which spans land, sea and air, plus freight and passengers, as shown in Figure 2. Nearly half of energy demand for global transport is from light duty vehicles and the number of passenger cars worldwide is expected to rise from 1 to 2.5 billion by 2050 [13].



65 **Figure 2: Breakdown of energy usage in the transport sector globally in 2015. The outer ring gives the share of individual modes. "Other" is primarily passenger rail and air freight. The middle and inner rings aggregate these uses by mode and function. Data from EIA [28]. Total consumption was 110 million TJ in 2015 worldwide, equivalent to 37 kWh per person per day in OECD countries and 7 kWh in non-OECD countries.**

70 The UK must halve its transport CO<sub>2</sub> emissions between 2015 and 2030 to meet national carbon budget commitments [23]. Emissions have increased though, and the share of renewable energy in UK transport has fallen to 4.2% versus a target of 10% [29], bringing calls for stronger action [30]. Hydrogen represents one of three main options for low-carbon transport alongside biofuels and electric vehicles (EVs). Hydrogen avoids the land-use and air quality impacts of biofuels, and the limited range and long recharging times associated with EVs [5]. However, electric cars are several years ahead of hydrogen in terms of maturity due to their lower costs and readily-available infrastructure. Plug-in electric vehicles now account for 30% of new vehicle sales in Norway and 2% in the UK [31, 32].

80 In addition to tackling climate change, hydrogen vehicles can improve air quality. This is an urgent priority with over half a million premature deaths per year across Europe due to particulates and NO<sub>x</sub> emissions [33, 34]. The direct cost of air pollution due to illness-induced loss of production, healthcare, crop yield loss and damage to buildings is around €24bn per year across Europe with external costs estimated to be €330–940bn per year [35]. 92% of the world's population are exposed to air quality levels that exceed World Health Organisation limits [36, 37]. Major cities have

85

recently announced bans on all diesel-powered cars and trucks by 2025 [38], and UK and France have announced nationwide bans on all pure combustion vehicles by 2040 [39, 40].

## 2.1 Hydrogen powertrains

Conventional internal combustion engines can be modified to run on pure hydrogen ('HICEs') and could see early deployment as they are substantially cheaper than fuel cells. However, hydrogen combustion is less efficient than a fuel cell and releases NO<sub>x</sub>, hence is not expected to play a significant long-term role in transport. Hydrogen can be blended with natural gas ('hythane') or diesel in dual-fuel vehicles; or it is possible to switch between both in bi-fuel powertrains. This allows the use of existing infrastructure, but these are not zero-emission and could eventually be displaced by lower-carbon options [41].

Fuel cell electric vehicles (FCEVs) predominantly use PEM fuel cells, offering high efficiency, high power density and cold-start capabilities [42]. A 60 kW fuel cell is typical for European cars [43], which is substantially larger than for residential fuel cells (~1 kW). Competing powertrains includes conventional internal combustion engines (ICEs), battery electric vehicles (BEVs) and plug-in hybrid vehicles (PHEVs, also known as range-extender EVs), which allow most journeys to be completed using a battery, and switch to the engine or fuel cell for less-frequent longer journeys [44].

Hydrogen powertrains are compared to alternatives in Table 1, and differ in the following ways [42, 45]:

- 1. Capital cost:** FCEVs have higher capital and operating cost than BEVs today: \$60–75k for the Toyota Mirai or Hyundai ix35 [46, 47] versus \$25–30k for the Renault Zoe or Nissan Leaf [48, 49]. However, FCEVs have the potential for considerable cost reduction as manufacturing volumes rise, and could end up as cheaper alternatives [5, 43].
- 2. Range and refuelling time:** FCEVs have longer driving ranges and shorter refuelling times than BEVs, comparable to conventional vehicles (c. 500 miles and 3 minutes) [42]. The power-hungry computers and sensors in driverless cars will impact BEV range more than FCEV [50], as does the air conditioning / heating for vehicles in hot / cold regions.
- 3. Infrastructure requirements:** Hydrogen filling stations can serve substantially more vehicles than EV chargers, and a wider radius due to greater FCEV range [51]. Hydrogen refuellers are currently more expensive than electric charging posts: around \$1.5m versus <\$1,000 for slow chargers) [4, 52-54], although costs are expected to fall by two-thirds once the technology matures [7, 41].
- 4. Lifetime:** Battery lifetimes are affected by local climate, overcharging, deep discharge and high charging/discharging rates [55]; Tesla expect batteries to last 10–15 years, yet most BEVs are <5 years old so such lifetimes are unproven [44]. In contrast to batteries, hydrogen tanks can undergo fast refilling and frequent, deep discharging without compromising lifetime, and fuel cell stacks are expected to outlive other drivetrain components [56].


5. **User experience:** FCEVs offer a smoother driving experience than ICEs (quieter, less vibration and no gear shifting) [57]. However, hydrogen tanks are large and inconveniently shaped, potentially restricting luggage space.
6. **Emissions:** FCEVs have zero emissions at point of use and are low-carbon at the point of production if made from renewable-powered electrolysis, biomass or fossil fuels with CCS. The same is true for BEVs, whereas there is limited decarbonisation potential for ICEs. Blending biofuels with petrol and diesel can reduce CO<sub>2</sub> emissions, but not improve local air quality.
7. **Network requirements:** FCEVs and refuelling infrastructure can avoid the electricity network upgrades required for significant BEV penetration, and offer valuable grid-balancing services.
8. **Safety:** FCEVs have comparable, but different, safety considerations to BEVs and ICEs. Hydrogen is flammable (more so than petrol) but hydrogen fires can cause little damage to the vehicle due to their localised nature [42].

**Table 1: Comparative performance of primary drivetrains. Symbols give a qualitative comparison between different performance metrics (low / medium / high). Data from [42].**

	ICE	FCEV	BEV	
<i>Lower is better</i>	Current Capital Cost	\$	\$\$\$	\$\$
	Fuel cost	\$\$	\$\$\$	\$
	Maintenance costs	\$\$\$	\$	\$
	Infrastructure needs	\$	\$\$\$	\$\$
	Emissions	●●●	●	●
<i>Higher is better</i>	Efficiency	*	**	***
	Range	***	***	*
	Refuelling speed	***	***	*
	Lifetime	***	***	**
	Acceleration	**	***	***

## 2.2 Passenger cars

Deep decarbonisation of transport must focus on private cars, which account for around half of the global transport sector (Figure 2). FCEVs are currently expensive, but several analyses suggest cost reductions from mass-production could see their total cost of ownership (TCO) converging with other principal powertrains by 2030 (Figure 3) [4, 7, 13, 43, 58, 59].



150 **Figure 3: Total cost of ownership for major powertrains from [43]. Hydrogen, electric and fossil-fuelled vehicle lifetime costs are expected to converge by 2030.**

Passenger FCEVs are believed to require production volumes of around 100,000 units per year (and hence considerable financial support) to approach cost parity. With global passenger car sales of ~70 million per year, this small penetration represents a sizeable market [60]. If cost parity is achieved, other key aspects relating to user experience may make FCEVs favourable: 78% of automotive executives believe faster refuelling will make FCEVs the breakthrough for electric mobility, whilst BEV recharging times will remain an insuperable obstacle to acceptance [61].

160 Deployment could be accelerated by targeting powertrain configurations with smaller initial hurdles. These include range-extender EVs (FC RE-EVs), where smaller stacks (<20 kW) and lower fuel consumption mean FC RE-EVs can be competitive at smaller volumes [7].


165 Toyota, Hyundai and Honda now produce FCEV passenger vehicles, with Audi, Mercedes-Benz and others expected to follow suit [62]. Whilst FCEVs are offered in only a few countries due to infrastructure requirements, around 3,000 FCEVs have been sold to date (see Section 6.1). Deployment is expected to accelerate, with thirteen companies forming the Hydrogen Council in January 2017 and pledging to invest \$1.75 billion p.a. [63]. Longer term, the IEA concludes that FCEV sales could reach 8 million by 2030 in developed nations, and 150 million sales and a 25% share of road transport by 2050 [4].

## 2.3 Refuelling stations

175 A complication for passenger vehicles is the need for extensive expansion of refuelling infrastructure to offer the reach and freedom of conventional vehicles [51]. Battery electric vehicles face this to a lesser extent due to the lower cost of electric chargers: the UK has rapidly developed 5,000 electric charging locations to rival its 8,500 petrol stations, compared to just 15 hydrogen stations [64, 65]. While 15 hydrogen dispensers could deliver comparable throughput to 900 BEV fast-chargers, they do not offer the same geographic coverage and convenience.



180 Globally, there are 330 hydrogen refilling stations as of 2018, half of which are in Japan and the US  
[66] (Figure 4). The various European H2Mobility programs have suggested a rollout of refuelling  
stations at critical locations, with a network of 65 refuelling stations for the UK by 2020 to start the  
market, growing to 1,150 stations by 2030 to cover the whole country [67]. The Hydrogen Council  
185 targets 3,000 refilling stations globally by 2025, sufficient to provide hydrogen for about 2 million  
FCEVs, after which refuelling infrastructure should be self-sustaining [59]. National roadmaps only  
target around half this number though (see Section 6.1).



190 **Figure 4: Map of the hydrogen filling stations currently in operation and planned. The map  
focusses on the existing stations in the northern hemisphere, a further 8 stations are not plotted.  
Data from [www.h2stations.org](http://www.h2stations.org) by LBST and TÜV SÜD [66].**

Return-to-base fleets such as delivery vans and taxis, or passenger cars in a future car-sharing  
economy will see high utilisation and benefit from single refuelling depots with fast, infrequent  
195 refuelling. The requirement for less infrastructure could enable distribution costs to fall more rapidly  
than in the passenger FCEV sector, suggesting deployment in these sectors should be targeted [7].  
Urban taxis are another promising early market: new London taxis must be zero emission capable  
from 2018 [68], and Paris will purchase 60 new FCEV taxis with plans for hundreds more [69].

200

## 2.4 Other road transport

Whilst FCEVs face strong competition from ICE and BEV passenger cars, they may be the best (and  
perhaps the only) realistic zero-carbon option for high-utilisation, heavy-duty road transport vehicles  
such as buses and trucks. These are significant sectors, accounting for a quarter of transport energy  
205 usage (Figure 2 earlier). Growing calls to minimise urban air and noise pollution are major drivers for  
hydrogen bus rollout [57]. Back-to-base operation means fewer refuelling stations are needed and  
are more highly utilised, reducing initial refuelling costs.

Three key differences for heavy-duty transport are low manufacturing volumes (meaning the cost gap  
with ICE is smaller), and the need for greater longevity and energy density. The US DOE targets  
210 25,000 hour operating lifetime for fuel cell buses, versus just 8,000 for passenger cars [70, 71].  
Greater vehicle weight and driving range mean battery technologies are likely to remain unsuitable  
outside of urban environments; for example, fuel cell buses consume 10 times more hydrogen per  
kilometre than passenger cars – amplifying range limitations [72, 73].

215

## 2.4.1 Fuel cell buses

220

Fuel cell buses in particular have attracted significant attention and are relatively mature, at Technology Readiness Level (TRL) 7 [74]. On-board tanks typically hold around 40 kg of hydrogen stored in the bus roof [41], and reduced space restrictions mean this can be stored at 350 bar, reducing tank and compression costs. Fuel cell buses may have a 10–20% higher total cost of ownership (TCO) than diesel by 2030, and could be cheaper if deployed at scale [75].

225

Fuel cell buses have seen substantial early deployment, with 7 million kilometres of operational experience so far in Europe [76]. Europe has 83 operating fuel cell buses, with 44 in North America [77, 78]. Toyota is planning to introduce over 100 fuel cell buses before the Tokyo 2020 Olympic Games [79]. China has the world's largest bus market [80], with 300 fuel cell buses ordered for Foshan City (quadrupling the global fleet of hydrogen powered buses) [81]. For context though, Shenzhen City has electrified its entire fleet of over 16,000 buses using BEVs [82].

230

Good progress is being made with longevity, with four London buses operating more than 18,000 hours [77]. Ten buses in California have passed 12,000 hours of operation with one reaching 22,400 hours: close to the DOE's ultimate target of 25,000 hours [70, 72]. Fuel cell bus availability has exceeded 90% in Europe (versus an 85% target), with refuelling station availability averaging 95% [77].

235

## 2.4.2 Trucks

240

Trucks show considerable potential for fuel cell adoption as high energy requirements mean few low-emission alternatives exist. Light goods vehicles with short low-speed journeys could be managed with batteries and range-extender vehicles [41]; however, long-haul heavy vehicles which require high utilisation are likely to require hydrogen. Competition from batteries is nonetheless increasing, with the Tesla Semi expected to offer 300–500 mile range for ~\$200,000 [83]. Cost parity of fuel cell trucks with other low-carbon alternatives could be achieved with relatively low manufacturing volumes [7]. Return-to-base delivery vehicles could see lower fuel costs with a single refuelling depot, although long-range HGVs need an adequate refuelling network.

245

Higher longevity is required than for other applications due to the high mileage expected of trucks, with one program targeting 50,000 hour stack lifetime [41]. High efficiency and low fuel costs are also essential [4]. Kenworth and Toyota are considering hydrogen truck production [84, 85], and Nikola is also developing a long-distance HGV using liquefied hydrogen in the US [86]. Fuel cells are also being developed as Auxiliary Power Units (APUs) for HGVs [41]. These could power refrigeration units and 'hotel' loads on stationary HGVs (e.g. cabin heating, cooling, lighting, and electrical devices) to avoid engine idling [87].

250

255

FCEV trucks have seen lower adoption than buses due to the HGV market being highly cost sensitive with limited government support or intervention, and highly conservative with hauliers wary of being pioneers [41]. Interest could grow as diesel trucks begin to be banned from the centres of major cities [38].

### 2.4.3 Motorbikes

260 Motorbikes and scooters are dominant passenger vehicles in many regions, and Intelligent Energy has developed a 4 kW fuel cell system in cooperation with Suzuki [41], now being trialled in the UK [88]. Their low fuel consumption allows them to be refuelled using hydrogen canisters from vending machines. FCEV motorbikes could contribute toward air quality and noise pollution targets.

## 2.5 Off-road transport

### 2.5.1 Trains

265 Electrification can replace diesel trains but progress has slowed recently across Europe [41]. Hydrogen trains could be used on routes which are difficult or uneconomic to electrify due to route length or lack of space in urban areas. A fuel-cell powered train with roof-mounted hydrogen tanks and a range of 500 miles has begun testing in Germany [89], and 40 trains could be in service by 270 2020 [90]. Light rail also presents opportunities for hydrogen, with fuel cell-powered trams being developed and operated in China [7, 91]. Low volumes mean that hydrogen trains are expected to use the same stacks and storage tanks as buses and trucks, so cost reductions will be consolidated with the automotive sector. Hydrogen powertrains may be 50% more expensive than diesel, but economic viability will depend on lower-cost fuel, and hydrogen costing under \$7/kg [7]. One study 275 concludes that FCEV trains are already cost competitive with diesel trains from a TCO perspective [59].

### 2.5.2 Shipping

280 Marine applications hold promise for hydrogen deployment, with fuel cells already being used for propulsion in a handful of projects including ferries [7, 41]. Hydrogen is not expected to gain traction until after 2030, although the growth of emissions controlled zones (such as the Baltic Sea and urban ports) and hydrogen's higher efficiency than LNG could drive early niches [41]. Most vessels have long lifetimes, are built in small numbers highly tailored to specific applications; this could hamper the rollout of new propulsion systems [7]. With ferries potentially consuming 2,000 kg of hydrogen 285 per day, cryogenic storage is necessary, and fuel costs are more important than upfront capital, with hydrogen significantly below \$7/kg needed [7, 92]. Fuel cells for auxiliary power could be adopted earlier than for propulsion [41], and port vehicles could also be early adopters, improving local air quality with a single refuelling depot.

### 2.5.3 Aviation

290 Aviation is one of the hardest sectors to decarbonise, and reducing emissions from aircraft propulsion has seen little progress. In 2016 the International Civil Aviation Organization agreed to cap aviation emissions at 2020 levels, but primarily through carbon offsetting rather than low-emission fuels [93]. Some hybrid electric concepts are being studied, though emission reductions 295 will be limited [94]. Biofuels could be suitable due to their higher energy density than hydrogen or batteries, but are not completely emission-free and could remain costly with limited availability. Hydrogen could be used as a propulsion fuel, but needs to be liquefied to supply the required range. Combustion turbines are likely to be needed as fuel cells lack the power required for take-off.

300 However the climate benefits of hydrogen for aviation have been questioned because it produces  
more than double the water vapour emissions of kerosene; water vapour at high altitudes, although  
short lived in the atmosphere, causes radiative forcing and thus contributes to net warming [95].  
Significant hydrogen deployment is thought unlikely before 2050 except perhaps for small or low-  
flying aircraft [41]. Hence much work remains on developing options for low-emission aircraft  
propulsion.

305 Other aviation-based sectors are more promising. Fuel cells have been tested for aircraft auxiliary  
power units and for taxiing aircraft to/from airport terminals [96]. There is an increasing motivation  
to improve air quality around airports and fuel cells could play an important role in powering ground  
vehicles and buses in the next 10 to 20 years [41], aided by the need for a low number of refuelling  
310 stations experiencing high utilisation. Unmanned aerial vehicles (UAVs) are also attracting  
considerable interest for both civilian and military applications [7]. Fuel cell UAVs are quieter, more  
efficient, and have lower vibration and infrared signatures than fossil fuel-powered UAVs, and are  
lighter than battery systems, offering longer range. Fuel cell UAVs are currently considerably more  
expensive than battery UAVs; but the cost gap will close with manufacturing volume, and fuel cells  
315 retain the advantage in long-duration or high energy applications [7].

#### 2.5.4 Forklift trucks and others

Other promising off-road applications include forklift trucks, with around 12,000 fuel cell units  
deployed in the US and a handful elsewhere [97]. Plug Power supplies 85% of FC forklifts in the US  
320 [98]. The zero emissions from FC forklifts allow them to operate indoors, and their faster refuelling  
than batteries can lead to TCO savings of 24% in a typical high throughput warehouse [99]. FC  
forklifts also have a wide temperature range, capable of operating in temperatures as low as -40°C.  
PEMFCs are most widely used with longer lifetimes, but direct methanol fuel cells (DMFCs) are also  
found in lower usage applications with shorter lifetimes and lower cost of ownership [98]. Fuel cells  
325 could also see adoption in agricultural equipment such as tractors [100] and recreational  
applications such as caravan APUs and golf carts, one of the few sectors where manufacturers are  
returning a profit [80].


## 3 Heat and industry

330 Heat and hot water accounts for 60–80% of final energy consumption in residential and commercial  
buildings across Europe [101, 102]. Emissions from heating need to be reduced rapidly and largely  
eliminated by 2050; however, the heat sector is proving hard to decarbonise for several reasons [103,  
104]:

- 335 1. Heating is the largest energy demand in many temperate countries and presents a problem of  
scale;
2. Requirements are diverse, ranging from dispersed low temperature space heating to large  
high-temperature industrial loads, with no one solution capable of meeting all heat demands;
3. Heat demand varies daily and seasonally, requiring highly flexible supply [105];
- 340 4. Fossil heating fuels provide this flexibility at a lower cost than low-carbon alternatives less  
competitive and risk increasing energy poverty [106].

A particular challenge for low-emission heating in temperate countries is meeting winter peak heat  
demand [107-109], which is considerably higher and more variable than peak electricity demand  
(Figure 5 and Figure 6). This strong seasonal variation is easily met by prevailing gas heating  
345 technologies, as low per-kW capital cost means they are routinely oversized for buildings [105], and  
the gas network (including geological storage) can store a month's worth of consumption [108].

Improved insulation, residential or communal thermal storage, and more efficient conversion devices  
could reduce peak requirements, but require strong regulation which has not been forthcoming [108].  
350 Alternative low carbon options such as electrification or district heating could meet peak heat  
demand but large infrastructural investment would be required, and a decarbonised gas-based  
approach may be more cost-effective.



355 **Figure 5: Demand for the major energy vectors in Britain [110].**




Figure 6: Variation in British household heat demand between classes of housing for an average year. Heat demand includes space and water heating. Consumption is strongly temperature-dependent and winter peaks can be much higher in a cold year [109].

360

Hence progress in decarbonising heating has lagged severely behind other sectors. For example, the UK relies heavily on natural gas and is likely to miss its 2020 target for renewable heat [29, 111]. It may only achieve emission reductions from buildings and industry of around 20% by 2030, compared to an overall target of 57% [23]. Natural gas is currently a cheap, convenient and relatively clean alternative to coal and oil, and is the dominant fuel for heating in many countries, as shown in Figure 7. Electric heat pumps are well established in Asia, America and parts of Europe, with over a billion systems heating homes [112]; whilst district heating is widely used in Russia and Scandinavia [113].

365

370




Figure 7: The share of fuels used for domestic heating in ten countries, estimated using the DESSTINEE model [114] with data from the IEA [115]. Biomass includes both traditional (wood, dung) and modern (wood and miscanthus products); Heat is generated off-site and sold to users; Electricity includes both traditional (resistance and night-storage heaters) and modern (heat pumps).

375

## 3.1 Options for low-carbon heat

Five main options have been proposed for decarbonising heat globally [108, 116-119], as summarised in Table 2 and below. Most of these have gained traction in specific countries, but none are widely used on a global scale. The main options are:

**1. Demand reduction.** Insulation, higher efficiency devices and changing demand behaviour (e.g. via smart meters and pricing) can all reduce heating energy demand. Residential heat consumption could fall 20% by 2050 [108], which is a valuable contribution and an enabler for other low-carbon heating technologies, but insufficient in isolation. Barriers to greater reduction include 80–90% of the 2050 housing stock having already been built in developed countries [111]; some properties being unsuitable for retrofitted insulation; and household size (people per building) shrinking due to lifestyle choices [114].

**2. Green gas.** Natural gas could be replaced by a low-carbon gases, utilising the existing gas network assets and potentially reducing costs and disruption [120]. Biogases can be generated by anaerobic digestion or gasification of waste, sewage, landfill gas, energy crops, etc. However, barriers to large-scale delivery include: resource availability and priority (it could be used in various energy/product routes); emission reduction potential; local emissions; and gas quality. The UK Bioenergy Strategy therefore limits heating uptake to 15% [108]. An alternative is hydrogen, which can be injected into the existing gas network in small quantities, or the existing gas network can be converted to distribute 100% hydrogen rather than natural gas (Section 5.4).

**3. Electrification.** Heat pumps are widely used in many countries, and globally could deliver an 8% reduction in CO<sub>2</sub> emissions if widely adopted [112]. However, their low-grade heat and limited output may not meet peak winter demand and consumer preferences, and high uptake may force electricity network upgrades [121]. High upfront costs restrict uptake, although these might fall as rollout progresses. Nevertheless, heat pumps may play an important role, particularly for rural homes too remote for district heating or gas networks, which use expensive high carbon fuels such as heating oil, and with space for larger systems [120]. Electric heating is also well suited to high density urban housing blocks where gas is not allowed for fire safety, and space heating requirements are lower [120].

**4. Heat networks.** District heating is only commonplace in a handful of countries, which typically combine a cold climate with an acceptance of collective solutions. It has the potential to provide 10–20% of residential heat by 2050 in densely populated countries such as the UK [108, 122]. Retrofitted heat networks are capital-intensive and disruptive to install, and heat losses limit transmission distances to around 30 km [123]. They are best suited to urban new-build, but offer 30% lower heating costs than gas boilers [107]. They can use geothermal heat or waste heat from industry and data centres. Large district heating CHP schemes are cheaper and more efficient than individual residential systems.

**5. Onsite renewables.** Modern renewable energy produces 9% of the world's heat, nine-tenths of which is biomass, and the remainder solar thermal and geothermal [21]. However, there are concerns over the limited availability and high localised emissions of biomass, poor matching between solar

thermal production and demand [108, 124], and cost and performance penalties of small-scale residential systems [125].

425

**Table 2: Summary of the decarbonisation options for heat.**

	<b>Advantages</b>	<b>Disadvantages</b>
<b>Demand Reduction</b>	<ul style="list-style-type: none"> <li>+ Insulation and more efficient devices raise consumer awareness</li> <li>+ Reduction to energy bills</li> <li>+ Low-regret option</li> </ul>	<ul style="list-style-type: none"> <li>– Low turnover rate of building stock</li> <li>– Difficulty retrofitting existing buildings</li> <li>– Consumer indifference / apathy</li> </ul>
<b>Green Gas</b>	<ul style="list-style-type: none"> <li>+ High customer satisfaction / familiarity</li> <li>+ Low cost for gas appliances</li> <li>+ Easily meets peak demand</li> <li>+ Low conversion cost and disruption</li> </ul>	<ul style="list-style-type: none"> <li>– Gas is difficult to decarbonise</li> <li>– Limited availability and need for cleaning</li> <li>– Hydrogen networks unproven, with uncertain availability, costs and safety implications</li> </ul>
<b>Electrification</b>	<ul style="list-style-type: none"> <li>+ Proven and widely used in many countries</li> <li>+ Benefits from further decarbonisation of electricity systems</li> <li>+ Well suited to countries with mild winters</li> <li>+ Good option for remote rural properties not on gas or heat networks</li> </ul>	<ul style="list-style-type: none"> <li>– Could necessitate power system upgrades</li> <li>– Difficulty meeting peak demand without greater building thermal efficiency.</li> <li>– Higher cost, higher space requirements</li> <li>– May require heat storage</li> <li>– Performance sensitive to installation quality</li> </ul>
<b>Heat Networks</b>	<ul style="list-style-type: none"> <li>+ Proven and widely used in some countries</li> <li>+ Could meet ~10-20% of UK heating needs</li> <li>+ Good option for new-builds and densely-populated regions</li> </ul>	<ul style="list-style-type: none"> <li>– High conversion cost and disruption</li> <li>– Heat cannot be transported long distances</li> <li>– Needs low-carbon heat sources</li> <li>– User scepticism</li> </ul>
<b>Onsite Renewables</b>	<ul style="list-style-type: none"> <li>+ Use local energy sources</li> <li>+ Reduces network dependence and upgrade requirements</li> </ul>	<ul style="list-style-type: none"> <li>– Small schemes less cost-effective</li> <li>– Limited availability and high emissions (biomass)</li> <li>– Poor match to demand (solar thermal)</li> </ul>

Each low carbon heating technology exhibits barriers or uncertainties associated with technical feasibility, cost, suitability across regions and building types, user acceptance and safety. Individual countries are often dominated by a single technology. The UK has an 84% penetration of gas, although this is a recent development (Figure 8). In the US, 97% of new family homes are either heated by natural gas or electricity [126]. Previous studies have therefore focussed on widespread rollout of a single technology to meet decarbonisation needs [127].

430

However, a portfolio of complementary heating technologies used to be more prevalent, and is now regaining recognition [109]. For example fuel cell CHP systems can export electricity to the grid at the same time as heat pumps consume it; a UK case study found that a 50% penetration of fuel cell micro-CHP could completely offset the electrical demand from a 20% penetration of heat pumps [109]. The UK recognises the lack of consensus on the optimal technology mix to deliver the required long-term changes, and the need to thoroughly re-assess the evidence and test different approaches [107]. This technology mix could vary according to regional availability and building type and provide a hedge against uncertainties over technology feasibility and fuel prices.

435

440






Figure 8: The mix of heating technologies used in UK households over forty years [128].

445

## 3.2 Hydrogen and fuel cell technologies

Until recently, most energy systems and building stock models did not include hydrogen and fuel cell technologies for meeting decarbonisation targets [109]. However, recent studies have identified hydrogen as having an important role in decarbonising heat [108, 129], able to provide the majority of UK heat demand by 2050 [41]. There are several H<sub>2</sub>FC technologies to deliver heating.

450

### 3.2.1 Hydrogen boilers


Existing gas boilers and furnaces can run on hydrogen mixtures at low levels (see Section 5.4.4). Although high concentrations have a similar Wobbe index to natural gas, different burner tips are required due to hydrogen's higher flame speed [130]. Catalytic boilers are also under development, which eliminate NO<sub>x</sub> formation [41] but are less powerful and require higher purity hydrogen [131]. Consequently, a changeover to hydrogen would require wholesale refitting of either appliances or components within appliances. Such a wholesale refitting of appliances is not unprecedented: many countries have switched from town gas to natural gas in recent decades, with the UK replacing 40 million appliances, at a cost of £8bn in 2015 money, over an 11-year conversion programme [131].

460

### 3.2.2 Fuel cell CHP

Combined heat and power (CHP) systems co-produce electricity and heat at high efficiencies via engines or fuel cells and may use a variety of fuels [25]. The balance between electrical and thermal generation varies between technologies (Figure 9). Combustion devices (IC engines and Stirling engines) generate more heat than electricity so are better suited to large buildings with high heat loads, but release particulates and NO<sub>x</sub> [132].

465



470 **Figure 9: Thermal and electrical efficiencies of CHP devices [133]. The ‘thermal efficiency’ of heat pumps is their coefficient of performance (COP) [112] multiplied by the efficiency of power generation.**

475 All CHP technologies offer greater combined efficiency than the ‘traditional frontier’ of using average power stations and condensing gas boilers. Only fuel cell CHP can exceed the efficiency of the ‘all-electric frontier’ of using the best combined-cycle gas power stations with the best ground-source heat pumps [133]. Fuel cell CHP systems have higher electrical efficiency and lower emissions (Table 3) than other CHP. PEMFCs and SOFCs are typically used for domestic systems, and SOFCs, PAFCs and MCFCs for larger commercial systems [109]. Given their higher power-to-heat ratio, fuel cells are more suitable for well-insulated buildings with lower heat loads. FC-CHPs are currently expensive, but costs have halved in the last six years and lifetimes have grown with increasing rollout in Japan and also more recently in Europe [134]. Existing CHP systems mostly operate on natural gas, but could switch to hydrogen if available with little modification (or even simplification).

485 **Table 3: At-a-glance summary of fuel cell CHP performance [133, 135].**

		PEMFC	SOFC	PAFC	MCFC
<b>Application</b>					
<b>Electrical capacity</b>	(kW)	0.75–2	0.75–250	100–400	300+
<b>Thermal capacity</b>	(kW)	0.75–2	0.75–250	110–450	450+
<b>Electrical efficiency*</b>	(LHV)	35–39%	45–60%	42%	47%
<b>Thermal efficiency*</b>	(LHV)	55%	30–45%	48%	43%
<b>Expected lifetime</b>	(‘000 hrs)	60–80	20–90	80–130	20
	(years)	10	3–10	15–20 <sup>†</sup>	10 <sup>†</sup>
<b>Degradation rate<sup>‡</sup></b>	(per year)	1%	1–2.5%	0.5%	1.5%

\* Rated specifications when new.

<sup>†</sup> Loss of peak power and efficiency

<sup>‡</sup> Requires an overhaul of the fuel cell stack half-way through the operating lifetime.

490 Figure 10 visualises how prices are falling with increased uptake for some technologies (residential PEMFCs in Asia), but have stagnated for others (large MCFC and SOFCs in the US). Prices are

converging at around \$10,000 per kW; a price point which solar PV modules reached in 1990 [136]. Other issues such as product lifetime and reliability have improved significantly, to the extent that a fuel cell CHP unit is now equivalent in both these respects to a modern gas-fired boiler [137-142].

495




Figure 10: Learning curves fitted to historic prices of Japanese and Korean residential PEMFCs [134, 143, 144], American SOFCs and MCFCs [145, 146]. The year for the first and last data point in each series is shown. Each doubling in production has seen prices fall by 16% for EneFarm in Japan; by 21% for Korean residential PEM generators; by 5% for 250 kW-class MCFCs in the US; and increase by 2% for 200 kW-class SOFCs in the US.

500

### 3.2.3 Other technologies

Other heat technology options include gas-driven heat pumps (GDHPs), where the heat pump is powered by an engine, which could run on hydrogen. GDHPs currently achieve energy savings of 26–43% compared to condensing boilers, and avoid upstream complications from increased electricity demand [108]. Tens of thousands of non-residential GDHPs have been sold across Europe and Asia; costs are currently high, but should come down significantly [108, 109]. Hybrid heat pumps are another option, with electric heat pumps providing the majority (60–95%) of a building’s annual heat demand, but with a gas boiler retained for meeting peak demand [108]. Several studies have identified hybrid heat pumps as suitable for many buildings in 2050 [41, 108, 109]; though such systems require additional capital expenditure and connection to both electric and gas networks. Wall-mounted fires are waning in popularity, but several hydrogen-powered fireplaces have been designed [131].

515

There is considerable scope for hydrogen usage as a cooking fuel, with burners and barbecues under development today [109]. Hydrogen for cooking will need food-safe odourants and colourants, and will alter cooking times as hydrogen produces about 60% more water vapour than natural gas when burnt [131].

520

### 3.3 Residential and commercial heating

Residential fuel cells have seen significant uptake, and now have the largest market share for micro-CHP systems [7], with over 225,000 systems installed globally (see Section 6.1). PEMFCs are the dominant technology with high efficiency, durability, reliability, rapid start-up and shut-down, part-load capability and operating temperatures of around 80 °C [25, 109]. Their electrical efficiency is lower than other fuel cells (~35%), but with higher thermal efficiencies (55%) [134]. Their low-temperature heat output makes them suitable for individual buildings. About 7% of Japan's systems are SOFCs [147], which tend to run constantly as start-up and shut-down times can exceed 12 hours [109]. They have higher electrical efficiency (~40–60%), greater fuel flexibility, reduced purity requirements, reduced catalyst costs due to higher operating temperatures, and higher temperature heat which is more suitable for existing building stock with smaller radiators [7].


The cost of residential systems is dominated by capital and stack replacement costs, with small systems used to maximise utilisation [41]. Fuel cell micro-CHP could be cost competitive with other heating technologies between 2025–2050 [109, 148], with fuel costs becoming dominant. Larger multi-family home and commercial units (2–20 kW<sub>e</sub>) could be competitive at smaller production volumes, but have a smaller market [7].

CHP systems are also popular in the commercial sector, with 100s of MWs installed globally, primarily in the US and South Korea [7]. MCFC and PAFC fuel cells dominate commercial systems with stable operation, cheaper catalysts and high efficiencies, although their complex subsystems do not scale down well for smaller applications (e.g. needing to remain heated whilst off to prevent electrolyte freezing). MCFCs have higher electrical efficiencies (>50%) with correspondingly lower heat production; however, they are inflexible with short lifetimes (20,000 hours) and high degradation rates due to corrosive electrolytes (Table 3). Their reliance on carbon dioxide for fundamental electrode reactions also make them unsuitable for operating on hydrogen [41], but opens up new possibilities for carbon capture and storage [149]. PAFCs have a lower electrical efficiency than MCFCs but a higher thermal and overall efficiency (Table 3). They last longer (80,000–130,000 hours) with lower degradation rates and are more flexible, giving scope for load-following capability [7]. PAFCs could potentially be cost-competitive with ICE-CHP by 2025 at relatively low production levels of 100 units per year [7].

FC-CHP systems are quiet and low-emission making them ideal for urban areas [106]. Fuel costs are a major component of the Total Cost of Ownership (TCO), driving improvements in efficiency [7]. PEMFC and SOFC also see some uptake in commercial applications.

### 3.4 Industry

Industry relies on fossil fuels for three-quarters of its fuel mix [20], and accounts for one fifth of direct global greenhouse gas emissions (see Figure 11), with very little progress on decarbonisation to date. Hence low-carbon options for industry need to be identified urgently; options identified to date include CCS, biomass as a fuel, electrification, energy efficiency and heat recovery, industrial clustering and switching to hydrogen – noting it can be both a fuel and feedstock [7]. Long equipment lifetime and investment cycles in conservative sectors mean change will be slow.



565 **Figure 11: Carbon emissions from industry, broken down by fuel. Global emissions (including those from electricity production) were 12 GtCO<sub>2</sub> in 2014, 37% of the global total. Data from [150].**


Hydrogen is already widely used in industry as a chemical feedstock (e.g. in ammonia production and oil refining) and produced as a by-product in chemical manufacturing processes (e.g. chlorine),  
 570 rather than as an energy vector [109, 123]. Hydrogen could replace natural gas as a fuel for providing heat and power in a number of industries; burners and furnaces may need replacement, but would not require high purity. Hydrogen could also be introduced into several high-temperature industries including steelmaking and cement, although commercialisation is not expected before 2030 due to low maturity, uncertain costs, the likelihood of needing fundamentally redesigned plant and the slow  
 575 turnover of existing systems [7, 41]. Industry requires cost-effective and reliable systems, with purchasing decisions based primarily on technical performance and economic rationality; space constraints and aesthetic concerns can be largely ignored [109].

## 4 The power system

580 Global electricity consumption has doubled since 1990 and represents 40% of primary energy demand [115, 151]. Fossil fuels produce two-thirds of global electricity, emitting 15 GtCO<sub>2</sub> each year, or 42% of the global total [152]. National roadmaps [23, 153] and international modelling studies [116, 154, 155] agree that electricity should be rapidly decarbonised during the 2020s and then push forwards the decarbonisation of transport and heating through electrification.

585 Unlike other sectors, electricity generation has available a range of low-, zero- and even negative-carbon alternatives already available. The IPCC recommends that low-carbon generation rise from around 30% of total generation today to over 80% by 2050 [156]. This radical shift appears feasible: Figure 12a shows that wind and solar power have seen ten-fold growth over the last decade to total 590 665 GW: 11% of global generating capacity [151].

Wind and solar power are forms of intermittent renewable energy: their output cannot be fully controlled or predicted as they rely upon the weather. Balancing supply and demand requires new solutions if electricity systems are to fully decarbonise whilst maintaining current levels of cost and reliability. Electricity has the fundamental constraint that supply must always balance demand [157], and system reliability is paramount as outages cause severe economic and social damage [158]. At the same time, electricity demand is anticipated to grow in both developing and developed countries, as the rise of electric vehicles and electric heating will exceed even the most stringent efficiency measures [114]. This will raise demand during cold winter evenings, when demand is already highest in temperate countries, thus adding to the difficulties of maintaining secure, affordable and clean electricity.



605 **Figure 12: Installed power generation capacity worldwide over the last 25 years (left) [151, 159], and global installed power capacity of stationary fuel cells (power-only and micro-CHP) (right) [160-162]. Annual growth rates since 2000 has been 52% for solar, 25% for fuel cells, 24% for wind, and 1-5% for other technologies.**

Hydrogen technologies are able to assist with both the integration and expansion of low-carbon electricity generation and with the electrification of heating and transport sectors. Power generation from hydrogen is gaining ground – global capacity reached the milestone of 1 GW in 2015, as seen in the bottom right corner of Figure 12a. Figure 12b shows that the installed capacity of stationary fuel cells has grown by 25% per year. If this were maintained, fuel cells would reach 10 GW capacity in 2025, and 30 GW in 2030. However despite this growth, no company has yet turned a profit through sale of stationary fuel cells [163].

615

## 4.1 Electricity generation

Fuel cells can benefit the electricity system in several ways: they are flexible, controllable, typically co-located with demand (minimising losses in transmission and distribution), and likely to generate when demand for electricity is highest if used for combined heat and power (thus helping to cope with peak demand). Additionally, hydrogen feedstock may be produced from power-to-gas, providing the large-scale long-term storage required to shift electricity from times of renewable surplus to those of shortfall.

It is important to note that the decarbonisation potential depends on the hydrogen feedstocks and supply chains. Any use of fossil fuel-derived natural gas to produce hydrogen (without CCS) will necessarily lead to carbon emissions that are at least at the level of a new CCGT power station.

625

### 4.1.1 Peak generation

With changes to turbine design, existing gas turbines can be converted to burn hydrogen rather than natural gas [164]. This is the hydrogen equivalent of business as usual: it allows grid operators continued access to low-cost thermal peaking plant and to operate much as they do now. Lack of hydrogen delivery infrastructure is an impediment, so the ETI suggests a system of on-site production and storage: a small steam-methane reformer (SMR) equipped with carbon capture and storage (CCS), a salt cavern for storage and a large open-cycle gas turbine (OCGT) [165]. The other key disadvantage is the low efficiency of combustion relative to electrochemical conversion (35–40% vs. 40–60%), giving high operating costs.

635

A key advantage of fuel cells is that they retain their performance at smaller scales. Parasitic loads and thermal losses mean the efficiency of other small-scale gas generators is at least a quarter lower than their larger (>10 MW) equivalents [166, 167]. In contrast, fuel cells can deliver electrical efficiencies that are comparable to the best combined-cycle gas power stations (~60%) from several hundred kW down to 1 kW residential units [133, 168]. Small, modular units can be co-located with centres of demand, saving on transmissions losses of around 7% in America and Europe [115], and allowing fuel cells to provide ancillary services to the grid operator.

645

### 4.1.2 Power-only and backup fuel cells

Power-only fuel cell systems (i.e. without combined heat and power) are gaining popularity, particularly with American technology firms and multinationals seeking a green image. The units

650 deliver cheaper electricity than local utilities (8–10 ¢/kWh versus 14 ¢/kWh [169]), and allow a move away from diesel engines as an uninterruptable power supply.

The Bloom Energy Server is a high-profile example, a 200 kW SOFC module that runs on either natural gas or bio-gas with an efficiency of 50–60% [168]. The first commercial units were installed at Google in 2008, and units can now be leased for either 10 or 15 years [170]. Bloom’s announced contracts outstrip those of its three largest competitors combined [171].

660 Energy Servers have received large subsidies from US green generation incentives (e.g. \$200 million in California in 2010 [172]) , but carbon savings are relatively low. The carbon intensity of SOFC using natural gas is 350–385 gCO<sub>2</sub>/kWh [168], compared to new combined-cycle gas turbines at 360–390 gCO<sub>2</sub>/kWh, or the average British electricity mix at below 250 g/kWh [173]. Power-only fuel cells therefore match the best conventional production technology, but require decarbonised fuel sources to offer further carbon savings. For comparison, the carbon intensity of electricity from fuel-cell CHP (with a credit for co-produced heat) with natural gas feedstock is in the range 240-290 gCO<sub>2</sub>/kWh [105], lower than the average electricity mix in most large countries.

665

### 4.1.3 Vehicle-to-grid

670 Electrification of the transport sector has the potential to exacerbate the peak power problem if the charging of vehicle batteries is unmanaged [174, 175]. The use of FCEVs rather than BEVs removes this issue, whilst also potentially delivering additional benefits. Private vehicles spend around 95% of the time parked, and so a large fleet of electric vehicles would provide grid operators with a reliable resource to call upon [174].

675 Vehicle-to-grid (V2G) describes a system for communication with electric vehicles, allowing grid operators and utilities to access the energy stored within electric vehicles to meet demand and provide other grid services [176]. In this system FCEV might be able to act as a distributed source of peak power and spinning reserve [177], though studies indicate that the economics for this scenario are marginal under current market conditions [178, 179]. The increasing value of balancing services as electricity systems move towards more variable renewables may radically alter this in the future [180].

685 A key barrier for drivers is the fear of being left ‘out of gas’ when an unexpected or emergency need to travel arises [181]. This ‘range anxiety’ is a key issue for BEVs due to range limitations, but not so for FCEVs as they could use their hydrogen tank for further top-up. For example, the Toyota Mirai, holds 5 kg of hydrogen, or 600 MJ of chemical energy (LHV basis). If this could be converted with 50% efficiency, then half a fuel tank would yield 40 kWh of electricity. With current battery technologies, the lifetime of a BEV would be reduced through participation in V2G, since additional charge/discharge cycles degrades the battery. Even with current lifetimes, it is expected that the fuel cell stacks would not be a chief determinant of lifetime in FCEVs [177, 181].

690



## 4.2 Electricity storage

With growing deployment of variable renewables and distributed generation, flexibility and control to balance supply and demand becomes increasingly valuable. There are already several technologies in various stages of maturity that allow the temporal shifting of electrical energy over time periods of hours to a few days (e.g. pumped hydro, batteries and compressed air electrical storage (CAES)). None of these can provide spatial redistribution of energy or storage on the week-month timescale that is required for balancing the output from wind generation [182, 183]. Hydrogen technologies have the potential to meet both these needs.

Power-to-gas (P2G) refers to the process of converting excess electrical energy into storable chemical energy in the form of either hydrogen or grid-compatible methane – a key form of ‘sector coupling’. Surplus electricity is used to power hydrogen production via water electrolysis. The resulting gas may then be stored and used when required, for instance by a fuel cell, or undergo further processing to produce methane, also known as synthetic natural gas (SNG). Equally, it can then be converted back to electricity or used to displace demand for natural gas in the heating (and power) sector, or indeed for transport. There are two commercially available processes for water electrolysis: alkaline electrolysis cells (AEC) and polymer electrolyte membranes (PEMEC); while solid oxide (SOEC) offers the possibility of high efficiency but are still at a development stage [184]. These technologies are described later in Section 5.1, and their market uptake is shown in Figure 13. Globally, 30% of P2G pilot plants now use PEMEC [185], and with rapid growth, prices are likely to fall to those of AEC by 2030 [186, 187].




Figure 13: Total installed power in existing power-to-gas pilot plants. Data from [188, 189].

### 4.2.1 Power-to-hydrogen or power-to-methane?

Power-to-hydrogen is superior to power-to-methane in terms of both process cost and simplicity [190]. In its most basic implementation, the process is being used to provide fuel for the rapidly-growing numbers of hydrogen filling stations. It is also the process in use in the majority of larger-scale P2G demonstration projects [188]. In the absence of a hydrogen distribution network, one key

issue is the storage of the gas once it has been produced. From the range of alternatives [191, 192], storage in high pressure tanks is currently the favoured option. Another solution is to inject the resulting hydrogen into the natural gas network, although blending may be limited to 10–20% at most as explained in Section 5.4.4.

725

Onward conversion of the hydrogen to methane is a less efficient and significantly more complex process. Methanation of hydrogen is achieved via either a catalytic [193] or a biological process [194], and requires a source of CO or CO<sub>2</sub>, plus compression and storage of the hydrogen feedstock. Overall, power-to methane has an efficiency in the range 49–65%, while power-to-hydrogen achieves efficiencies in the range 51–77% [195, 196]. The roundtrip efficiency of a power-to-hydrogen-to-power process is in the range 34–44%, while for power-to-methane-to-power it is only 30–38% [196]. Estimates indicate that the levelised cost of power-to-methane is 15–30% more than for simple conversion to hydrogen [185]. The advantage of power-to-methane is the ability to feed directly into existing gas infrastructure. Globally, the energy storage capacity of the natural gas network is in excess of 3600 TWh [197], approximately three times the global production from wind and solar power combined in 2016 [151]. The source of CO or CO<sub>2</sub> is obviously central to whether power-to-methane aids carbon emission reductions: only carbon derived from biomass or direct air capture will be carbon neutral. There is a growing number of power-to-methane pilot projects in progress globally [198], with Europe leading the way in driving forwards development of the technology.

730

735

740

## 4.2.2 Economics of power-to-gas

Several modelling studies have considered the economics of P2G under differing assumptions and scenarios [185, 191, 199, 200]. Several authors conclude that P2G is not profitable at present, nor in the near-term: the costs are too high and the regulatory environment is unhelpful [185, 201–206]. However, the studies show that P2G significantly reduces the need for curtailment of renewables [201, 204] and that, where the resulting hydrogen is injected into the gas grid, further benefits may be gained from reduced costs and improved performance of both the gas and electricity grids [202, 204]. The potential to exploit multiple revenue streams (e.g. selling H<sub>2</sub>, CH<sub>4</sub> or O<sub>2</sub>, providing ancillary services, heating, exploiting carbon levies, frequency control) improves the chances of profitability [185], as does operating the plant so that it only uses renewable energy that would otherwise have been curtailed. The common message is that falling electrolysis costs and altered national regulatory frameworks should render P2G profitable within 10–15 years [205].

745


750

Looking further ahead, several authors have examined the role that P2G might play in future national electricity markets with very high penetration of renewables. All studies indicate that P2G could play a pivotal role in balancing electricity systems once the penetration of VRE exceeds about 80%, in spite of the high cost and low efficiency [195, 203, 207]. With investment in hydrogen infrastructure, or increasing local demand for hydrogen, high-renewables scenarios envisage hundreds of GW of installed P2G capacity by the 2050s.

760

# 5 Hydrogen infrastructure

The development of hydrogen infrastructure is an important barrier to the widespread uptake of H<sub>2</sub>FC technologies. There is a perception that an all-encompassing ‘hydrogen economy’ must be established with enormous cost and duplication of existing energy infrastructure [208-210]. However, numerous production and distribution pathways exist, as summarised in Figure 14, and include several incremental steps which do not require a wholesale infrastructure transformation. Developing a cost-efficient infrastructure from these options that may evolve over time with developing demand is a significant challenge [211].



**Figure 14: Hydrogen delivery pathways discussed in this paper. This diagram is simplified and non-exhaustive, and serves to highlight the diversity of options at each stage of the system.**

The upper half of Figure 14 depicts centralised production methods that rely on new distribution networks, synonymous with the ‘hydrogen economy’ vision. Incremental and less infrastructurally-intensive routes also exist (the lower half of the figure), which utilise existing gas or electricity networks and reduce large up-front costs, albeit at the expense of lower efficiency. Indeed, H<sub>2</sub>Mobility concluded that only 60 small refuelling stations with onsite hydrogen production would be sufficient to supply most of the UK population in the early stages of a transition to fuel cell vehicles, with additional infrastructure deployed as demand increased [67]. This suggests that infrastructure development might not be as challenging as some have suggested.

## 5.1 Hydrogen production

785 Producing cost-competitive low-carbon hydrogen at a range of scales is arguably the greatest barrier  
to developing the hydrogen energy system [212]. Approximately 45–65 Mt/yr hydrogen is produced  
globally as feedstock for chemical and petrochemical industries, equivalent to 5.4–7.8 EJ, or ~1% of  
global energy supply [213–216]. Around half of this is produced by steam reforming natural gas, 30%  
from partial oxidation of crude oil products, 18% from coal gasification, and 4% from water  
790 electrolysis. Several emerging hydrogen production routes are at earlier stages of development [212],  
including high-temperature steam electrolysis [217, 218], solar thermo-chemical water splitting  
(artificial photosynthesis) [219, 220] and biological hydrogen production [221, 222].

### 5.1.1 Fossil fuels and biomass

795 Reforming is the conversion of hydrocarbons and steam into hydrogen and carbon monoxide (known  
as syngas). It produces relatively pure hydrogen with high efficiency, but is a slow endothermic  
reaction, and so does not react well to transient or stop/start cycling [223].

Partial oxidation is the incomplete combustion of a fuel-rich mixture to produce syngas. It is more  
versatile than reforming, allowing a greater range of fuels to be used, and proceeds more rapidly with  
800 no need for external heat input (allowing for smaller reactors); however, the hydrogen yield is lower  
(meaning more hydrocarbon feedstock is required), and the resulting gas requires additional  
cleaning [224].

805 Gasification is the process of partially combusting coal or biomass at high temperature and pressure  
to produce syngas. This gives a faster reaction than steam reforming, but has higher costs as the  
solid fuel requires pre-treatment and the resulting syngas requires greater treatment [184].

810 The vast majority of hydrogen is produced from fossil fuels, with CO<sub>2</sub> emission intensities depending  
on the feedstock and conversion efficiency [225]. Carbon capture and storage (CCS) could be  
feasible for large centralised production and could potentially deliver negative CO<sub>2</sub> emissions when  
using bioenergy feedstocks [226, 227]. This relies on CCS maturing to the point of widespread rollout  
after ‘a lost decade’ [228, 229] and on wider sustainability issues surrounding bioenergy supply-  
chains being carefully managed [230, 231].

### 5.1.2 Water electrolysis

815 Alkaline electrolysis cells (AEC) are the incumbent technology with a 100 year history, but polymer  
electrolyte membrane (PEMEC) are rapidly reaching maturity and are of particular interest for power-  
to-gas applications, while solid oxide electrolysers are transitioning from the laboratory to the  
demonstration phase [187, 194, 232, 233].

820 Alkaline electrolysers are the most mature, durable and cheapest technology [234]. A direct voltage  
current is applied between an anode and a cathode submerged in an alkaline electrolyte. Units can  
be several MW in size, but have a limited operating range (from a minimum of 20–40% to 150% of

design capacity) and slow start-times [189, 191, 194]. With growing interest in integration with renewable energy, development aims to improve its dynamic operation [186, 232].

PEM systems were introduced in the 1960s and became commercialised in the last decade [187]. They have faster response and start-up and a wider dynamic range (0–200%), more suitable for intermittent power supply [189, 233]. They have higher power density (and thus are smaller) due to their solid plastic electrolyte [235], and have a high-pressure output (e.g. 80 bar) reducing the energy required for compression downstream. However, capital costs are currently approximately twice those of AEC [186, 187, 236], and cell lifetimes need to improve [188, 194].

Solid oxide electrolyzers (SOEC) use a solid ceramic electrolyte and operate at very high temperatures (700–900 °C), enabling higher electrical efficiencies than other electrolyzers [235, 237]. Material degradation and lifetimes are critical shortcomings that must be improved [187, 238–240].

Capital costs for electrolyzers are high, around \$1300/kW for AEC and \$2,500/kW for PEMEC [187], although these are declining rapidly [236], whereas variable costs are governed by the electricity source. They also have high fuel costs for electricity, although the growing prospects of overproduction from intermittent renewables means zero (or negative) electricity prices are becoming more common [241].

### 5.1.3 Production efficiency

Table 4 summarises the nominal efficiency and energy requirements for different hydrogen production methods. Early demonstrations have seen much lower efficiencies in practice though. For example, hydrogen production efficiency at dozens of filling stations in California and Japan averaged  $55.8 \pm 8.4\%$  efficiency from natural gas [242], while electrolyzers averaged  $55.9 \pm 3.5\%$  LHV (for those with >4 operating hours per day) [243–247].

**Table 4: The efficiency and energy consumption of hydrogen production pathways. Data from [135, 187, 194].**


	Efficiency (LHV)	Energy requirement (kWh / kgH <sub>2</sub> )
Steam Methane Reforming	72% (65–75%)	46 (44–51)
Electrolysis	61% (51–67%)	55 (50–65)
Coal Gasification	56% (45–65%)	59 (51–74)
Biomass Gasification	46% (44–48%)	72 (69–76)

## 5.2 Hydrogen compression

Hydrogen is produced at a range of pressures across the different options and can be generated up to 15–80 bar by high-pressure electrolyzers [248]. Hydrogen pipelines typically operate at such pressures, with regularly-spaced pipeline compressors used to maintain pressure over long distances. For storage, hydrogen must either be compressed or liquefied to obtain sufficient energy

860 density. Highly-compressed gas is currently the preferred option for onboard vehicle storage, avoiding the expense and boil-off losses of liquefaction, the conversion losses of synthetic fuels such as ethanol and the technological immaturity of hydrogen carriers such as hydrides. Refuelling stations store hydrogen in in high-pressure tanks (825–950 bar) to allow fast refuelling despite the pressure drop across the dispenser [249]. Compressed hydrogen also needs cooling to  $-20$  to  $-40^{\circ}\text{C}$   
865 to avoid overheating the vehicle’s tank [135].

The energy penalty of compression to 875 bar is significant, as can be seen in Figure 15 [24]. About 9% of the hydrogen’s energy content (3.5 kWh/kg) is used to compress from a 20 bar pipeline to 875 bar. While this is notably less than required for liquefaction, it still adds appreciably to the cost and carbon intensity of the resulting fuel. Compression costs are significant but not prohibitive, adding around \$1.50/kg for pipeline and onsite production, or \$0.40/kg from tube trailers [249]. These are not expected to change dramatically due to mature compressor technology [250].  
870



875 **Figure 15: Hydrogen compression work requirements to 875 bar [24]. Efficiency is reported relative to the adiabatic input required (where compression heat is not removed during compression). A standard compressor of 70% efficiency is plotted, and the US DoE has targeted 80% compressor efficiency by 2020, though this is still low compared to some other compressor technologies [249].**

880 Mechanical compressors are the most mature technology for hydrogen, although they suffer poor reliability and are a leading cause of downtime in hydrogen refilling stations [249, 251]. Within this category, centrifugal compressors are used in centralised production and pipelines, and piston compressors are used for high-pressure refuelling stations [252]. Electrolysis can generate hydrogen at pressures up to 200 bar with higher efficiency than mechanical technologies [248]. Less mature technologies include electrochemical, ionic and hydride compressors (Table 5). See [24] for further discussion.  
885

**Table 5: Advantages and disadvantages of compression technologies.**

Technology	Advantages	Disadvantages
<b>Mechanical</b> [249, 251, 252]	+ Commercially available + Wide operating range	– Low efficiency (~70%) and expensive – Poor reliability due to many moving parts – Regular maintenance needed due to start-ups – Purification required due to oil contamination
<b>High-pressure electrolysis</b> [233, 248]	+ High efficiency + Production at 50–200 bar + High temperature reduces energy use	– Strong materials needed (increasing cost) – Increased cross-over and back-diffusion losses – Long start-up times requires stable supply
<b>Electrochemical</b> [7, 253, 254]	+ High efficiency + 1000 bar demonstrated + High reliability (no moving parts) + Pure output (no oil contamination)	– Strong materials needed (increasing cost) – Back-diffusion and resistive losses – Low throughput needed to increase efficiency – Pure inlet required and needs drying
<b>Ionic</b> [255]	+ Low contamination + High efficiency + Reliable (few moving parts)	– Expensive and unproven – Limited throughput to avoid foaming
<b>Hydride</b> [233]	+ Compact, reversible + Reliable (few moving parts)	– Expensive and unproven – Heavy

890

## 5.2.1 Liquefaction

Liquefaction of hydrogen greatly increases its energy density, allowing large-scale transport by road tanker or ship which is particularly attractive for long distances where pipelines are not economically feasible [41]. Over 90% of merchant hydrogen is transported as liquid in the US, indicating the maturity of liquefaction technology [256].

895

Liquefaction consumes considerably more energy than compression, as seen in Table 6. The US’s 2020 target for the energy consumption of large-scale liquefaction is 11 kWh/kg, with the potential to reduce to 6 kWh/kg in the long-term [256]. All large-scale hydrogen liquefaction plants are based on the pre-cooled Claude system and while several alternate designs have been proposed, “they are still neither more efficient nor realistic” [257]. For context, 11 kWh is one third of the LHV content of a kg of fuel, so if the electricity input is produced with 50% efficiency, liquefaction adds 0.66 units of primary energy consumed per unit of delivered hydrogen.

900

905

**Table 6: The efficiency and energy consumption of hydrogen distribution pathways, assuming production at 20 bar. Data from [135, 194]. The energy penalty is measured relative to the LHV energy content of hydrogen, and assumes electricity is produced with 50% efficiency (generation plus distribution).**

	Energy penalty (vs. LHV)	Electricity requirement (kWh / kgH <sub>2</sub> )
Compression to 500 bar (including cooling)	15% (12–24%)	2.6 (2–4)
Compression to 900 bar (including cooling)	21% (18–30%)	3.5 (3–5)
Liquefaction	78% (66–90%)	13 (11–15)

910

## 5.3 Hydrogen purity

915

The ISO 14687-2 standard for transport PEMFCs requires 99.97% purity hydrogen [258], and all fuel cell systems have tightly-controlled specifications on input purity to preserve cell lifetimes (Table 7). High temperature SOFCs and MCFCs have the advantage of being the most fuel-flexible technologies, in some cases able to use methane and carbon monoxide directly as a fuel. PAFCs are tolerant to around 1% CO; however, the Pt catalyst in the PEMFC is easily poisoned, and so the CO present in syngas must be removed or converted. Sulphur is a critical poison to all fuel cells, which is problematic due to its use as an odourant in natural gas for safety reasons.

**Table 7: Summary of fuel tolerance for different fuel cell types. Data from [139, 223].**

	Polymer (PEMFC)	Phosphoric Acid (PAFC)	Molten Carbonate (MCFC)	Solid Oxide (SOFC)
<b>Sulphur (S, H<sub>2</sub>S, COS)</b>	< 0.1 ppm	< 50 ppm	< 0.1–10 ppm	< 1–2 ppm
<b>CO</b>	< 10–100 ppm <sup>(a)</sup>	< 0.5–1%	Fuel	Fuel
<b>NH<sub>3</sub></b>	Poison	< 4%	< 1%	< 0.5%

920

**(a) Standard Pt anode catalysts can only withstand CO concentrations up to 10 ppm, and PtRu alloys up to 30 ppm. These limits can be extended by bleeding air into the anode and using alternative bi-layer catalysts.**

### 5.3.1 Hydrogen from electrolysis

925

Hydrogen produced from water electrolysis is typically pure enough for FCEV applications, as recombination catalysts remove oxygen that crosses the membrane [259, 260]. The main contaminant is water vapour, which, although required for fuel cell humidification, corrodes and erodes the compressing, storing and transporting equipment. It can also freeze in cold temperatures, damaging pipework and valves. Electrolysers therefore normally include dryers, typically regenerative desiccant towers, which are low-cost with low power consumption. However regeneration either involves electrical heating, or sending some dry gas back through the wet tower to pick up the accumulated moisture, typically reducing yield by around 10%, though there is scope for reducing this [261].


930



### 5.3.2 Hydrogen from steam methane reforming

935 Hydrogen from reformed natural gas needs several clean-up stages if used in low-temperature fuel cells, as shown in Figure 16. Pressure-swing adsorption (PSA) is the incumbent technology for separating hydrogen from carbon dioxide and other contaminants, and is capable of achieving hydrogen purities of >99.9% at the expense of loss of yield [225, 262]. Hydrogen purification costs from SMR have been estimated as \$0.70/kg, projected to fall to \$0.40/kg in 2025 [7].

940 An alternative to PSA is pressure-driven diffusion membranes, typically palladium-based. Current palladium filters achieve exceptionally high purity but are expensive, require a 400°C operating temperature and a pressure differential of 10–15 bar [263], reduce yield by 3-5%, and can suffer short lifetimes. One study found a palladium-based separation system that is potentially cheaper than PSA [263] and further research is required to determine potential for diffusion membranes and electrochemical compressors [7].



950 **Figure 16: An overview of fuel processing for fuel cell systems. Each stage is highlighted in bold, and given with the most common methods that are used; for each stage, the primary method is highlighted in italics. A description of each stage is given at the far left, along with the ideal reactions for the primary method. Indicative ranges of gas composition after each stage are given to the right. Following the stages down from natural gas to each type of fuel cell on the right indicates which processing stages are required. Data from [134, 139].**

955

### 5.3.3 Hydrogen from pipelines and storage

Hydrogen extracted from pipelines and/or salt-cavern storage requires onsite cleaning before FCEV usage to remove lubricants, odourants, colourants, debris or dust acquired. Odourants are likely needed to warn against leaks; cyclohexene has been found to be compatible with fuel cell technology in Japan, but is described as having too pleasant a smell and lacking the stench of current

960

EU odourants [131, 225]. A colourant may also be required to warn users of fires, as hydrogen burns with a colourless flame; an extremely dilute strontium solution is being considered [225]. It may be that PSA or activated carbon filters would be appropriate for onsite purification. The cost of cleaning hydrogen from pipelines is currently an unknown and requires further work [7].

965

## 5.4 Hydrogen distribution

There are typically three routes for hydrogen distribution, the suitability of which depends on the size of demand and the transportation distance (Table 8). Compressed hydrogen transport via tube trailers is likely to assist initial rollout, whereas pipelines are better suited for mass deployment. Pipelines could provide scalability if heat, power and industry converted to hydrogen as well as transport. Liquefaction could be used for international shipping of bulk hydrogen; distribution of liquefied hydrogen by road could be restricted to a few heavy-duty transport sectors.

970

**Table 8: Qualitative overview of hydrogen T&D technologies for hydrogen delivery in the transport sector [4].**

975

Distribution route	Capacity	Transport Distance	Energy Loss	Fixed Costs	Variable Costs	Deployment Phase
On-site production	Low	Zero	Low	Low	High	Near term
Gaseous tube trailers	Low	Low	Low	Low	High	Near term
Liquefied tankers	Medium	High	High	Medium	Medium	Medium term
Hydrogen pipelines	High	High	Low	High	Low	Long term

### 5.4.1 Gas tube trailers

An option for low demand, such as during initial rollout, is distributing hydrogen from centralised production facilities as a compressed gas in tube trailers. This is well-established, and large trailers for FCEV refuelling hold 1000 kg capacity at 500 bar [7]. The trailer can be parked at the refuelling station to refuel vehicles directly, reducing onsite storage and compression requirements as compression begins from a much higher starting pressure. However, this uses valuable surface space at the refuelling station and delays the trailer's return for its next load. Tube trailers become less economic as demand rises and over long distances [41], but remain an attractive near-term solution for its lower infrastructure cost and risk [264]. Longer term it could still present the best option for remote or low-demand areas [41].

980

985

### 5.4.2 Liquid hydrogen tankers

Liquid hydrogen tanker capacities are typically 2,000–7,500 kg and have greater density than compressed storage [41]. This would likely pose additional safety restrictions, as applied to industrial sites using hydrogen [41]. Despite early interest in using liquid hydrogen for vehicles, boil-off results in high storage losses for low-utilisation vehicles and is potentially unsafe for parking in enclosed spaces [265]. While lower density compressed hydrogen offers sufficient range for personal

990

995 vehicles, heavy-duty transport sectors (e.g. trucks and ships) may still be better served by liquid hydrogen [13].

### 5.4.3 Gas pipelines

1000 Pipelines are regarded as the most efficient method of transporting large quantities of hydrogen over short distances [41]. Around 3,000 km of high-pressure hydrogen pipelines are already in use in Europe and North America for industrial processes [41]. However, high costs prevent further pipeline development until sizeable and consistent demand for hydrogen can be assured.

1005 Low initial utilisation and high upfront costs are likely to hinder financing [41]. Existing high-carbon steel natural gas pipelines might fail if repurposed due to hydrogen embrittlement, so new high-grade steel construction would be required [266]. Embrittlement is not a concern at lower pressures [267] and newer polythene natural gas pipes being installed across the UK and Europe are hydrogen compatible [268]. These polythene pipes are currently limited to 7 bar, but larger plastic pipes up to 17 bar have been proposed [41]. Hydrogen pipelines have long lifetimes (50–100 years), although the rate of embrittlement in steel pipelines can make this difficult to predict [41].

### 5.4.4 Blending hydrogen into natural gas

1015 Hydrogen can be safely mixed in small quantities with natural gas and injected into the existing gas network, but administrative and technical constraints limit the permissible fraction of hydrogen. The level of hydrogen that could be safely added depends on the distribution system and end-use appliances. The UK and US have amongst the lowest legal limits of any country at 0.1%, compared to 10–12% (by volume) in Germany and the Netherlands (Figure 17, left).

1020 Current research aims to refine this range of allowable injections [263, 269-272]. A Dutch study concluded that off-the shelf gas appliances operated with no serious problems with up to 20% hydrogen blends by volume [273]. Similarly, the Health and Safety Laboratory concluded that 20% hydrogen was unlikely to harm the UK gas network or most appliances, although the identification and modification of vulnerable appliances is required for concentrations above 10% [130]. The different combustion characteristics of hydrogen may interact differently across the wide range of gas appliances in use, many installed decades ago.

1025 Even if limits were relaxed, a 20% blend would represent only 7% hydrogen by energy content, due to its lower density than methane. The share of hydrogen by energy content ( $E_H$ ) is calculated from the volume percentage (or mole fraction) of hydrogen ( $V_H$ ) and methane ( $V_M$ ) as in Equation 1:

$$E_H = \frac{11.88 V_H}{11.88 V_H + 39.05 V_M} \quad (1)$$

1030 where 11.88 and 39.05 are the volumetric HHV energy content of hydrogen and methane respectively (MJ/m<sup>3</sup>) [274], and  $V_M = 1 - V_H$  by definition.

1035

The direct carbon emissions savings of a 20% (volume) hydrogen blend would be 13 gCO<sub>2</sub>/kWh (Figure 17, right), so hydrogen injection alone could not achieve deep decarbonisation of the gas network. That said, this amount of hydrogen blending would deliver most of the decarbonisation required in UK buildings to 2030 (a 10% reduction on 2015 emissions [23]), not accounting for upstream hydrogen supply chain emissions.




Figure 17: Limits on hydrogen blending into national gas grids around the world, using data from [275] (left); and the relationship between energy content, carbon savings and hydrogen injection mixtures (right).

1040

### 5.4.5 Converting the natural gas network to hydrogen

1045

An alternative to blending is complete conversion of existing natural gas distribution networks to distribute hydrogen. Consumer satisfaction with gas heating indicates this could be a popular low-carbon choice [276]; although the UK is among the only countries actively considering this option, e.g. with the Leeds H21 project [225] or in Manchester [277]. In the 1970s, Britain converted from town gas to natural gas progressively over 11 years, with all networks converted in parallel [278]. Early desk studies have shown that conversion back to hydrogen could be technically feasible and economically viable [15, 225]. Such a switch would likely take 10–20 years, with appliances in every building being systematically converted or replaced and careful planning to ensure continuity of supply [225].

1050

1055

Gradual conversion of the heating stock as products reach their end of life; with a roll-out of 1 million properties a year at a cost of \$5,000 per house is considered feasible [41]. This transition period may require “hydrogen-ready” boilers capable of running on both natural gas and hydrogen. While this is thought of as uneconomical [131], it was used in the gradual roll-out of digital television and in plans for “CCS-ready” power stations [279]. Legislating for standardised backplates for all new boilers would greatly reduce the cost and time required for such a conversion [280].

1060

## 5.5 Hydrogen storage

### 5.5.1 Bulk storage

1065

1070

Large-scale hydrogen storage is one of the few low-carbon solutions to balance long-term intermittency in electricity generation from wind and solar power, especially in relation to inter-seasonal shifts (see Section 4.2) [200]. As with compressed air energy storage (CAES), hydrogen can be stored in compressed form in underground salt caverns [281]. Hydrogen offers energy densities of 280 kWh/m<sup>3</sup> – 100 times greater than for compressed air [41]. A limited number of regions have suitable salt deposits, but several chemical and refinery complexes have used substantial hydrogen salt cavern storage facilities since the 1960s [41]. Operational projects include a 24 GWh facility in the UK and an 83 GWh facility in Texas [282]. Hydrogen storage is currently the only low-carbon technology able to store over 100 GWh and operate over a timescale of weeks or even months, although this is countered by low round-trip efficiency and high costs for the conversion equipment [282, 283].

1075

1080

1085

If hydrogen were delivered by pipeline for heat and electricity provision, line-packing (using the compressibility of gas within the network) combined with geologic storage could balance supply and demand. However, significant high-pressure decentralised storage is required for transport applications due to space constraints, particularly at refuelling stations and on-board vehicles. Higher pressures increase tank material and compressor specifications, compression work requirements and safety measures such as minimum separation distances at forecourts. Low (~45 bar) and medium pressure (200–500 bar) pressure vessels are common in industry, but high pressure tubes and tanks (700–1,000 bar) are almost exclusively used for FCEVs and refilling stations, and are currently produced in low quantities [41]. Hydrogen tanks at refuelling stations have higher pressures than in FCEVs (e.g. 925 vs 700 bar) to allow rapid refuelling without requiring a slow compressor to fill vehicle tanks. Compressed hydrogen gas has only 15% the energy density of petrol, so refuelling stations require more physical space to supply the same amount of fuel. This could be offset by using underground storage at refuelling stations to reduce surface land usage in densely populated urban areas. Even then it is possible that many existing urban refuelling stations would not be suitable for hydrogen if they were remote from the high-pressure hydrogen network [41].

1090

### 5.5.2 Alternative hydrogen carriers

1095

Hydrogen can also be distributed in the form of fuels such as ethanol, CNG or ammonia [284], which can be low-carbon if produced from biomass or non-fossil fuel sources. These could offer low-pressure, high-volume energy carriers similar to those used extensively today. However, biomass availability is limited and synthetic fuels are costly and difficult to produce, so these options are not currently under widespread consideration.

1100

A number of alternative hydrogen carriers with lower technology-readiness levels are currently under investigation. Solid carriers including metal hydrides are already established in a few niche applications including submarines and scooters [41]. They operate at low pressure and hence require lower safety restrictions and separation distances than highly-compressed or liquefied hydrogen, making them attractive in densely-populated areas. Their gravimetric energy density (around 3%

hydrogen by weight) is comparable to compressed gas at 500 bar [285]. Borohydrides are a promising option being intensively researched, offering the potential for over 10 wt% storage [286, 287].

1105

Energy is released during charging (i.e. hydrogenation), but energy input of about 30% is required during discharging [41]. Hydrides have cheaper system components (e.g. a small compressor, a heater for discharging) than for compressed or liquefied hydrogen storage. Slow charging and discharging rates limit their suitability for on-board applications, meaning that the hydrogen must be released from the hydrides at the refuelling stations and compressed for on-board storage.

1110

Liquid organic hydrogen carriers (LOHCs) attain densities of 6 wt%, and like hydrides they offer low pressure operation and improved safety [41]. Around 25% of the energy content of hydrogen is required to release the fuel, though this could be offset if the equivalent amount of energy released during hydrogenation could be captured [288]. Catalysts can be employed to speed up the reactions, potentially enabling their usage on-board vehicles hence avoiding compression requirements.

1115

For comparison, 700 bar compressed hydrogen tanks offer 5.7 wt% hydrogen storage (using the Toyota Mirai as an example) [289]. The DOE target improvement to 7.5 wt% at a cost reduction from \$33/kWh at present to \$8/kWh [290].

1120

## 6 Policy challenges

### 6.1 International policy context

1125 Globally, relatively few energy policies apply directly to H2FC technologies. Policies aimed at reducing GHG emissions such as feed-in tariffs focus on renewables and exclude non-green hydrogen, while policies that tackle energy affordability generally exclude hydrogen and fuel cells due to their current high costs [24].

1130 This is slowly changing, as some countries extend their policies to include H2FC technologies. For example, European hydrogen refuelling infrastructure is now promoted under the Alternative Fuels Infrastructure Directive [291], and while the current Renewable Energy Directive (RED) accepts renewable biofuels and bioliquids that save at least 60% GHG emissions, hydrogen is excluded [292]. However, the revised RED will be broadened to include hydrogen from 2021, with pathways saving 70% GHG emissions being classified as a renewable fuel of non-biological origin [293, 294], which may encourage countries to give policy support to hydrogen supply chains. Support exists in the US, with eight federal programs having some scope to promote H2FC uptake, although individual states define the supporting mechanisms, meaning FCEV rebates range from zero to \$5,000 per vehicle [295].

1140 Table 9 summarises the national targets for H2FC technology uptake in six leading countries, and Table 10 compares the level of financial support provided to achieve these. Whilst these demonstrate ambition towards FCEV uptake, incentives are smaller than for other technologies. For example, the UK budget for hydrogen transport projects is £23m, while the funding for BEV recharging and manufacturing infrastructure is £646m [296]. Additionally, the UK supports only biogas combustion micro-CHP devices rather than fuel cell CHP, whilst there is support for battery electric vehicles but not fuel cell vehicles [297].

**Table 9 Summary of hydrogen and fuel cells uptake targets. Data from: [298, 299].**

Country	CHP		Fuel cell cars			Refuelling stations		
	2020	2030	2020	2025	2030	2020	2025	2030
Japan	1.4m	5.3m	40,000	200,000	800,000	160	320	900
Germany	–	–	100% ZEV <sup>(a)</sup> by 2040			400	–	–
China	–	–	3,000 <sup>(b)</sup>	50,000	1m	100	300	1,000
US	–	–	0	3.3m	–	100 <sup>(c)</sup>	–	–
South Korea	–	1.2 MW	10,000	100,000	630,000	100	210	520
UK	–	–	100% ZEV <sup>(a)</sup> by 2040			30	150	–

1150 (a) Zero Emission Vehicle

(b) Shanghai only

(c) California only

1155

**Table 10 Summary of the support offered in various countries for hydrogen and fuel cells in 2017. Data from: [295, 298-309]. Values given in 2016 US Dollars, converted as ¥102 = €0.75 = CNY 3.5 = KRW 894 = £0.69 = \$1.**

Country	Residential CHP	Fuel Cell Vehicles	Refuelling
Japan	\$93m \$700–1,700 / unit	\$147m	\$61m
Germany	\$13,600 / unit	\$4,000 / vehicle	\$466m
China	–	\$1,700 / kW (up to \$57,000 / vehicle)	\$1.1m / unit
US	\$1,000 / unit (up to \$3,000/kW for larger systems)	Up to \$13,000 / vehicle	30% of cost (up to \$30,000) (California \$100 M up to 2023)
South Korea	\$5.3m		\$5.4m (up to \$31,000 / vehicle)
UK	–		\$33m (60% of cost for refuelling)

1160

Policy support for H<sub>2</sub>FC technologies are driven by various national priorities, including air quality, climate change [24], energy security [310], affordability and economic growth [311]. US policy is driven by the need to improve air quality due to transportation; thus there are no national targets for deploying fuel cells in stationary applications. China aims to reduce severe urban air quality issues and boost economic growth through manufacturing fuel cells as part of the “Made in China 2025” strategy [312]. In Japan, hydrogen is promoted to provide energy security through improving efficiency, to support national industries and revitalise regional economies and reduce environmental burdens [313].

1165

1170

Japan envisions a three stage transition to a hydrogen society: promoting FCEVs, hydrogen production and residential fuel cells (currently); developing and integrating hydrogen supply chains into the energy system (by 2030); and finally establishing a carbon-free hydrogen supply by 2040 [314]. In contrast, the main driver in Europe is reducing GHG emissions, with hydrogen also seen as a critical part of the industrial strategy of countries such as the UK [299]. The UK and France plan to halt the sale of new petrol and diesel cars from 2040 [315, 316] and the Netherlands from 2030 [317]. Norway aims to replace sales of diesel cars with electric and hydrogen passenger cars from 2025 [318].

1175

## 6.2 Current market size

Evidently, countries that have provided stronger incentives and broader strategies (Table 10) have seen greater uptake of H<sub>2</sub>FC technologies, as shown in

1180

Table 11. Fuel cell vehicles are an area where the US is leading, with 2,750 FCEVs sold as of 2017, more than in Japan and Europe combined [319, 320]. China’s stance on fuel cells could have global implications [80]; its 2016 Fuel Cell Vehicle Technology Roadmap includes a modest target for 5,000 FCEVs in 2020 but a scale of millions in 2030 [321].

**Table 11: Summary of hydrogen and fuel cells uptake as of 2017. Data from [66, 298, 320, 322, 323].**

Country	CHP Units	Fuel Cell Vehicles	Refuelling stations	Forklift Trucks
---------	-----------	--------------------	---------------------	-----------------




<b>Japan</b>	223,000	1,800 cars	90	21
<b>Germany</b>	1,200	467 cars, 14 buses	33	16
<b>China</b>	1	60 cars, 50 buses	5	N/A
<b>US</b>	225 MW	2,750 cars, 33 buses	39 public 70 total	11,600
<b>South Korea</b>	177 MW	100 cars	11	N/A
<b>UK</b>	10	42 cars, 18 buses	14	2

1185

1190

1195

Figure 18 illustrates the extent to which Japan is leading fuel cell CHP rollout: South Korea and Europe trail by a decade, and the US has seen very limited uptake. In 2012, fuel cells outsold engine-based micro-CHP systems for the first time, taking 64% of the global market [324]. Japan has deployed 98% of the world's residential fuel cell systems with over 223,000 systems sold as of October 2017 [298, 325]. The dotted lines in Figure 18 indicate the Japanese government's target of 1.4 million fuel cells installed by 2020 [326], although Bloomberg forecast that only a quarter of this target will be reached as subsidies have fallen too quickly to offset high costs and competition from rooftop solar. Toshiba recently exited the industry, leaving only two EneFarm manufacturers [327]. The European Union originally anticipated 50,000 systems by 2020, but only 1,046 systems were installed in the ene.field project [328], and 2,650 additional units will be installed by 2021 as part of the PACE demonstration [329].



1200

**Figure 18: Cumulative number of residential micro-CHP systems installed to date (solid lines) and near-term projections (dotted lines). Data from [16, 329-331].**

1205

1210

Strong policy signals can evidently yield substantial benefits, as seen by the uptake of home heating systems and vehicles deployed in Japan, and the strength of Japanese manufacturers. Demonstration projects that enable learning-by-doing through manufacturing scale-up have been necessary for decreasing the price of H<sub>2</sub>FC technologies as with other technologies. However, the scale of such demonstration programmes has arguably been trivial outside of Japan. For context, the two largest demonstration projects in Europe (ene.field and PACE) target just 3% the number of households that received solar PV panels in Germany's 100,000 roofs programme over a decade ago [332].

## 6.3 Policy drivers for hydrogen and fuel cells

1215 The drivers for promoting hydrogen and fuel cells in energy policy relate to improving the reliability, efficiency and security of the energy system, reducing environmental impacts, and developing new low-carbon industries, with their associated employment opportunities and skills. The potential of H<sub>2</sub>FC technologies to contribute to all the dimensions of sustainable development (environmental, social and economic) arguably justifies their systematic and long-term policy support.

1220 Several European countries are working to define green hydrogen standards, showing a concern for the climate benefits from fuel cells rather than just the level of uptake [333]. Some standards focus on hydrogen from renewable sources, others include hydrogen from low-carbon sources (including nuclear and CCS). These differences will need to be resolved if a pan-European, or even a global, certification scheme is to be agreed [24].

1225 A changing climate, natural disasters, war and cyber-security flaws can have extreme impacts on energy supply chains [310]. H<sub>2</sub>FC technologies can support the electricity system in balancing weather-dependent renewables, and hydrogen can improve national energy self-reliance, as it has numerous production pathways. Hydrogen can also be produced anywhere, which makes it particularly attractive to oil-deficient countries as one of the principal alternative fuels with a considerable potential for long-term substitution of oil and natural gas [291].

1230 Hydrogen and fuel cells are currently more expensive in most applications than their low-carbon competitors. However, they possess some superior characteristics to these competitors, which could aid the public acceptability of decarbonising personal energy use. The steep cost reductions seen for fuel cells in Asia (see Section 3.2) suggest that programmes to support for research, development and deployment can significantly influence the economic viability of H<sub>2</sub>FC technologies. Japan's Hydrogen and Fuel Cell Roadmap, the US DOE Hydrogen and Fuel Cells Program, and Europe's Fuel Cells and Hydrogen Joint Undertaking (FCH-JU) are prominent examples.

1240

## 7 Conclusions

---

1245

Hydrogen has fallen in and out of favour since the oil shocks of the 1970s and remains a marginal energy system option. However, mainstream products are now emerging: Honda, Toyota and Hyundai have launched the first mass-produced hydrogen fuel cell vehicles, and fuel cells now heat 225,000 homes. Early-mover companies, notably in Japan, are beginning to see lucrative export opportunities.

1250

Hydrogen can play a major role alongside electricity in the low-carbon economy, with the versatility to provide heat, transport and power system services. It does not suffer the fundamental requirement for instantaneous supply-demand balancing, and so enables complementary routes to deeper decarbonisation through providing low carbon flexibility and storage. The numerous hydrogen production, distribution and consumption pathways present complex trade-offs between cost, emissions, scalability and requirements for purity and pressure; but provide a multitude of options which can be exploited depending on local circumstances (e.g. renewable energy or suitable sites for CO<sub>2</sub> sequestration).

1255

Hydrogen and fuel cells are not synonymous; they can be deployed in combination or separately. Fuel cells can operate on natural gas, which avoids combustion and thus 90% of airborne pollutants. Hydrogen can be burnt in engines and boilers with no direct CO<sub>2</sub> and near-zero NO<sub>x</sub> emissions. When used together, hydrogen fuel cells are zero-emission at the point of use, with overall emissions dependent on the fuel production method (as with electricity).

1260

Fuel cell vehicle costs are high relative to battery electric vehicles, but with mass production they can achieve parity by 2025–2030. Driving range and refuelling time are significantly better than premium electric vehicles, which is particularly advantageous for buses, heavy goods and other highly-utilised vehicles. As with electric vehicles and unlike biofuels, fuel cell vehicles can tackle urban air quality problems by producing zero exhaust emissions. This has the potential to drive deployment in cities, railways, airports, seaports and warehouses.

1265

Innovations in heat decarbonisation lag behind other sectors as heat pumps, district heating and burning biomass face multiple barriers. Households are accustomed to powerful, compact, rapid response heating systems, which can be modified to use hydrogen. Fuel cell combined heat and power can operate on today's natural gas network, albeit with limited carbon savings. Hydrogen presents various options for decarbonising this network in the longer term.

1270

Hydrogen technologies can support low-carbon electricity systems dominated by intermittent renewables and/or electric heating demand. Fuel cells provide controllable capacity that helpfully offsets the additional peak demand of heat pumps. In addition to managing short-term dynamics, converting electricity into hydrogen or other fuels (power-to-gas) could provide the large-scale, long-term storage required to shift renewable electricity between times of surplus and shortfall.

1275

1280

Hydrogen applications and the supporting infrastructure may be installed incrementally and simultaneously, with care taken to avoid potentially high-regret investments early on. Existing

1285 electricity and gas infrastructures can be used for on-site hydrogen production in distributed refilling  
stations and fuel cell heating. Focussing on specific users such as captive vehicle fleets (e.g. urban  
buses with central refuelling depots) could provide the high utilisation and demand certainty needed  
for investment. Given the diversity of decarbonisation pathways, a clear strategy will reduce the  
costs of introducing hydrogen and fuel cell technologies.

1290 Successful innovation requires focused, predictable and consistent energy policy, which is probably  
the single greatest challenge in realising the hydrogen and fuel cell potential. Stop-go policies, and  
frequent, unexpected policy changes undermine the confidence that businesses and industry need to  
make long-term investments in low-carbon technologies such as hydrogen and fuel cells. Countries  
should develop a system of policy support for hydrogen and fuel cell technologies that offers the  
1295 long-term stability needed for large, transformative investments to be made. Policy reviews, decision  
points and milestones in a support programme should be announced well in advance, with ongoing  
support conditional on meeting reasonable performance and cost targets. Given such sustained  
support, and the technological progress in hydrogen and fuel cells in recent years, there are strong  
grounds for believing that hydrogen and fuel cells can experience a cost and performance trajectory  
similar to those of solar PV and batteries, and in the medium term provide another important and  
1300 complementary low-carbon option with versatility to be deployed in multiple uses across the energy  
system.

## 8 Acknowledgements

---

1305 We thank the Engineering and Physical Sciences Research Council for funding this work via the H2FC  
Supergen Hub EP/J016454/1 and EP/P024807/1.

## 9 References

---

- [1] US DoE, 1995. *The Green Hydrogen Report*, NREL, Editor. NREL: Golden, CO. URL: <https://www.hydrogen.energy.gov/pdfs/greenhyd.pdf>
- 1310 [2] World Energy Council, 2017. *World Energy Issues Monitor*.
- [3] Cackett N, 2017. Honda Clarity FCV review. URL: <https://www.autocar.co.uk/car-review/honda/clarity-fcv>
- [4] International Energy Agency, 2015. *Technology Roadmap: Hydrogen and Fuel Cells*: Paris. URL: <http://www.iea.org/publications/freepublications/publication/technology-roadmap-hydrogen-and-fuel-cells.html>
- [5] Brandon NP and Kurban Z, 2017. *Clean energy and the hydrogen economy*. Philosophical Transactions of the Royal Society A, **375**(2098): 1-17.
- 1315 [6] Hydrogen Council, 2017. *Hydrogen scaling up: A sustainable pathway for the global energy transition*. URL: [www.hydrogencouncil.com](http://www.hydrogencouncil.com)
- [7] Hart D, Howes J, Madden B and Boyd E, 2016. *Hydrogen and Fuel Cells: Opportunities for Growth. A Roadmap for the UK*. E4Tech and Element Energy. URL: <http://www.e4tech.com/reports/hydrogen-and-fuel-cells-opportunities-for-growth-a-roadmap-for-the-uk/>
- 1320 [8] Hanley ES, Deane JP and Gallachóir BPÓ, 2018. *The role of hydrogen in low carbon energy futures—A review of existing perspectives*. Renewable and Sustainable Energy Reviews, **82**: 3027-3045.
- [9] Pudukudy M, Yaakob Z, Mohammad M, Narayanan B and Sopian K, 2014. *Renewable hydrogen economy in Asia – Opportunities and challenges: An overview*. Renewable and Sustainable Energy Reviews, **30**: 743-757.

- 1325 [10] Abbasi T and Abbasi SA, 2011. 'Renewable' hydrogen: Prospects and challenges. *Renewable and Sustainable Energy Reviews*, **15**(6): 3034-3040.
- [11] Sheffield JW, 2007. *Energy Security Through Hydrogen*, in *Assessment of Hydrogen Energy for Sustainable Development*, Sheffield JW and Sheffield Ç, Editors. Springer Netherlands: Dordrecht. p. 1-8. URL: [http://dx.doi.org/10.1007/978-1-4020-6442-5\\_1](http://dx.doi.org/10.1007/978-1-4020-6442-5_1)
- 1330 [12] Dunn S, 2002. *Hydrogen futures: toward a sustainable energy system*. *International Journal of Hydrogen Energy*, **27**(3): 235-264.
- [13] Coalition study, 2010. *A portfolio of power-trains for Europe: a fact-based analysis*. McKinsey & Company. URL: [www.fch-ju.eu/sites/default/files/documents/Power\\_trains\\_for\\_Europe.pdf](http://www.fch-ju.eu/sites/default/files/documents/Power_trains_for_Europe.pdf)
- [14] Tollefson J, 2010. *Hydrogen vehicles: Fuel of the future?* *Nature*, **464**: 1262-1264.
- 1335 [15] Dodds PE and Demoullin S, 2013. *Conversion of the UK gas system to transport hydrogen*. *International Journal of Hydrogen Energy*, **38**(18): 7189-7200.
- [16] Dodds PE, Staffell I, Hawkes AD, Li F, et al., 2015. *Hydrogen and fuel cell technologies for heating: A review*. *International Journal of Hydrogen Energy*, **40**(5): 2065-2083.
- [17] Napp TA, Gambhir A, Hills TP, Florin N and Fennell PS, 2014. *A review of the technologies, economics and policy instruments for decarbonising energy-intensive manufacturing industries*. *Renewable and Sustainable Energy Reviews*, **30**(Supplement C): 616-640.
- 1340 [18] Ball M and Weeda M, 2015. *The hydrogen economy – Vision or reality?* *International Journal of Hydrogen Energy*, **40**(25): 7903-7919.
- [19] Samsatli S, Staffell I and Samsatli NJ, 2016. *Optimal design and operation of integrated wind-hydrogen-electricity networks for decarbonising the domestic transport sector in Great Britain*. *International Journal of Hydrogen Energy*, **41**(1): 447-475.
- 1345 [20] World Resources Institute, 2015. *CAIT Climate Data Explorer*. URL: <http://cait.wri.org>
- [21] REN21, 2017. *Renewables Global Status Report*. URL: <http://www.ren21.net/gsr>
- [22] DECC, 2016. *Provisional UK greenhouse gas emissions national statistics 2015*, Department of Energy and Climate Change, Editor: London, UK. URL: <https://www.gov.uk/government/statistics/provisional-uk-greenhouse-gas-emissions-national-statistics-2015>
- 1350 [23] CCC, 2015. *The Fifth Carbon Budget: The next step towards a low-carbon economy*. Committee on Climate Change.
- [24] Staffell I, Dodds P, Scamman D, Velazquez Abad A, et al., 2017. *The Role of Hydrogen and Fuel Cells in Future Energy Systems: H2FC Supergen*.
- [25] Hawkes A, Staffell I, Brett D and Brandon N, 2009. *Fuel Cells for Micro-Combined Heat and Power Generation*. *Energy & Environmental Science*, **2**(7): 729-744.
- 1355 [26] Momirlan M and Veziroglu TN, 2002. *Current status of hydrogen energy*. *Renewable and Sustainable Energy Reviews*, **6**(1-2): 141-179.
- [27] Mazloomi K and Gomes C, 2012. *Hydrogen as an energy carrier: Prospects and challenges*. *Renewable and Sustainable Energy Reviews*, **16**(5): 3024-3033.
- 1360 [28] Energy Information Administration, 2017. *International Energy Outlook*.
- [29] ECC Select Committee, 2016. *Government to miss 2020 renewable energy targets*. URL: <https://www.parliament.uk/business/committees/committees-a-z/commons-select/energy-and-climate-change-committee/news-parliament-2015/heat-transport-report-published-16-17/>
- [30] CCC, 2016. *Meeting Carbon Budgets – 2016 Progress Report to Parliament*. URL: <https://www.theccc.org.uk/publication/meeting-carbon-budgets-2016-progress-report-to-parliament/>
- 1365 [31] Norsk Elbil Forening, 2017. *Elbilsalget: Ned i fjor – venter ny vekst i år*. URL: <http://elbil.no/elbilsalget-ned-i-fjor-venter-ny-vekst-i-ar/>
- [32] Next Greencar, 2017. *Electric car market statistics*. URL: <http://www.nextgreencar.com/electric-cars/statistics/>
- [33] EEA, 2016. *Air quality in Europe – 2016 report*. European Environment Agency: Luxembourg. URL: <http://www.eea.europa.eu/publications/air-quality-in-europe-2016>
- 1370 [34] Heather Walton DD, Sean Beevers, Martin Williams, Paul Watkiss, Alistair Hunt, 2015. *Understanding the Health Impacts of Air Pollution in London*. King's College London: London. URL: <https://www.kcl.ac.uk/lsm/research/divisions/aes/research/ERG/research-projects/HIAinLondonKingsReport14072015final.pdf>
- 1375 [35] European Commission, 2013. *Communication from the Commission to the Council, the European Parliament, the European Economic and Social Committee and the Committee of the Regions a Clean Air Programme for Europe* European Commission, Editor. European Commission, Brussels. URL: <http://eur-lex.europa.eu/legal-content/EN/TXT/PDF/?uri=CELEX:52013SC0532&from=EN>
- [36] WHO, 2016. *WHO releases country estimates on air pollution exposure and health impact*. World Health Organisation: Geneva. URL: <http://www.who.int/mediacentre/news/releases/2016/air-pollution-estimates/en/>
- 1380 [37] UN, 2015. *Transforming our world: the 2030 Agenda for Sustainable Development*. United Nations General Assembly: New York. URL: [http://www.un.org/ga/search/view\\_doc.asp?symbol=A/RES/70/1&Lang=E](http://www.un.org/ga/search/view_doc.asp?symbol=A/RES/70/1&Lang=E)

- [38] McGrath M, 2016. *Four major cities move to ban diesel vehicles by 2025*, in BBC. URL: <http://www.bbc.co.uk/news/science-environment-38170794>
- 1385 [39] DEFRA, 2017. *Plan for roadside NO<sub>2</sub> concentrations published*. URL: <https://tinyurl.com/defra-no2>
- [40] Reuters, 2017. *France to end sale of diesel and gasoline vehicles by 2040*. URL: <https://uk.reuters.com/article/us-climatechange-france/france-to-end-sale-of-diesel-and-gasoline-vehicles-by-2040-idUKKBN19RoVZ>
- [41] Hart D, Howes J, Lehner F, Dodds P, *et al.*, 2015. *Scenarios for deployment of hydrogen in contributing to meeting carbon budgets and the 2050 target*. URL: <https://www.theccc.org.uk/wp-content/uploads/2015/11/E4tech-for-CCC-Scenarios-for-deployment-of-hydrogen-in-contributing-to-meeting-carbon-budgets.pdf>
- 1390 [42] Pollet BG, Staffell I and Shang JL, 2012. *Current status of hybrid, battery and fuel cell electric vehicles: From electrochemistry to market prospects*. *Electrochimica Acta*, **84**: 235-249.
- [43] Dodds PE and Ekins P, 2014. *A portfolio of powertrains for the UK: An energy systems analysis*. *International Journal of Hydrogen Energy*, **39**(26): 13941-13953.
- 1395 [44] Stewart A and Dodson T, 2016. *Low carbon cars in the 2020s: Consumer impacts and EU policy implications*. *Element Energy for BEUC (The European Consumer Organisation)*: Brussels. URL: [http://www.beuc.eu/publications/beuc-x-2016-121\\_low\\_carbon\\_cars\\_in\\_the\\_2020s-report.pdf](http://www.beuc.eu/publications/beuc-x-2016-121_low_carbon_cars_in_the_2020s-report.pdf)
- [45] Offer GJ, Howey D, Contestabile M, Clague R and Brandon NP, 2010. *Comparative analysis of battery electric, hydrogen fuel cell and hybrid vehicles in a future sustainable road transport system*. *Energy Policy*, **38**(1): 24-29.
- 1400 [46] Autocar, 2015. *Hyundai ix35 Fuel Cell review*. URL: <https://www.autocar.co.uk/car-review/hyundai/ix35-fuel-cell/first-drives/2015-hyundai-ix35-fuel-cell-review>
- [47] Green Car Reports, 2016. *Toyota Mirai Priced At \$57500, With \$499 Monthly Lease*. URL: [http://www.greencarreports.com/news/1095511\\_2016-toyota-mirai-priced-at-57500-with-499-monthly-lease](http://www.greencarreports.com/news/1095511_2016-toyota-mirai-priced-at-57500-with-499-monthly-lease)
- [48] Renault, 2018. *ZOE - Models & prices*. URL: <https://www.renault.co.uk/vehicles/new-vehicles/zoe-250/models-and-prices.html>
- 1405 [49] Nissan, 2018. *2017 Leaf Specs*. URL: <https://www.nissanusa.com/electric-cars/leaf/versions-specs/version.s.html>
- [50] Bloomberg, 2017. *Driverless Cars Are Giving Engineers a Fuel Economy Headache*. URL: <https://tinyurl.com/y92aqxuz>
- [51] Alazemi J and Andrews J, 2015. *Automotive hydrogen fuelling stations: An international review*. *Renewable and Sustainable Energy Reviews*, **48**: 483-499.
- 1410 [52] Melaina M and Penev M, 2013. *Hydrogen Station Cost Estimates*. NREL Technical Report: TP-5400-56412 URL: <https://www.nrel.gov/docs/fy13osti/56412.pdf>
- [53] Cleantech Canada, 2017. *Ontario to get first public hydrogen fueling stations as feds shell out \$1.6M*. URL: <https://tinyurl.com/yaj7kgxv>
- [54] Rolec, 2017. *Rolec Electric Vehicle Charging Stations*. URL: <http://www.rolec.com/ev-charging>
- 1415 [55] Kabir MM and Demirocak DE, 2017. *Degradation mechanisms in Li-ion batteries: a state-of-the-art review*. *International Journal of Energy Research*, **41**(14): 1963-1986.
- [56] Scamman D, Newborough M and Bustamante H, 2015. *Hybrid hydrogen-battery systems for renewable off-grid telecom power*. *International Journal of Hydrogen Energy*, **40**(40): 13876-13887.
- [57] Ammermann H, Ruf Y, Lange S, Fundulea D and Martin A, 2015. *Fuel Cell Electric Buses – Potential for Sustainable Public Transport in Europe*. URL: [http://www.fch.europa.eu/sites/default/files/150909\\_FINAL\\_Bus\\_Study\\_Report\\_OUT\\_o.PDF](http://www.fch.europa.eu/sites/default/files/150909_FINAL_Bus_Study_Report_OUT_o.PDF)
- 1420 [58] Jason Marcinkoski JS, Adria Wilson, Dimitrios Papageorgopoulos, 2015. *Fuel Cell System Cost - 2015*, in *Hydrogen and Fuel Cells Program Record*. DoE. URL: [https://www.hydrogen.energy.gov/pdfs/15015\\_fuel\\_cell\\_system\\_cost\\_2015.pdf](https://www.hydrogen.energy.gov/pdfs/15015_fuel_cell_system_cost_2015.pdf)
- [59] Hydrogen Council, 2017. *How hydrogen empowers the energy transition*. URL: <http://hydrogeneurope.eu/wp-content/uploads/2017/01/20170109-HYDROGEN-COUNCIL-Vision-document-FINAL-HR.pdf>
- 1425 [60] International Organization of Motor Vehicle Manufacturers, 2017. *OICA Sales Statistics*. URL: <http://www.oica.net/category/sales-statistics/>
- [61] Becker D, Pawelke M, Dodd A, Romani B, *et al.*, 2017. *Global Automotive Executive Survey 2017*. KPMG. URL: <https://home.kpmg.com/xx/en/home/insights/2017/01/global-automotive-executive-survey-2017.html>
- [62] Mearian L, 2017. *Hydrogen refueling stations for cars to reach 5,000 by 2032*, in *Computerworld*. URL: <http://www.computerworld.com/article/3159642/car-tech/hydrogen-refueling-stations-for-cars-to-reach-5000-by-2032.html>
- 1430 [63] Daimler, 2017. *New “Hydrogen Council” launches in Davos*. URL: <http://media.daimler.com/marsMediaSite/en/instance/ko/New-Hydrogen-Council-launches-in-Davos.xhtml?oid=15337613>
- [64] Zap-Map, 2017. URL: <https://www.zap-map.com/>
- 1435 [65] Murray J, 2016. *Electric vehicle charge points to outnumber petrol stations by 2020, say Nissan*, in *The Guardian*: Manchester. URL: <https://www.theguardian.com/environment/2016/aug/04/electric-vehicle-charge-points-to-outnumber-petrol-stations-by-2020-say-nissan>
- [66] Ludwig-Bölkow-Systemtechnik and TÜV SÜD, 2017. *Hydrogen Refuelling Stations Worldwide*. URL: <https://www.netinform.de/H2/H2Stations/Default.aspx>

- 1440 [67] UK H2Mobility, 2013. *Phase 1 Results*: London, UK. URL: [www.gov.uk/government/publications/uk-h2mobility-potential-for-hydrogen-fuel-cell-electric-vehicles-phase-1-results](http://www.gov.uk/government/publications/uk-h2mobility-potential-for-hydrogen-fuel-cell-electric-vehicles-phase-1-results)
- [68] GLA, 2017. *Draft Mayor's Transport Strategy*. Greater London Authority: London. URL: <https://www.london.gov.uk/press-releases/mayoral/fairer-greener-healthier-more-prosperous-city>
- [69] Cars UK, 2016. *An extra 60 Hyundai ix35 Hydrogen Fuel Cell taxis for Paris – will grow to a fleet of HUNDREDS*, in *Cars UK*. URL: <http://www.carsuk.net/an-extra-60-hyundai-ix35-hydrogen-fuel-cell-taxis-for-paris-will-grow-to-a-fleet-of-hundreds/>
- 1445 [70] Spendelow J and Papageorgopoulos D, 2012. *Fuel Cell Bus Targets*, in *Fuel Cell Technologies Program Record*. DoE. URL: [https://www.hydrogen.energy.gov/pdfs/12012\\_fuel\\_cell\\_bus\\_targets.pdf](https://www.hydrogen.energy.gov/pdfs/12012_fuel_cell_bus_targets.pdf)
- [71] Adria Wilson JM, Dimitrios Papageorgopoulos, 2016. *On-Road Fuel Cell Stack Durability – 2016*, in *Hydrogen and Fuel Cell Technologies Program Record*. DoE. URL: [https://www.hydrogen.energy.gov/pdfs/16019\\_fuel\\_cell\\_stack\\_durability\\_2016.pdf](https://www.hydrogen.energy.gov/pdfs/16019_fuel_cell_stack_durability_2016.pdf)
- 1450 [72] Eudy L, Post M and Jeffers M, 2016. *Zero Emission Bay Area (ZEBA) Fuel Cell Bus Demonstration Results: Fifth Report*. URL: <http://www.nrel.gov/docs/fy16osti/66039.pdf>
- [73] US Department of Energy, 2017. *Compare Fuel Cell Vehicles*. URL: [http://www.fueleconomy.gov/feg/fcv\\_sbs.shtml](http://www.fueleconomy.gov/feg/fcv_sbs.shtml)
- [74] Eudy L, Post M and Jeffers M, 2016. *Fuel Cell Buses in U.S. Transit Fleets: Current Status 2016*. NREL: Golden, CO. URL: [https://www.energy.gov/sites/prod/files/2016/12/f34/fcto\\_2016\\_fuel\\_cell\\_bus\\_report.pdf](https://www.energy.gov/sites/prod/files/2016/12/f34/fcto_2016_fuel_cell_bus_report.pdf)
- 1455 [75] FCH-JU, 2012. *Urban buses: alternative powertrains for Europe*. URL: <https://tinyurl.com/fchju-2012-urban-buses>
- [76] Brahy N, 2015. *Fuel Cell Electric Buses – Potential for Sustainable Public Transport in Europe*. URL: [http://www.fch.europa.eu/sites/default/files/BRAHY%20%20FC%20BUS%20Lyon%20April%202015%20\(ID%202436341\)%20\(ID%20249777\).pdf](http://www.fch.europa.eu/sites/default/files/BRAHY%20%20FC%20BUS%20Lyon%20April%202015%20(ID%202436341)%20(ID%20249777).pdf)
- 1460 [77] Madden B, 2016. *London hydrogen buses and the CHIC project*. Presented at *All-Energy*. URL: [http://www.all-energy.co.uk/RXUK/RXUK\\_All-Energy/2016/Presentations%202016/Hydrogen%20and%20Fuel%20Cells/Ben%20Madden.pdf](http://www.all-energy.co.uk/RXUK/RXUK_All-Energy/2016/Presentations%202016/Hydrogen%20and%20Fuel%20Cells/Ben%20Madden.pdf)
- [78] Hua T, Ahluwalia R, Eudy L, Singer G, et al., 2014. *Status of hydrogen fuel cell electric buses worldwide*. *Journal of Power Sources*, **269**: 975-993.
- 1465 [79] Toyota, 2016. *Toyota to Start Sales of Fuel Cell Buses under the Toyota Brand from Early 2017*. URL: <http://newsroom.toyota.co.jp/en/detail/13965745>
- [80] E4Tech, 2016. *The Fuel Cell Industry Review*.
- [81] Pearson NO, 2017. *China's Buses Bolster Ballard's Three-Decade Quest for Hydrogen*, in *Bloomberg*. URL: <https://www.bloomberg.com/news/articles/2017-03-26/china-s-buses-bolster-ballard-s-three-decade-quest-for-hydrogen>
- 1470 [82] Ximin H, 2017. *全球规模最大！深圳专营公交车辆实现纯电动化*, in *Shenzhen Daily*. URL: <http://bit.ly/2EwhKM1>
- [83] Tesla, 2017. *Semi*. URL: <https://www.tesla.com/semi>
- [84] Kenworth, 2016. *Kenworth Receives \$8.6 Million in Grants for Low-Emission T680 Day Cab Drayage Truck Projects in California*. URL: <http://tinyurl.com/zm84j3d>
- [85] Forbes, 2017. *Toyota Rolls Out Hydrogen Semi Ahead Of Tesla's Electric Truck*. URL: <https://tinyurl.com/ljs9xke>
- 1475 [86] Nikola Motor Company, 2016. *Nikola One: Electric Sleeper Semi-Truck*. URL: <https://nikolamotor.com/one>
- [87] Velazquez Abad A, Cherrett T and Waterson B, 2016. *Sim-heuristics low-carbon technologies' selection framework for reducing costs and carbon emissions of heavy goods vehicles*. *International Journal of Logistics Research and Applications*, **20**(1): 3-19.
- [88] Intelligent Energy, 2017. *Met trials hydrogen powered scooters*. URL: <https://tinyurl.com/yddjx4yl>
- 1480 [89] Alstom, 2016. *Alstom unveils its zero-emission train Coradia iLint at InnoTrans*. URL: <http://www.alstom.com/press-centre/2016/9/alstom-unveils-its-zero-emission-train-coradia-ilint-at-innotrans/>
- [90] Thompson S, 2016. *The Origin of Hydrail and the International Journal of Hydrogen Energy*, in *International Association for Hydrogen Energy Electronic Newsletter*. URL: [http://hydrail.org/sites/hydrail.org/files/IAHENewsletter\\_Dec2016.pdf](http://hydrail.org/sites/hydrail.org/files/IAHENewsletter_Dec2016.pdf)
- [91] Ballard Power Systems, 2015. *Ballard Signs Framework Agreement for Fuel Cell Module Development to Power Trams in China*. URL: <http://ballard.com/about-ballard/newsroom/news-releases/news06101501.aspx>
- 1485 [92] Baldassari E, 2016. *Hydrogen-powered ferry? National lab says it's possible, though costly* in *East Bay Times*. URL: <http://www.eastbaytimes.com/2016/11/14/hydrogen-powered-ferry-national-lab-says-its-possible-though-costly/>
- [93] ICAO, 2016. *Historic agreement reached to mitigate international aviation emissions*. International Civil Aviation Organization. URL: <http://www.icao.int/Newsroom/Pages/Historic-agreement-reached-to-mitigate-international-aviation-emissions.aspx>
- 1490 [94] Gonzalez C, 2016. *The Future of Electric Hybrid Aviation*, in *Machine Design*. URL: <http://machinedesign.com/batteriespower-supplies/future-electric-hybrid-aviation>
- [95] IPCC, 2013. *Climate Change 2013: The Physical Science Basis. Contribution of Working Group I to the Fifth Assessment Report of the Intergovernmental Panel on Climate Change*: Cambridge University Press. URL: <http://ipcc.ch/report/ars/wg1/>
- 1495 [96] Lawson C, 2016. *eTaxi Fuel Cell System - Feasibility for Low Cost Carriers*. Presented at *Royal Aeronautical Society*. London. URL: <http://tinyurl.com/jny07fu>
- [97] US Department of Energy, 2016. *Industry Deployed Fuel Cell-Powered Lift Trucks*.

- [98] Ahmad Mayyas MW, Shuk Han Chan, Tim Lipman, 2014. *Fuel Cell Forklift Deployment in the U.S.* NREL. URL: <http://www.nrel.gov/analysis/pdfs/Fuel%20Cell%20Forklift%20Deployment%20in%20the%20US.pdf>
- 1500 [99] Ballard Power Systems, 2010. *Economics of Fuel Cell Solutions for Material Handling*. URL: [http://ballard-power.developmentwebsite.ca/docs/default-source/motive-modules-documents/material-handling/mh\\_econbenefits\\_fcvelocity\\_041411.pdf](http://ballard-power.developmentwebsite.ca/docs/default-source/motive-modules-documents/material-handling/mh_econbenefits_fcvelocity_041411.pdf)
- [100] New Holland, 2017. *NH2 Hydrogen Tractor*. URL: <http://www.newholland.co.nz/?id=155>
- [101] International Energy Agency, 2016. *Energy Technology Perspectives*. Paris: OECD/IEA.
- 1505 [102] Lapillonne B and Pollier K, 2014. *ODYSSEE-MURE: Energy Efficiency Trends for households in the EU*. Enerdata.
- [103] Chaudry M, Abeysekera M, Hosseini SHR, Jenkins N and Wu J, 2015. *Uncertainties in decarbonising heat in the UK*. Energy Policy, **87**: 623-640.
- [104] Eyre N, 2016. *Decarbonising Heat*. Presented at *Oxford Energy Expert Meeting*. London. URL: <http://www.energy.ox.ac.uk/wordpress/wp-content/uploads/2015/01/Decarbonising-Heat-NE-introduction.pdf>
- 1510 [105] Staffell I, Hamilton I and Green R, 2015. *The Residential Energy Sector*, in *Domestic Microgeneration: Renewable and Distributed Energy Technologies, Policies and Economics*, Staffell I, Brett DJL, Brandon NP, and Hawkes AD, Editors. Routledge: London.
- [106] Staffell I, Brett DJL, Brandon NP and Hawkes AD, 2015. *Domestic Microgeneration: Renewable and Distributed Energy Technologies, Policies and Economics*. London: Routledge.
- 1515 [107] DBEIS, 2016. *Baroness Neville-Rolfe's speech at Policy Exchange's Heat Summit*. URL: <https://www.gov.uk/government/speeches/baroness-neville-rolfes-speech-at-the-policy-exchanges-heat-summit>
- [108] Richard Howard ZB, 2016. *Too Hot to Handle? How to decarbonise domestic heating*. Policy Exchange. URL: <https://policyexchange.org.uk/publication/too-hot-to-handle/>
- [109] Dodds PE, Hawkes A, McDowall W, Li F, et al., 2014. *The role of hydrogen and fuel cells in providing affordable, secure low-carbon heat*. London: H2FC SUPERGEN.
- 1520 [110] Grant Wilson IA, 2016. *Energy Data Visualization Requires Additional Approaches to Continue to be Relevant in a World with Greater Low-Carbon Generation*. *Frontiers in Energy Research*, **4**(33).
- [111] CCC, 2016. *Next steps for UK heat policy*. Committee on Climate Change. URL: <https://www.theccc.org.uk/wp-content/uploads/2016/10/Next-steps-for-UK-heat-policy-Committee-on-Climate-Change-October-2016.pdf>
- 1525 [112] Staffell I, Brett D, Brandon N and Hawkes A, 2012. *A review of domestic heat pumps*. *Energy & Environmental Science*, **5**(11): 9291-9306.
- [113] Hanna R, Parrish B and Gross R, 2016. *Best practice in heat decarbonisation policy: A review of the international experience of policies to promote the uptake of low-carbon heat supply*. UKERC Working Paper. URL: <https://www.theccc.org.uk/wp-content/uploads/2017/01/UKERC-for-the-CCC-Best-practice-in-heat-decarbonisation-policy.pdf>
- 1530 [114] Boßmann T and Staffell I, 2015. *The shape of future electricity demand: Exploring load curves in 2050s Germany and Britain*. *Energy*, **90**, Part 2: 1317-1333.
- [115] International Energy Agency, 2012. *World Energy Balances*: ESDS International, University of Manchester. URL: <http://dx.doi.org/10.5257/iea/web/2012>
- [116] GEA, 2012. *Global Energy Assessment: Toward a Sustainable Future*: Cambridge University Press.
- 1535 [117] O OL, Ürge-Vorsatz D, Ahmed AZ, Akbari H, et al., 2014. *Buildings*, in *Climate Change 2014: Mitigation of Climate Change. Contribution of Working Group III to the Fifth Assessment Report of the Intergovernmental Panel on Climate Change*, Edenhofer O, Pichs-Madruga R, Sokona Y, Farahani E, et al., Editors: Cambridge University Press.
- [118] European Climate Foundation, 2010. *Roadmap 2050: A Practical Guide to a Prosperous, Low Carbon Europe*.
- [119] Ofgem, 2016. *Future Insights Series: The Decarbonisation of Heat*.
- 1540 [120] MacLean K, Sansom R, Watson T and Gross R, 2016. *Comparing the impacts and costs of transitions in heat infrastructure*. URL: <http://www.imperial.ac.uk/media/imperial-college/research-centres-and-groups/icept/Heat-infrastructure-paper.pdf>
- [121] Staffell I and Pfenninger S, 2018. *The increasing impact of weather on electricity supply and demand*. *Energy*, **145**: 65-78.
- [122] DECC, 2016. *Heat Networks Investment Project Consultation: Capital Funding For Building Heat Networks*. URL: [https://www.gov.uk/government/uploads/system/uploads/attachment\\_data/file/532483/HNIP\\_consultation\\_vFINAL.pdf](https://www.gov.uk/government/uploads/system/uploads/attachment_data/file/532483/HNIP_consultation_vFINAL.pdf)
- 1545 [123] Lidstone L, 2016. *UK Networks Transition Challenges: Heat*. Energy Technologies Institute. URL: <https://dzumxknyjne36n.cloudfront.net/insightReports/Network-Transitions-Heat.pdf>
- [124] Staffell I, Baker P, Barton JP, Bergman N, et al., 2010. *UK microgeneration. Part II: technology overviews*. Proceedings of the ICE - Energy, **163**(4): 143-165.
- [125] Staffell I and Hamilton I, 2015. *Cross-Cutting Issues for Microgeneration*, in *Domestic Microgeneration: Renewable and Distributed Energy Technologies, Policies and Economics*, Staffell I, Brett DJL, Brandon NP, and Hawkes AD, Editors. Routledge: London.
- 1550 [126] US Census Bureau, 2014. *Annual Characteristics of New Housing*. URL: <http://www.census.gov/construction/chars/>
- [127] DECC, 2013. *The Future of Heating: Meeting the challenge*. URL: [https://www.gov.uk/government/uploads/system/uploads/attachment\\_data/file/190149/16\\_04-DECC-The\\_Future\\_of\\_Heating\\_Accessible-10.pdf](https://www.gov.uk/government/uploads/system/uploads/attachment_data/file/190149/16_04-DECC-The_Future_of_Heating_Accessible-10.pdf)
- 1555



- [128] Palmer J and Cooper I, 2013. *United Kingdom housing energy fact file*. London: Department of Energy and Climate Change.
- [129] CCC, 2017. *Meeting Carbon Budgets: Closing the policy gap. 2017 Report to Parliament*. London. URL: <https://www.theccc.org.uk/wp-content/uploads/2017/06/2017-Report-to-Parliament-Meeting-Carbon-Budgets-Closing-the-policy-gap.pdf>
- 1560 [130] Hodges J, Geary W, Graham S, Hooker P and Goff R, 2015. *Injecting hydrogen into the gas network – a literature search*. Health and Safety Laboratory: Buxton. URL: <http://www.hse.gov.uk/research/rrpdf/rr1047.pdf>
- [131] Dorrington M, Lewitt M, Summerfield I, Robson P and Howes J, 2016. *Desk study on the development of a hydrogen-fired appliance supply chain*. Kiwa & E4 Tech. URL: [https://www.gov.uk/government/uploads/system/uploads/attachment\\_data/file/537594/30686\\_Final\\_Report\\_DECC\\_Hydrogen\\_appliances\\_08.07.16.pdf](https://www.gov.uk/government/uploads/system/uploads/attachment_data/file/537594/30686_Final_Report_DECC_Hydrogen_appliances_08.07.16.pdf)
- 1565 [132] Staffell I and Entchev E, 2015. *Micro-CHP Engines*, in *Domestic Microgeneration: Renewable and Distributed Energy Technologies, Policies and Economics*, Staffell I, Brett DJL, Brandon NP, and Hawkes AD, Editors. Routledge: London.
- [133] Staffell I, 2015. *Zero carbon infinite COP heat from fuel cell CHP*. Applied Energy, **147**: 373-385.
- [134] Ellamla HR, Staffell I, Bujlo P, Pollet BG and Pasupathi S, 2015. *Current status of fuel cell based combined heat and power systems for residential sector*. Journal of Power Sources, **293**: 312-328.
- 1570 [135] Stolten D, Samsun RC and Garland N, 2015. *Fuel Cells – Data, Facts and Figures*. Weinheim: Wiley-VCH.
- [136] IRENA, 2012. *Renewable Energy Technologies: Cost Analysis Series. Volume 1, Issue 4: Solar Photovoltaics*. URL: <https://tinyurl.com/irena-cost-1-4>
- [137] Panasonic, 2013. *Launch of New 'Ene-Farm' Home Fuel Cell Product More Affordable and Easier to Install*.
- 1575 [138] Nagata Y, 2013. *Toshiba Fuel Cell Power Systems ~ Commercialization of Residential FC in Japan*. Presented at FCH-JU General Assembly. Brussels. URL: <http://tinyurl.com/q8ov9td>
- [139] Staffell I, 2010. *Fuel cells for domestic heat and power: Are they worth it?* PhD Thesis, University of Birmingham. URL: <http://tinyurl.com/fcchp-worth-it>
- [140] Kuwaba K, 2013. *Development of SOFC for Residential Use by Aisin Seiki*. Presented at 9th FC Expo. Tokyo.
- 1580 [141] Osaka Gas, 2012. *Long-term durability data for single-cell*. URL: <http://tinyurl.com/osaka-sofc-longterm>
- [142] Ballhausen A, 2013. *BlueGen: Vom Feldversuch in den Markt (From Field Tests to Market)*. Presented at NIP General Assembly. Berlin. URL: <http://tinyurl.com/psvs3av>
- [143] Staffell I and Green R, 2013. *The cost of domestic fuel cell micro-CHP systems*. International Journal of Hydrogen Energy, **38**(2): 1088-1102.
- 1585 [144] Kawamura S, 2017. *IPHE Country Update: Japan*. Presented at 28th IPHE Steering Committee Meeting. The Hague, Netherlands.
- [145] Wei M, Smith SJ and Sohn MD, 2017. *Experience curve development and cost reduction disaggregation for fuel cell markets in Japan and the US*. Applied Energy, **191**: 346-357.
- [146] Wei M, Chan SH, Mayyas A and Lipman T, 2016. *Deployment and Capacity Trends for Stationary Fuel Cell Systems in the USA*, in *Fuel Cells: Data, Facts, and Figures*, Stolten D, Samsun RC, and Garland N, Editors. Wiley VCH.
- 1590 [147] Maruta A, 2016. *Japan's ENE-FARM programme*. Presented at Open Workshop: "Fuel cells: Why is Austria not taking off?". URL: <https://www.energyagency.at/fileadmin/dam/pdf/projekte/gebaeude/Maruta.pdf>
- [148] Roland Berger, 2015. *Advancing Europe's energy systems: Stationary fuel cells in distributed generation*. European Commission: FCH-JU. URL: <https://dx.doi.org/10.2843/088142>
- 1595 [149] 2016. *ExxonMobil and FuelCell Energy, Inc. Pursue Novel Technology in Carbon Capture* URL: <https://tinyurl.com/exxon-fuelcell-energy>
- [150] International Energy Agency, 2016. *CO<sub>2</sub> Emissions from Fuel Combustion*. URL: <http://dx.doi.org/10.5257/iea/co2/2012>
- [151] BP, 2017. *BP Statistical Review of World Energy*.
- [152] International Energy Agency, 2016. *World Energy Outlook*. Paris. URL: [http://www.iea.org/bookshop/720-World\\_Energy\\_Outlook\\_2016](http://www.iea.org/bookshop/720-World_Energy_Outlook_2016)
- 1600 [153] Deep Decarbonization Pathways Project, 2015. *Pathways to deep decarbonization 2015 report*: SDSN - IDDRI.
- [154] IPCC, 2014. *Climate Change 2014 - Mitigation of Climate Change. Contribution of Working Group III to the Fifth Assessment Report of the Intergovernmental Panel on Climate Change*. URL: <http://ipcc.ch/report/ar5/wg3>
- [155] Kriegler E, Weyant JP, Blanford GJ, Krey V, et al., 2014. *The role of technology for achieving climate policy objectives: overview of the EMF 27 study on global technology and climate policy strategies*. Climatic change, **123**(3): 353-367.
- 1605 [156] IPCC, 2014. *Climate Change 2014. Synthesis Report. Summary for Policymakers*. URL: <http://www.ipcc.ch/report/ar5/syr/>
- [157] Green R and Staffell I, 2016. *Electricity in Europe: exiting fossil fuels?* Oxford Review of Economic Policy, **32**(2): 282-303.
- [158] Royal Academy of Engineering, 2014. *Counting the cost: the economic and social costs of electricity shortfalls in the UK*.
- [159] Platts, 2016. *World Electric Power Plants Database*.
- 1610 [160] Fuel Cell Today, 2011. *The Industry Review 2011*.
- [161] U.S. Department of Energy, 2007. *2007 Fuel Cell Technologies Market Report*.
- [162] Adamson K-A, 2016. *The Fuel Cell and Hydrogen Annual Review 2016*. URL: <http://tinyurl.com/4ew-fchar>

- [163] Wessof E, *Fuel Cells 2016: 'Within Striking Distance of Profitability'*. URL: <http://tinyurl.com/zmmkecb>
- 1615 [164] Chiesa P, Lozza G and Mazzocchi L, 2005. *Using Hydrogen as Gas Turbine Fuel*. Journal of Engineering for Gas Turbines and Power, **127**(1): 73-80.
- [165] ETI, 2015. *The role of hydrogen storage in a clean responsive power system*. Energy Technologies Institute: Loughborough, UK. URL: <http://www.eti.co.uk/insights/carbon-capture-and-storage-the-role-of-hydrogen-storage-in-a-clean-responsive-power-system/>
- 1620 [166] EPA, 2008. *Catalog of CHP Technologies*. U.S. Environmental Protection Agency Combined Heat and Power Partnership. URL: <http://tinyurl.com/b4z7qer>
- [167] Osaka Gas, 2012. *Review of Operations*. URL: <http://tinyurl.com/ckpxcmc>
- [168] Bloom Energy, *ES-5700 Energy Server Data Sheet*. URL: <http://www.bloomenergy.com/fuel-cell/es-5700-data-sheet/>
- [169] New York Times, 2010. *A Maker of Fuel Cells Blooms in California*. URL: <http://tinyurl.com/j5csg7w>
- [170] Bloom Energy, *NASA™ Technology Comes to Earth*. URL: <http://www.bloomenergy.com/about/company-history/>
- 1625 [171] Smith R, 2016. *3 Top Hydrogen Fuel Cell Stocks You Can Buy Right Now*. URL: <http://www.fool.com/investing/2016/11/28/should-you-invest-in-a-fuel-cell-stock.aspx>
- [172] Hardman S, Chandan A and Steinberger-Wilckens R, 2015. *Fuel cell added value for early market applications*. Journal of Power Sources, **287**: 297-306.
- [173] Staffell I, 2017. *Measuring the progress and impacts of decarbonising British electricity*. Energy Policy, **102**: 463-475.
- 1630 [174] Letendre S, Denholm P and Lilienthal P, 2006. *Electric & Hybrid Cars: New Load, or New Resource?*, in *Public Utilities Fortnightly*. Public Utilities Reports, Inc. URL: <https://www.fortnightly.com/fortnightly/2006/12/electric-hybrid-cars-new-load-or-new-resource>
- [175] EREC, 2013. *Re-thinking 2050: A 100% renewable energy vision for the European Union*. European Renewable Energy Council.
- 1635 [176] Tomic J and Kempton W, 2007. *Using fleets of electric-drive vehicles for grid support*. Journal of Power Sources, **168**(2): 459-468.
- [177] Kempton W, Jasna T, Steven L, Alec B and Timothy L, 2001. *Vehicle-to-Grid Power: Battery, Hybrid, and Fuel Cell Vehicles as Resources for Distributed Electric Power in California*. California Air Resources Board and the California Environmental Protection Agency.
- 1640 [178] Kempton W and Tomic J, 2005. *Vehicle-to-grid power fundamentals: Calculating capacity and net revenue*. Journal of Power Sources, **144**(1): 268-279.
- [179] Lipman TE, Edwards JL and Kammen DM, 2004. *Fuel cell system economics: comparing the costs of generating power with stationary and motor vehicle PEM fuel cell systems*. Energy Policy, **32**(1): 101-125.
- 1645 [180] Strbac G, Aunedi M, Pudjianto D, Djapic P, et al., 2012. *Strategic Assessment of the Role and Value of Energy Storage Systems in the UK Low Carbon Energy Future*. London, UK: Carbon Trust. URL: <http://tinyurl.com/c7gubyk>
- [181] Moura F, 2006. *Driving Energy System Transformation with "Vehicle-to-Grid" Power*. IIASA. URL: <http://pure.iiasa.ac.at/8072/>
- [182] Diaz-Gonzalez F, Sumper A, Gomis-Bellmunt O and Villafafila-Robles R, 2012. *A review of energy storage technologies for wind power applications*. Renewable & Sustainable Energy Reviews, **16**(4): 2154-2171.
- 1650 [183] Grams CM, Beerli R, Pfenninger S, Staffell I and Wernli H, 2017. *Balancing Europe's wind-power output through spatial deployment informed by weather regimes*. Nature Climate Change, **7**(8): 557-562.
- [184] Holladay JD, Hu J, King DL and Wang Y, 2009. *An overview of hydrogen production technologies*. Catalysis Today, **139**: 244-260.
- 1655 [185] Parra D and Patel MK, 2016. *Techno-economic implications of the electrolyser technology and size for power-to-gas systems*. International Journal of Hydrogen Energy, **41**(6): 3748-3761.
- [186] Bertuccioli L, Chan A, Hart D, Lehner F, et al., 2014. *Study on development of water electrolysis in the EU*. URL: <http://tinyurl.com/h2dgojw>
- [187] Schmidt O, Gambhir A, Staffell I, Hawkes A, et al., 2017. *Future cost and performance of water electrolysis: An expert elicitation study*. International Journal of Hydrogen Energy **42**(52): 30470-30492.
- 1660 [188] Gahleitner G, 2013. *Hydrogen from renewable electricity: An international review of power-to-gas pilot plants for stationary applications*. International Journal of Hydrogen Energy, **38**(5): 2039-2061.
- [189] Reiter G, 2015. *Power-to-Gas*, in *Fuel Cells – Data, Facts and Figures*, Stolten D, Samsun RC, and Garland N, Editors. Wiley-VCH: Weinheim.
- 1665 [190] Balan OM, Buga MR, Brunot A, Badea A and Froelich D, 2016. *Technical and economic evaluation of Power-to-Gas in link with a 50 MW wind park*. Journal of Energy Storage, **8**: 111-118.
- [191] Gotz M, Lefebvre J, Mors F, Koch AM, et al., 2016. *Renewable Power-to-Gas: A technological and economic review*. Renewable Energy, **85**: 1371-1390.
- [192] Zhang F, Zhao PC, Niu M and Maddy J, 2016. *The survey of key technologies in hydrogen energy storage*. International Journal of Hydrogen Energy, **41**(33): 14535-14552.
- 1670 [193] Sabatier P and Senderens JB, 1902. *New synthesis of methane*. Comptes Rendus, **134**(514).

- [194] Lehner M, Tichler R, Steinmüller H and Koppe M, 2014. *Power-to-Gas: Technology and Business Models*: Springer International Publishing.
- [195] Jentsch M, Trost T, Sterner M and Eurosolar, 2014. *Optimal Use of Power-to-Gas Energy Storage Systems in an 85% Renewable Energy Scenario*. 8th International Renewable Energy Storage Conference and Exhibition (Ires 2013), **46**: 254-261.
- 1675 [196] M S and M. J., 2011. *Energiewirtschaftliche und ökologische Bewertung eines Windgas-Angebotes*. URL: <https://tinyurl.com/y7xufmja>
- [197] International Gas Union, 2012. *Triennium 2009-2012. Working Committee 2: Underground Gas Storage. WOC2 Final Report*. URL: <http://tinyurl.com/yc965zf6>
- 1680 [198] Bailera M, Lisbona P, Romeo LM and Espatolero S, 2017. *Power to Gas projects review: Lab, pilot and demo plants for storing renewable energy and CO<sub>2</sub>*. *Renewable & Sustainable Energy Reviews*, **69**: 292-312.
- [199] Kopp M, Coleman D, Stiller C, Scheffer K, et al., 2017. *Energiepark Mainz: Technical and economic analysis of the worldwide largest Power-to-Gas plant with PEM electrolysis*. *International Journal of Hydrogen Energy*, **42**(19): 13311-13320.
- 1685 [200] Schiebahn S, Grube T, Robinius M, Tietze V, et al., 2015. *Power to gas: Technological overview, systems analysis and economic assessment for a case study in Germany*. *International Journal of Hydrogen Energy*, **40**(12): 4285-4294.
- [201] Clegg S and Mancarella P, 2016. *Storing renewables in the gas network: modelling of power-to-gas seasonal storage flexibility in low-carbon power systems*. *Int Generation Transmission & Distribution*, **10**(3): 566-575.
- [202] Vandewalle J, Bruninx K and D'Haeseleer W, 2015. *Effects of large-scale power to gas conversion on the power, gas and carbon sectors and their interactions*. *Energy Conversion and Management*, **94**: 28-39.
- 1690 [203] de Boer HS, Grond L, Moll H and Benders R, 2014. *The application of power-to-gas, pumped hydro storage and compressed air energy storage in an electricity system at different wind power penetration levels*. *Energy*, **72**: 360-370.
- [204] Qadrdan M, Abeysekera M, Chaudry M, Wu JZ and Jenkins N, 2015. *Role of power-to-gas in an integrated gas and electricity system in Great Britain*. *International Journal of Hydrogen Energy*, **40**(17): 5763-5775.
- [205] Vanhoudt W, Barth F, Lanoix J-C, Neave J, et al., 2016. *Power-to-gas: Short term and long term opportunities to leverage synergies between the electricity and transport sectors through power-to-hydrogen*: Munich. URL: <http://tinyurl.com/y7ovktow>
- 1695 [206] Guandalini G, Campanari S and Romano MC, 2015. *Power-to-gas plants and gas turbines for improved wind energy dispatchability: Energy and economic assessment*. *Applied Energy*, **147**: 117-130.
- [207] FCH-JU, 2015. *Commercialisation of Energy Storage in Europe*. URL: <http://tinyurl.com/ktz2dm6>
- 1700 [208] Goltsov VA and Veziroglu TN, 2001. *From hydrogen economy to hydrogen civilization*. *International Journal of Hydrogen Energy*, **26**(9): 909-915.
- [209] National Research Council and National Academy of Engineering, 2004. *The Hydrogen Economy: Opportunities, Costs, Barriers, and R&D Needs*: Washington, DC: The National Academies Press. URL: <https://doi.org/10.17226/10922>
- [210] Balat M and Kirtay E, 2010. *Major Technical Barriers to a "Hydrogen Economy"*. *Energy Sources, Part A: Recovery, Utilization, and Environmental Effects*, **32**(9): 863-876.
- 1705 [211] Turner JA, 1999. *A Realizable Renewable Energy Future*. *Science*, **285**(5428): 687-689.
- [212] Royal Society Policy Briefing, 2018. *Options for producing low-carbon hydrogen at scale*. URL: <https://royalsociety.org/~media/policy/projects/hydrogen-production/energy-briefing-green-hydrogen.pdf>
- [213] OECD/IEA, 2007. *IEA Energy Technology Essentials: Hydrogen Production & Distribution*. URL: <http://www.iea.org/techno/essentials5.pdf>
- 1710 [214] Evers AA, 2008. *Actual Worldwide Hydrogen Production*. URL: <http://tinyurl.com/89h9zot>
- [215] MarketsandMarkets, 2011. *Hydrogen Generation Market - by Merchant & Captive Type, Distributed & Centralized Generation, Application & Technology - Trends & Global Forecasts (2011 - 2016)*: Dallas, Texas.
- [216] Wawrzinek K and Keller C, 2007. *Industrial Hydrogen Production & Technology*. Presented at *Funchy-Workshop*. Karlsruhe, Germany. URL: <http://tinyurl.com/7ax4fjr>
- 1715 [217] Mougín J, 2015. *8 - Hydrogen production by high-temperature steam electrolysis*, in *Compendium of Hydrogen Energy*. Woodhead Publishing: Oxford. p. 225-253. URL: <https://www.sciencedirect.com/science/article/pii/B978178242361400008X>
- [218] Buttler A and Spliethoff H, 2018. *Current status of water electrolysis for energy storage, grid balancing and sector coupling via power-to-gas and power-to-liquids: A review*. *Renewable and Sustainable Energy Reviews*, **82**: 2440-2454.
- 1720 [219] Muhich CL, Ehrhart BD, Al-Shankiti I, Ward BJ, et al., 2016. *A review and perspective of efficient hydrogen generation via solar thermal water splitting*. *Wiley Interdisciplinary Reviews: Energy and Environment*, **5**(3): 261-287.
- [220] Yadav D and Banerjee R, 2016. *A review of solar thermochemical processes*. *Renewable and Sustainable Energy Reviews*, **54**: 497-532.
- 1725 [221] Azwar MY, Hussain MA and Abdul-Wahab AK, 2014. *Development of biohydrogen production by photobiological, fermentation and electrochemical processes: A review*. *Renewable and Sustainable Energy Reviews*, **31**: 158-173.
- [222] Poudyal RS, Tiwari I, Koirala AR, Masukawa H, et al., 2015. *10 - Hydrogen production using photobiological methods*, in *Compendium of Hydrogen Energy*. Woodhead Publishing: Oxford. p. 289-317. URL: <https://www.sciencedirect.com/science/article/pii/B9781782423614000108>

- 1730 [223] Brett DJL, Agante E, Brandon NP, Brightman E, *et al.*, 2012. *The role of the fuel in the operation, performance and degradation of fuel cells*, in *Functional materials for sustainable energy applications*, Kilner J, Skinner S, Irvine S, and Edwards P, Editors. Woodhead Publishing: Cambridge.
- [224] Gupta RB, 2008. *Hydrogen Fuel, Production, Transport and Storage*: CRC Press.
- 1735 [225] Sadler D, Cargill A, Crowther M, Rennie A, *et al.*, 2016. *H21 Leeds City Gate: 100% hydrogen conversion feasibility study*. URL: <http://tinyurl.com/leeds-H21>. URL: <http://tinyurl.com/leeds-H21>
- [226] Susmozas A, Iribarren D, Zapp P, Linßen J and Dufour J, 2016. *Life-cycle performance of hydrogen production via indirect biomass gasification with CO<sub>2</sub> capture*. International Journal of Hydrogen Energy, **41**(42): 19484-19491.
- [227] Florin NH and Harris AT, 2008. *Enhanced hydrogen production from biomass with in situ carbon dioxide capture using calcium oxide sorbents*. Chemical Engineering Science, **63**(2): 287-316.
- 1740 [228] Hirschhausen Cv, Herold J and Oei P-Y, 2012. *How a "Low Carbon" Innovation Can Fail--Tales from a "Lost Decade" for Carbon Capture, Transport, and Sequestration*. Economics of Energy & Environmental Policy, **1**(2): 115-123.
- [229] Scott V, Gilfillan S, Markusson N, Chalmers H and Haszeldine RS, 2012. *Last chance for carbon capture and storage*. Nature Climate Change, **3**: 105.
- [230] Slade R, Bauen A and Gross R, 2014. *Global bioenergy resources*. Nature Clim. Change, **4**(2): 99-105.
- 1745 [231] Matthews R, Mortimer N, Lesschen JP, Lindroos TJ, *et al.*, 2015. *Carbon impacts of biomass consumed in the EU: quantitative assessment*: The European Commission DG ENER/C1/427.
- [232] Zeng K and Zhang D, 2010. *Recent progress in alkaline water electrolysis for hydrogen production and applications*. Progress in Energy and Combustion Science, **36**(3): 307-326.
- [233] Carmo M, Fritz DL, Mergel J and Stolten D, 2013. *A comprehensive review on PEM water electrolysis*. International Journal of Hydrogen Energy, **38**(12): 4901-4934.
- 1750 [234] Kreuter W and Hofmann H, 1998. *Electrolysis: The important energy transformer in a world of sustainable energy*. International Journal of Hydrogen Energy, **23**(8): 661-666.
- [235] US Department of Energy, 2016. *Hydrogen Production: Electrolysis*. URL: <http://energy.gov/eere/fuelcells/hydrogen-production-electrolysis>
- 1755 [236] Schmidt O, Hawkes A, Gambhir A and Staffell I, 2017. *The future cost of electrical energy storage based on experience rates*. Nature Energy, **2**: 17110.
- [237] US Department of Energy, 2015. *Future Central Hydrogen Production from Solid Oxide Electrolysis*, in *Central Natural Gas*, US DoE, Editor: Washington, DC. URL: [https://www.hydrogen.energy.gov/h2a\\_prod\\_studies.html](https://www.hydrogen.energy.gov/h2a_prod_studies.html)
- [238] Ebbesen SD, Jensen SH, Hauch A and Mogensen MB, 2014. *High Temperature Electrolysis in Alkaline Cells, Solid Proton Conducting Cells, and Solid Oxide Cells*. Chemical Reviews, **114**(21): 10697-10734.
- 1760 [239] Laguna-Bercero MA, 2012. *Recent advances in high temperature electrolysis using solid oxide fuel cells: A review*. Journal of Power Sources, **203**(Supplement C): 4-16.
- [240] Myung J-h, Neagu D, Miller DN and Irvine JTS, 2016. *Switching on electrocatalytic activity in solid oxide cells*. Nature, **537**: 528.
- 1765 [241] Joos M and Staffell I, 2018. *Short term integration costs of Variable Renewable Energy Sources – Recent developments in Great Britain and Germany*. Renewable & Sustainable Energy Reviews, **In Press**.
- [242] Wipke K, Sprik S, Kurtz J, Ramsden T, *et al.*, 2011. *Status of U.S. FCEV and Infrastructure Learning Demonstration Project*. Presented at *The FY2010 JHFC International Seminar*. Tokyo. URL: <http://tinyurl.com/3rqh2su>
- [243] National Renewable Energy Laboratory, 2010. *CDP#13: On-Site Hydrogen Production Efficiency*. URL: [http://www.nrel.gov/hydrogen/cdp\\_number.html](http://www.nrel.gov/hydrogen/cdp_number.html)
- 1770 [244] National Renewable Energy Laboratory, 2010. *CDP#60: On-Site Hydrogen Production Efficiency vs. Capacity Utilization*. URL: [http://www.nrel.gov/hydrogen/cdp\\_number.html](http://www.nrel.gov/hydrogen/cdp_number.html)
- [245] Monde M and Saito K, 2011. *WG1: Hydrogen Infrastructure WG*. Presented at *JHFC International Seminar*. Tokyo, Japan. URL: <http://tinyurl.com/3pmuvty>
- 1775 [246] Tomuro J, 2009. *Hydrogen Stations - JHFC Activities in FY2008*. Presented at *IPHE 11th ILC Meeting*. Oslo, Norway. URL: <http://tinyurl.com/ydbfc9m>
- [247] Okazaki K, 2005. *Operation Results and Efficiency Evaluation of JHFC Hydrogen Stations*. Presented at *The 4th JHFC Seminar for Japanese FY2005*. Tokyo. URL: <http://tinyurl.com/y7qcw4dk>
- [248] Hanke-Rauschenbach R, Bensmann B and Millet P, 2015. *7 - Hydrogen production using high-pressure electrolyzers*, in *Compendium of Hydrogen Energy*. Woodhead Publishing: Oxford. p. 179-224. URL: <https://www.sciencedirect.com/science/article/pii/B9781782423614000078>
- 1780 [249] Parks G, Boyd R, Cornish J and Remick R, 2014. *Hydrogen Station Compression, Storage, and Dispensing Technical Status and Costs*. NREL: Golden, CO.
- [250] IEA, 2015. *Technology Roadmap: Hydrogen and Fuel Cells*. International Energy Agency: Paris, France. URL: <http://www.iea.org/publications/freepublications/publication/TechnologyRoadmapHydrogenandFuelCells.pdf>
- 1785 [251] LCICG, 2014. *Technology Innovation Needs Assessment (TINA): Hydrogen for Transport*. Low Carbon Innovation Coordination Group.

- [252] Di Bella F, 2015. *Development of a Centrifugal Hydrogen Pipeline Gas Compressor*. DoE. URL: <https://www.osti.gov/scitech/biblio/1227195-development-centrifugal-hydrogen-pipeline-gas-compressor>
- 1790 [253] HyET, 2011. *Compressor without moving parts reaches 800 Bar*. URL: [http://www.hyet.nl/images/stories/110823hyet\\_reaches\\_800\\_bar.pdf](http://www.hyet.nl/images/stories/110823hyet_reaches_800_bar.pdf)
- [254] Lipp L, 2016. *Electrochemical Hydrogen Compressor*. EERE. URL: <https://doi.org/10.2172/1235441>
- [255] Kitchener A, 2016. *Bridging the pressure gap*. Presented at *Future of CAES in the UK*. London. URL: [http://www2.warwick.ac.uk/fac/sci/eng/research/grouplist/electricalpower/images/members/shared/theshard/presentations/pressure\\_gap\\_ak.pdf](http://www2.warwick.ac.uk/fac/sci/eng/research/grouplist/electricalpower/images/members/shared/theshard/presentations/pressure_gap_ak.pdf)
- 1795 [256] US Department of Energy, 2015. *Multi-Year Research, Development, and Demonstration Plan. Section 3.2 - Hydrogen Delivery*. Fuel Cell Technologies Office, US Department of Energy. URL: [https://energy.gov/sites/prod/files/2015/08/f25/fcto\\_myRDD\\_delivery.pdf](https://energy.gov/sites/prod/files/2015/08/f25/fcto_myRDD_delivery.pdf)
- [257] Krasae-in S, Stang JH and Neksa P, *Development of large-scale hydrogen liquefaction processes from 1898 to 2009*. International Journal of Hydrogen Energy, **35**(10): 4524-4533.
- 1800 [258] International Organization for Standardization, 2012. *ISO 14687-2:2012*. URL: <https://www.iso.org/standard/55083.html>
- [259] Grigoriev SA, Millet P, Korobtsev SV, Porembskiy VI, et al., 2009. *Hydrogen safety aspects related to high-pressure polymer electrolyte membrane water electrolysis*. International Journal of Hydrogen Energy, **34**(14): 5986-5991.
- [260] Ito H, Miyazaki N, Ishida M and Nakano A, 2016. *Cross-permeation and consumption of hydrogen during proton exchange membrane electrolysis*. International Journal of Hydrogen Energy, **41**(45): 20439-20446.
- 1805 [261] Hamdan M, 2014. *High Efficiency Large PEM Electrolyzers*. Presented at *H2FC Fair*. Hannover Messe. URL: <http://www.h2fc-fair.com/hm14/images/tech-forum-presentations/2014-04-07-1300.pdf>
- [262] Sircar S and Golden T, 2000. *Purification of hydrogen by pressure swing adsorption*. Sep Sci Technol, **35**: 667-687.
- [263] Melaina MW, Antonia O and Penev M, 2013. *Blending Hydrogen into Natural Gas Pipeline Networks: A Review of Key Issues*. NREL Technical Report NREL/TP-5600-51995.
- 1810 [264] Yang C and Ogden J, 2007. *Determining the lowest-cost hydrogen delivery mode*. International Journal of Hydrogen Energy, **32**(2): 268-286.
- [265] Kotchourko A, Baraldi D, Bénard P, Eisenreich N, et al., 2014. *State of the art and research priorities in hydrogen safety*: Joint Research Centre of the European Commission (JRC).
- 1815 [266] van der Zwaan BCC, Schoots K, Rivera-Tinoco R and Verbong GPI, 2011. *The cost of pipelining climate change mitigation: An overview of the economics of CH<sub>4</sub>, CO<sub>2</sub> and H<sub>2</sub> transportation*. Applied Energy, **88**(11): 3821-3831.
- [267] Nanninga NE, Levy YS, Drexler ES, Condon RT, et al., 2012. *Comparison of hydrogen embrittlement in three pipeline steels in high pressure gaseous hydrogen environments*. Corrosion Science, **59**: 1-9.
- [268] Gangloff RP and Somerday BP, 2012. *Gaseous Hydrogen Embrittlement of Materials in Energy Technologies*. Vol. 2: Woodhead Publishing. i-iii. URL: <https://www.sciencedirect.com/science/article/pii/B9781845696771500211>
- 1820 [269] Tabkhi F, Azzaro-Pantel C, Pibouleau L and Domenech S, 2008. *A mathematical framework for modelling and evaluating natural gas pipeline networks under hydrogen injection*. International Journal of Hydrogen Energy, **33**(21): 6222-6231.
- [270] Reitenbach V, Ganzer L, Albrecht D and Hagemann B, 2015. *Influence of added hydrogen on underground gas storage: a review of key issues*. Environmental Earth Sciences, **73**(11): 6927-6937.
- 1825 [271] Abeysekera M, Wu J, Jenkins N and Rees M, 2016. *Steady state analysis of gas networks with distributed injection of alternative gas*. Applied Energy, **164**(Supplement C): 991-1002.
- [272] Guandalini G, Colbertaldo P and Campanari S, 2017. *Dynamic modeling of natural gas quality within transport pipelines in presence of hydrogen injections*. Applied Energy, **185**(Part 2): 1712-1723.
- [273] Dodds PE and McDowall W, 2013. *The future of the UK gas network*. Energy Policy, **60**: 305-316.
- 1830 [274] Staffell I, 2011. *The Energy and Fuel Data Sheet*. URL: <http://tinyurl.com/energy-fuel-data-sheet>
- [275] ITM Power, National Grid, Shell, SSE, et al., 2013. *Power-To-Gas: A UK Feasibility Study*. Sheffield: ITM Power.
- [276] Ispos MORI and Energy Saving Trust, 2013. *Homeowners' Willingness To Take Up More Efficient Heating Systems*. DECC: London. URL: <https://tinyurl.com/decc-more-efficient-heating>
- [277] Vaughan A, 2017. *Trial to phase in hydrogen as fuel to begin in north-west*, in *The Guardian*. URL: <https://www.theguardian.com/business/2017/aug/07/trial-to-phase-in-hydrogen-as-fuel-to-begin-in-north-west>
- 1835 [278] Williams TI, 1981. *A History of the British Gas Industry*. Oxford, UK: Oxford University Press.
- [279] The Global Carbon Capture and Storage Institute, *CCS Ready Policy: Considerations and Recommended Practices for Policymakers* URL: <https://tinyurl.com/gccsi-capture-ready>
- [280] Policy Connect, 2017. *Next Steps for the Gas Grid*. URL: <http://www.policyconnect.org.uk/cc/research/next-steps-gas-grid-future-gas-series-part-1>
- 1840 [281] Ferreira HL, Garde R, Fulli G, Kling W and Lopes JP, 2013. *Characterisation of electrical energy storage technologies*. Energy, **53**(Supplement C): 288-298.
- [282] Ozarslan A, 2012. *Large-scale hydrogen energy storage in salt caverns*. International Journal of Hydrogen Energy, **37**(19): 14265-14277.
- 1845 [283] Staffell I and Rustomji M, 2016. *Maximising the value of electricity storage*. Journal of Energy Storage, **8**: 212-225.

- [284] Nissan, 2016. *Nissan unveils world's first Solid-Oxide Fuel Cell vehicle*. URL: <http://nissannews.com/en-US/nissan/usa/releases/nissan-unveils-world-s-first-solid-oxide-fuel-cell-vehicle>
- [285] Klebanoff L, 2016. *Hydrogen Storage Technology: Materials and Applications*. Boca Raton: FL: CRC Press.
- [286] Ley MB, Jepsen LH, Lee Y-S, Cho YW, et al., 2014. *Complex hydrides for hydrogen storage – new perspectives*. *Materials Today*, **17**(3): 122-128.
- 1850 [287] Klebanoff LE and Keller JO, 2013. *5 Years of hydrogen storage research in the U.S. DOE Metal Hydride Center of Excellence (MHCoE)*. *International Journal of Hydrogen Energy*, **38**(11): 4533-4576.
- [288] Hydrogenious Technologies, 2016. *Hydrogenious Release BOX*. URL: [http://hydrogenious.net/wp-content/uploads/2016/03/HT\\_Flyer\\_ReleaseBOX.pdf](http://hydrogenious.net/wp-content/uploads/2016/03/HT_Flyer_ReleaseBOX.pdf)
- 1855 [289] Toyota, 2014. *Toyota Mirai technical specifications vs FCHV-adv*. URL: <http://blog.toyota.co.uk/toyota-mirai-technical-specifications-vs-fchv-adv>
- [290] James BD, Colella WG and Moton JM, 2013. *Hydrogen Storage Cost Analysis*. DOE Annual Merit Review, : Arlington, VA. URL: [http://www.hydrogen.energy.gov/pdfs/progress14/iv\\_a\\_2\\_james\\_2014.pdf](http://www.hydrogen.energy.gov/pdfs/progress14/iv_a_2_james_2014.pdf)
- [291] European Commission, 2014. *DIRECTIVE 2014/94/EU on the deployment of alternative fuels infrastructure*. European Commission: Brussels. URL: <http://eur-lex.europa.eu/legal-content/EN/TXT/PDF/?uri=CELEX:32014L0094&from=EN>
- 1860 [292] European Commission, 2009. *DIRECTIVE 2009/28/EC on the promotion of the use of energy from renewable sources and amending and subsequently repealing Directives 2001/77/EC and 2003/30/EC*. European Commission: Brussels. URL: <http://eur-lex.europa.eu/legal-content/EN/TXT/PDF/?uri=CELEX:32009L0028&from=EN>
- [293] European Commission, 2016. *Proposal for a DIRECTIVE OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on the promotion of the use of energy from renewable sources (recast)*. European Commission: Brussels. URL: [http://ec.europa.eu/energy/sites/ener/files/documents/1\\_en\\_act\\_part1\\_v7\\_1.pdf](http://ec.europa.eu/energy/sites/ener/files/documents/1_en_act_part1_v7_1.pdf)
- 1865 [294] European Commission, 2017. *DIRECTIVE on the promotion of the use of energy from renewable sources (recast)*. European Commission: Brussels. URL: <http://eur-lex.europa.eu/legal-content/EN/TXT/PDF/?uri=CELEX:32009L0028&from=EN>
- [295] US DoE, 2017. *Federal Laws and Incentives for Hydrogen*. URL: <http://www.afdc.energy.gov/fuels/laws/HY/US>
- 1870 [296] HM Government and Automotive council UK, 2018. *Industrial Strategy: Automotive Sector Deal*, Business Eals, Editor. Crown: London. URL: [https://www.gov.uk/government/uploads/system/uploads/attachment\\_data/file/672824/automotive-sector-deal-double-pages.pdf](https://www.gov.uk/government/uploads/system/uploads/attachment_data/file/672824/automotive-sector-deal-double-pages.pdf)
- [297] Velazquez Abad A, 2017. *Techno-economic Comparison between Battery and Fuel Cell Electric Vehicles*, in *Southampton Business School*. University of Southampton: Southampton.
- 1875 [298] IPHE, 2017. *27th Steering Committee Meeting: Country Reports*. URL: [http://www.iphe.net/events/meetings/SC\\_27.html](http://www.iphe.net/events/meetings/SC_27.html)
- [299] DfT, OLEV and Hayes J, 2017. *£23 million boost for hydrogen-powered vehicles and infrastructure*, Transport Df, Vehicles OfLE, and MP TRHJHC, Editors. Crown: London. URL: <https://www.gov.uk/government/news/23-million-boost-for-hydrogen-powered-vehicles-and-infrastructure>
- 1880 [300] METI, 2016. *Compilation of the Revised Version of the Strategic Roadmap for Hydrogen and Fuel Cells*. URL: [http://www.meti.go.jp/english/press/2016/0322\\_05.html](http://www.meti.go.jp/english/press/2016/0322_05.html)
- [301] Maruta A, 2016. *Japan's ENE-FARM programme* Technova Inc: Vienna. URL: [https://www.energyagency.at/fileadmin/dam\\_en/pdf/fuelcells/Maruta.pdf](https://www.energyagency.at/fileadmin/dam_en/pdf/fuelcells/Maruta.pdf)
- [302] BMVI, 2016. *Fortsetzung des Nationalen Innovationsprogramms Wasserstoff- und Brennstoffzellentechnologie (NIP) 2016 – 2026 in Nationales innovationsprogramm*. BMVI: Berlin. URL: <https://www.now-gmbh.de/content/2-nationales-innovationsprogramm/2-foerderprogramm/nipii-massnahmen-bmvi.pdf>
- 1885 [303] NOW, 2016. *Government programme for hydrogen and fuel cell technology 2016-2026*. National Organisation Hydrogen and Fuel Cell Technology. URL: <https://www.now-gmbh.de/en/news/press/government-programme-for-hydrogen-and-fuel-cell-technology-2016-2026>
- [304] Rosner P and Appel G, 2016. *BOSCH FUEL CELL SYSTEM Experience in Austria and Germany*. URL: [https://www.energyagency.at/fileadmin/dam\\_en/pdf/fuelcells/Appel\\_Rosner.pdf](https://www.energyagency.at/fileadmin/dam_en/pdf/fuelcells/Appel_Rosner.pdf)
- 1890 [305] NOW, 2016. *Hydrogen as an electricity-based clean fuel in transport*. URL: <https://www.now-gmbh.de/en/news/press/hydrogen-as-an-electricity-based-clean-fuel-in-transport>
- [306] Acosta Iborra B, Gupta E and Seissler L, 2016. *4th International Workshop on Hydrogen Infrastructure and Transportation*, in *JRC Conference and Workshop Reports* European Commission, Editor. JRC: Luxembourg. URL: <http://publications.jrc.ec.europa.eu/repository/bitstream/JRC103586/4%20int%20workshop%20on%20h2%20infra%20final%20pdfonline.pdf>
- 1895 [307] US Department of Energy, 2016. *Federal Legislation Supports and Advances Alternative Fuels*. URL: [https://www.afdc.energy.gov/bulletins/2016\\_10\\_11\\_Fed\\_Advances.html](https://www.afdc.energy.gov/bulletins/2016_10_11_Fed_Advances.html)
- 1900 [308] MOTIE, 2015. *Korean government to increase the number of eco-friendly cars to one million by 2020*. URL: <https://tinyurl.com/MOTIE-2015-12-08>
- [309] HM Government, 2017. *Industrial Strategy: Automotive Sector Deal*. URL: <https://tinyurl.com/ybah838e>
- [310] Steinberger-Wilckens R, Radcliffe J, Al-Mufachi N, Dodds PE, et al., 2017. *The role of hydrogen and fuel cells in delivering energy security for the UK*. H2FC Supergen: London, UK.

- 1905 [311] Smith MJ, Alabi O, Hughes N, Dodds PE, et al., 2017. *The economic impact of hydrogen and fuel cells in the UK*. H2FC Supergen: London, UK.
- [312] State Council, 2015. *Made in China 2025*, Technology Molal, Editor: Beijing. URL: <http://www.cittadellascienza.it/cina/wp-content/uploads/2017/02/IoT-ONE-Made-in-China-2025.pdf>
- 1910 [313] ANRE, 2014. *Summary of the Strategic Road Map for Hydrogen and Fuel Cells*, METI, Editor. Agency for Natural Resources and Energy.: Tokyo. URL: [www.meti.go.jp/english/press/2014/pdf/0624\\_04a.pdf](http://www.meti.go.jp/english/press/2014/pdf/0624_04a.pdf)
- [314] METI, 2017. *Japan's Energy White Paper*. URL: [http://www.meti.go.jp/english/report/downloadfiles/energy\\_hakusho\\_201711.pdf](http://www.meti.go.jp/english/report/downloadfiles/energy_hakusho_201711.pdf)
- [315] Defra and DfT, 2017. *Plan for roadside NO2 concentrations published in Plan includes an end to the sale of all new conventional petrol and diesel cars and vans by 2040 and a new Clean Air Fund* Defra, Editor. Crown: London. URL: <https://www.gov.uk/government/news/plan-for-roadside-no2-concentrations-published>
- 1915 [316] Ministère de la Transition écologique et solidaire, 2017. *Mobilités et transports : quelles priorités ?*, solidaire MdtTée, Editor. Département Images et Édition: Paris. URL: <https://www.ecologique-solidaire.gouv.fr/mobilites-et-transports-quelles-priorites>
- [317] VVD, CDA, D66 and CU, 2017. *Confidence in the Future. 2017–2021 Coalition Agreement*, Affairs MoG, Editor. Ministry of General Affairs: Amsterdam. URL: <https://www.government.nl/binaries/government/documents/publications/2017/10/10/coalition-agreement-confidence-in-the-future/coalition-agreement-2017-confidence-in-the-future.pdf>
- 1920 [318] NEA, 2016. *Climate mitigation measures up to 2030 - short term climate effects and health effects*, Agency NE, Editor: Oslo. URL: [www.miljodirektoratet.no/Documents/publikasjoner/M494/M494.pdf](http://www.miljodirektoratet.no/Documents/publikasjoner/M494/M494.pdf)
- 1925 [319] Irfan U, 2016. *Lack of Cheap, Clean Hydrogen Slows Fuel-Cell Cars*, in *Scientific American*. URL: <https://www.scientificamerican.com/article/lack-of-cheap-clean-hydrogen-slows-fuel-cell-cars/>
- [320] EERE, 2017. *Cumulative U.S. Fuel Cell Vehicle Sales*. URL: <https://tinyurl.com/eere-fact-17-01>
- [321] Pan X, 2017. *IPHE Country Update March 2017: China*. International Partnership for Hydrogen and Fuel Cells in the Economy: Brussels. URL: <http://www.iphe.net/docs/Meetings/SC27/Country%20Reports/China%20Country%20Report.pdf>
- 1930 [322] Karlsson T, 2017. *Developments and Drivers for Fuel Cells Electric Mobility*. Presented at *2017 International Forum on Electric Vehicle Pilot Cities and Industrial Development*. URL: [http://www.iphe.net/docs/HomePage\\_RecentInfo/IPHE%20Presentation%20to%20Clean%20Energy%20Ministerial%20Side%20Event%20June%202017.pdf](http://www.iphe.net/docs/HomePage_RecentInfo/IPHE%20Presentation%20to%20Clean%20Energy%20Ministerial%20Side%20Event%20June%202017.pdf)
- [323] US Department of Energy, 2018. *Hydrogen Fueling Station Locations*. URL: [https://www.afdc.energy.gov/fuels/hydrogen\\_locations.html](https://www.afdc.energy.gov/fuels/hydrogen_locations.html)
- 1935 [324] Delta-ee, 2013. *Micro-CHP Annual Roundup 2012*. URL: <http://www.delta-ee.com/research-consulting-services/micro-chp-service>
- [325] Ohira E, 2017. *Private communication of Japanese representative to the IEA Hydrogen meeting: Naples*. Presented.
- [326] Hara I, 2013. *Current Status of H2 and Fuel Cell Programs of Japan*. Presented at *20th IPHE Steering Committee Meeting*. Fukuoka, Japan. URL: <http://tinyurl.com/pj5pee6>
- 1940 [327] Shimizu A, 2017. *Will Japan's hydrogen dreams come true?*, in *Bloomberg New Energy Finance*.
- [328] Small M, 2017. *European-wide field trials for residential Fuel Cell micro-Cogeneration* Presented at *FCH-JU Programme Review Days*. Brussels. URL: <https://tinyurl.com/fch-enefield-pace-2017-11-23>
- [329] Biebuyck B, 2016. *EU policy & micro-CHP*. URL: <http://iphe.net/partners/europeancommission.html>
- 1945 [330] Yamazumi M and Kawamura S, 2016. *IPHE Country Update November 2016: JAPAN*. URL: <http://iphe.net/partners/japan.html>
- [331] Ko S, 2016. *IPHE Country Update May 2016: Korea*. URL: <http://iphe.net/partners/republicofkorea.html>
- [332] Dewald U and Truffer B, 2011. *Market Formation in Technological Innovation Systems—Diffusion of Photovoltaic Applications in Germany*. *Industry and Innovation*, **18**(3): 285-300.
- 1950 [333] Certifhy, 2016. *Developing a European Framework for the generation of guarantees of origin for green hydrogen*, in *Certifhy*. Hinicio: Brussels.