

The influence of uncertain loading on topology-optimized designs

Philipp Hofer^{1,2} and Erich Wehrle¹

¹ Free University of Bozen-Bolzano, Universitätsplatz 1, 39100 Bozen, South Tyrol, Italy, Philipp.Hofer@natec.unibz.it, Erich.Wehrle@unibz.it

² Master student, Faculty of Mechanical Engineering, Technical University of Munich, Boltzmannstr. 15, 85748 Garching, Germany, philipp96.hofer@tum.de

Correspondence: Philipp Hofer (philipp96.hofer@tum.de)

Abstract. The design of structures using topology optimization can improve the structural performance and save material, in turn reducing costs. Using a framework of large-scale, three-dimensional topology optimization implemented by the authors in an open-source multiphysical software, we investigate the influence of uncertain loading on the optimized design. Direct differentiation is used to reveal the relationship between displacements and applied force, giving an efficient and effective tool to postprocess optimized topologies. The developed methodology for the assessment of the sensitivity with respect to applied forces is explored using two three-dimensional examples: the classic MBB cantilever and a cableway pylon. The advantages and limitations of this method are discussed.

1 Introduction

In the development of new structures and mechanical systems, the proper load collective is critical for correct design and dimensioning. Unforeseen usage, misuse and re-purposing afflict the developed load collective with uncertainty and risk.

As topology optimization designs structures by finding the optimally allocated material for a specific load case or load collective, the uncertainty of loads is especially of interest. In this work, we pose the question, how “optimal” are designs with respect to (w.r.t.) the intrinsic uncertainty of load cases? Using the direct differentiation of the optimized compliance w.r.t. the applied loads, a framework is shown to quickly (and without further system evaluation) assess the influence of uncertain loading on the optimized design.

Topology optimization is a numerical method, which in concert with finite-element analysis, searches for the optimal allocation of material within a design domain (packaging) for a load case or a set of load cases (load collective). Topology optimization has seen recent attention as an essential tool for the Virtuous Circle of Lightweight Engineering Design (Wehrle and Gufler, 2021) in which lighter systems result in lowered loading as well as reduced material use and lower costs and therefore resulting in even lighter designs. The advent of additive manufacturing has further strengthened the attention to this design tool. Additive technologies allow for a practical manufacturing method for the resulting optimized topologies, which in past required elaborate and skilled interpretation to derive manufacturable designs (Langelaar, 2017).

Uncertainty is a well-established challenge in topology optimization. To handle geometrical uncertainty associated with nano-manufacturing, a robust topology optimization method is developed in Lazarov et al. (2012); Wang et al. (2010). In Achleitner

25 and Wehrle (2022), the latter methodology is extended to find not only geometrically robust designs, but also to improve convergence of the optimization algorithm when considering stress constraints. A robust method considering uncertain forces in a level-set framework is introduced in Dunning et al. (2011). To consider uncertain loading direction, Wu et al. (2016) introduce an interval-based robust topology optimization method.

30 Uncertainty in mechanical engineering design can be categorized into three categories: uncertain geometry, uncertain material and uncertain loading. Further, the modeling itself adds uncertainty via abstraction and simplification. The aim of this work is to assess the sensitivity of an optimum design w.r.t. uncertain loads and thereby giving feedback to the design engineer how susceptible the optimum design is to changes. The optimization will be carried out using Kratos Multiphysics and its Topology Optimization Application development by Hofer (2021) as an extension to Gonzalez (2015); Malfavon (2016). The developed methodology is based on the simple direct differentiation applied to the converged solutions and delivers meaningful results
35 regarding the robustness w.r.t. to the load case to the design engineer.

2 Topology optimization

Topology optimization solves the design problem of the optimal material use by parameterizing the density, which is then scaled between zero and unity, i.e. no material and full material,

$$x_i \in [0, 1], \quad (1)$$

40 where x_i is the i th design variable. The design domain is discretized using finite elements and the density of each element is variable and therefore x_i is the density of the i th element. In this work, topology optimization is implemented using the modified *solid isotropic material with penalization* (SIMP), first introduced by Bendsøe (1989) and modified by Sigmund (2007),

$$E_i = E_{\min} + (E_0 - E_{\min}) x_i^p, \quad (2)$$

where E_0 is the Young's modulus for the base material. For this modification a minimal Young's modulus $E_{\min}$ is introduced to
45 avoid singularities in global stiffness matrix. Additionally, the penalty term p provides a more discrete solution of the problem. Within this work, a penalty term of $p = 3$ is used (Bendsøe and Sigmund, 2003).

2.1 Optimization formulation

In topology optimization, the optimal material distribution is sought for a defined design domain and load case. For achieving efficiently stiff structures, the compliance C is minimized for a specified volume fraction v_{frac} , resulting in the optimization
50 formulation,

$$\min_{\underline{x} \in X} \{C(\underline{x})\}, \quad (3)$$

$$\text{subject to } g_j(\underline{x}) \leq 0, \quad j = 1, \dots, a,$$

$$h_k(\underline{x}) = 0, \quad k = 1, \dots, n.$$

Compliance is defined here as the strain energy for a defined load. Therefore, the minimization of compliance formulation
55 can be interpreted as a maximization of the stiffness for a given load. The compliance of the given structure with the design variables $\underline{x}$ and the force $\underline{F}$ can be calculated as follows:

$$C(\underline{x}) = \underline{F}^T \underline{u}. \quad (4)$$

Using the dependency of the displacement $\underline{u}$ and the global stiffness matrix $\underline{k}$,

$$\underline{F} = \underline{k} \underline{u}, \quad (5)$$

60 we calculate the compliance on an element basis, shown here for the i th element,

$$C_i(x_i) = \underline{u}_i^T \underline{k}_i \underline{u}_i. \quad (6)$$

The volume fraction v_{frac} is the ratio of the material used, to that of a full design domain V_Ω ,

$$v_{\text{frac}} = \frac{\sum_i x_i V_i}{V_\Omega}, \quad (7)$$

and is defined as an inequality constraint with respect to a prescribed volume fraction v_{max} ,

$$65 \quad g = \sum_i x_i V_i - v_{\text{max}} V_\Omega. \quad (8)$$

The modified SIMP approach is used for the element compliance (6) and summing these up over the elements of the design domain based on the elemental stiffness matrix of the base material of the i th element $\underline{k}_{0,i}$, the modified optimization problem reads as

$$\min_{x_i \in X} \left\{ \sum_i C_i(x_i) \right\}, \quad (9)$$

$$70 \quad \text{where } C_i(x_i) = (E_{\text{min}} + x_i^p (E_0 - E_{\text{min}})) \underline{u}_i^T \underline{k}_{0,i} \underline{u}_i,$$

$$\text{subject to } g(\underline{x}) = \sum_i x_i V_i - v_{\text{frac}} V_\Omega \leq 0,$$

$$\text{and } 0 \leq x_i \leq 1.$$

2.2 Sensitivity analysis

The sensitivities, i.e. gradients, of the design variables w.r.t. the objective and constraint functions are computed and provided
75 to the optimization algorithm. With this information, the design variable values are updated for the next iteration. As topology optimization typically carries more design variables than objective and constraint functions, the adjoint method is used in order to efficiently calculate the sensitivities.

The compliance sensitivity (6) is calculated for all elements. Applying the adjoint method and the simplifications as well as the modified SIMP approach, the objective function gradient of every element can be calculated as

$$\frac{\partial C}{\partial x_i} = -p x_i^{p-1} (E_0 - E_{\min}) \underline{u}_i^T \underline{k}_{0,i} \underline{u}_i. \quad (10)$$

The constraint sensitivity too can be calculated for every element. Due to the fact that every element has a constant volume, the constraint function sensitivity can be written as:

$$\frac{\partial g}{\partial x_i} = 1. \quad (11)$$

2.3 Sensitivity filtering

In order to avoid common problems with topology optimization, such as checkerboard patterns, different filtering methods can be used. In the case of this work, the sensitivity filtering is implemented in the optimization process in order to avoid such difficulties (Sigmund and Petersson, 1998). Checkerboard patterns refer to areas in the design domain that have full and zero density in neighboring elements, giving rise to a structure that looks like a checker- or chessboard (checkerboard patterns can be seen in fig. 8 (a), where a too low filter radius was used for the filtering process). Checkerboarding results in an unmanufacturable design as well as artificially (numerically) high stiffness (Bendsøe and Sigmund, 2003). The filtering of the sensitivities considering the surrounding elements alleviates this issue. Based on the value of these sensitivities and a weighting factor $H_{i,j}$, the gradient of the given element is altered. The weighting factor $H_{i,j}$ evaluates the distance from the i th element to the j th neighboring element.

The weighting of the surrounding elements of a given element can be seen in fig. 1, where the distance determines the influence of the neighboring element properties. Depending on the filter radius, a certain number of neighboring elements are considered. Mathematically, this filtering of the sensitivities is given by

$$\left. \frac{\partial C}{\partial x_i} \right|_{\text{filt}} = \left(\frac{\sum_j H_{i,j} x_j \partial C / \partial x_j}{\max(x_i, \gamma) \sum_j H_{i,j}} \right). \quad (12)$$

The weighting factor is defined by (Sigmund, 2007)

$$H_{i,j} = \max(0, r_{\min} - \text{dist}(i, j)), \quad (13)$$

where $r_{\min}$ represents the filter radius. With the difference of the radius value and the distance between the given element i and the element from which the sensitivity is considered (described by the index j), the factor can be calculated.

2.4 Optimization algorithm

The optimization problem is solved in this work using the Optimality Criteria (OC) algorithm, which is commonly used in topology optimization (Aage et al., 2015). The OC algorithm searches iteratively for the optimal design using the sensitivities of objective and constraint functions. A Lagrange multiplier is introduced to handle the constraint function, here volume fraction. This is done by using a bisectional algorithm.




Figure 1. Filter weighting factor $H_{i,j}$ with the filter radius $r_{\min}$.

The update of the design variable values is given by (Bendsøe, 1995)

$$x_i = \begin{cases} \max(0, x_i - m), & \text{for } x_i B_i^\eta \leq \max(0, x_i - m), \\ \min(0, x_i + m), & \text{for } x_i B_i^\eta \geq \min(1, x_i + m), \\ x_i B_i^\eta, & \text{else.} \end{cases} \quad (14)$$

For this iterative process, the tuning parameters m and η are needed, where m represents the move limit of the design variable and set here to 0.2. The tuning parameter η is introduced for numerical damping purposes and is set here to 0.5 (Bendsøe and Sigmund, 2003).

To evaluate the design variable, B_i is defined from the optimality condition as:

$$B_i = -\frac{1}{\lambda} \frac{\partial f / \partial x_i}{\partial g / \partial x_i}, \quad (15)$$

with $\partial f / \partial x_i$ being the objective function sensitivity defined as the compliance sensitivity $\partial C / \partial x_i$ and $\partial g / \partial x_i$ the constraint sensitivity, which has the value of unity for every element. The former is introduced in sec. 2.2 of which the filtered sensitivities are used (sec. 2.3). The volume constraint sensitivity is constant throughout the optimization and is simply the identity matrix for uniform meshes, as used here (Andreassen et al., 2011).

To determine if convergence has been reached, the relative change in the objective function is observed,

$$\frac{C(\underline{x}_k) - C(\underline{x}_{k-1})}{C(\underline{x}_0)} \leq \epsilon_{\text{stop}}. \quad (16)$$

For the following observations, the convergence criteria was set to $\epsilon_{\text{stop}} = 10^{-6}$. Further, there is a heuristic stopping criteria of maximum iterations, which was set to 200 iterations in this investigation.

2.5 Compliance sensitivity and robustness with respect to force

In this work, the variation of the force and the resulting impact on the compliance is investigated. This is carried out in a post-optimization step to assess the consequence in the applied load. By changing the force vector on the structure and optimizing the design domain, the uncertainty in load cases and the resulting optimized topologies are investigated.

Directly differentiating (5) w.r.t. the i th force F_i gives

$$\frac{\partial \underline{k}}{\partial F_i} \underline{u} + \underline{k} \frac{\partial \underline{u}}{\partial F_i} = \frac{\partial \underline{F}}{\partial F_i}, \quad (17)$$

and solving for displacement sensitivity w.r.t. to the force vector reveals

$$\frac{\partial \underline{u}}{\partial F_i} = \underline{k}^{-1} \left(\frac{\partial \underline{F}}{\partial F_i} - \frac{\partial \underline{k}}{\partial F_i} \underline{u} \right). \quad (18)$$

The compliance sensitivity w.r.t. force is found by applying the chain rule applied to (4),

$$\frac{\partial C}{\partial F_i} = \frac{\partial \underline{F}}{\partial F_i} \underline{u} + \underline{F}^T \left(\underline{k}^{-1} \left(\frac{\partial \underline{F}}{\partial F_i} - \frac{\partial \underline{k}}{\partial F_i} \underline{u} \right) \right). \quad (19)$$

The sensitivity of the stiffness matrix w.r.t. force is zero in linear-elastic analysis. The sensitivity of the force vector w.r.t. to a single force (or multiple forces) is a vector with ones at the point of interest and zero else, denoted here as e_i . The compliance sensitivity w.r.t. to force simplifies to

$$\begin{aligned} \frac{\partial C}{\partial F_i} &= e_i \underline{u} + \underline{u} e_i, \\ &= 2 \sum_i u_i. \end{aligned} \quad (20)$$

Summarizing, the compliance sensitivity w.r.t. to force is twice the resulting displacement of the degree of freedom of the force (or forces) in question.

Although *design robustness* can have a wide range of understandings in engineering design, in this work it is defined in line with the following definitions:

Box & Fung (1994): *Robustness means insensitivity to variation* (Box and Fung, 1994).

Arvidsson & Gremyr (2008): *Robust Design Methodology means systematic efforts to achieve insensitivity to noise factors* (Arvidsson and Gremyr, 2008).

Taguchi (1986): *Robustness is the state where the technology, product, or process performance is minimally sensitive to factors causing variability* (Taguchi, 1986).

Mathematically, this is therefore defined in this work as the inverse of the sensitivity w.r.t. the uncertainty or noise factors, i.e. here compliance w.r.t. force,

$$\mathcal{R}_{C,F_i} = \frac{1}{|\partial C / \partial F_i|}. \quad (21)$$

It should be noted that the absolute value of the compliance sensitivity is used as robustness measure of *how sensitive* a structure is and not *how it changes*. Specifically, the higher the sensitivity (gradient) of the compliance w.r.t. the force, the higher the resulting variation and the lower the robustness (Kemmler et al., 2015). For the extreme case of infinite robustness, the sensitivity is zero while for zero robustness, the sensitivity is infinity.

3 Results of numerical investigations to uncertain loading

In this study, uncertain loading is explored in topology optimization with three-dimensional domains on two examples. The first example is the classic MBB cantilever, e.g. Sigmund (2001), in which the out-of-plane dimension is much smaller than the in-plane dimensions, resulting in a relatively thin-walled cantilever. The second example, developed in Hofer (2021) finds the optimized topology of a cableway pylon.

3.1 Thin-walled MBB cantilever

The Messerschmitt–Bölkow–Blohm (MBB) cantilever is a classic benchmark example in topology optimization. It stems from a structural problem of the company Messerschmitt–Bölkow–Blohm (now integrated into Airbus SE) in the design of a floor structure of the Airbus passenger aircraft (Bulman et al., 2001). Considering the MBB cantilever, the change of the compliance in respect of the changing force is investigated. For this investigation, a three-dimensional MBB cantilever of the dimensions $60 \times 20 \times 4$ mm (see fig. 2) is used. The given cantilever beam is considered having a generic isotropic material with a Young's modulus of 1 Pa. The finite-element model has a regular mesh using 1 mm element length, resulting in 4800 hexahedral elements and 6408 nodes.

Two base load cases will be investigated below: 1) a downward load of $\underline{F} = [0.0, -1.0, 0.0]^T$ N, and 2) a diagonal load of $\underline{F} = [0.5, -0.5, 0.5]^T$ N. These base load cases are used for the numerical investigation of uncertain loading.

3.1.1 MBB cantilever under downward loading condition

The first load case foresees a downward (negative y) load. In the following, this load is varied in x , y and z and the compliance sensitivities are calculated.

To investigate the optimized design, the load is varied. In different optimization processes the force in y -direction is increased or decreased, whereas in the x - and z -direction a force is added in the positive or negative direction. To avoid to large step sizes and to evaluate also small variations, the change of the force or the added load was 0.1, 0.2 and 0.3 N in both positive and negative directions. The resulting optimized topologies can be seen in fig. 4.

On the other hand, when investigating the sensitivities, the step sizes were chosen smaller. Due to the fact that a sensitivity is an information of the given condition, the best way to numerically calculate these values is to choose a very low step size. Additionally, the MBB beam is thin walled in the z -direction, which could lead to a sensitive behavior and therefore a smaller step size should improve the results.




Figure 2. Thin-walled MBB cantilever, showing design domain, boundary condition, loading and exemplary optimized topology for downward load case and diagonal load case in red and green, respectively.




Figure 3. Optimized compliance w.r.t. to change in applied force for the MBB cantilever, ● optimization results, — expected from analytical sensitivity, base load of $\underline{F} = [0.0, -1.0, 0.0]^T$ N.




Figure 4. Optimized topology w.r.t. to change in applied force for the MBB cantilever with base load of $\underline{F} = [0.0, -1.0, 0.0]^T$ N.

Fig. 3 shows the optimized compliance w.r.t. the force in x , y and z , respectively. For both variation of force in x and y , the relationship is nearly linear. For the force in z , the compliance increases in both negative and positive directions as this is a increase in the load. In fact this compliance sensitivity shows a quadratic form w.r.t. force (see fig. 3). Further of interest is the compliance sensitivity in x : the compliance increases with a compression of the structure, but with a load in positive x -direction, the compliance decreases. This means that although an increase in the magnitude of the load, the stiffness of the structure can be increased.

The analytical sensitivities of the compliance w.r.t. the forces used in the diagrams in fig. 3 can be calculated. For this, the displacement is taken at the node where the force is acting on the structure. Therefore the displacement of the degree of freedom of the applied force. The sensitivity is defined simply by twice the displacement (20).

For the calculation of the compliance sensitivity, the displacements are considered where the structure is loaded (here a point load),

$$\underline{u}_i = \begin{bmatrix} u_{i,x} \\ u_{i,y} \\ u_{i,z} \end{bmatrix} = \begin{bmatrix} -11.7877 \\ -50.348 \\ -0.00989191 \end{bmatrix} \text{ mm.}$$

The compliance sensitivities calculated via (20) are given by

$$\frac{\partial C}{\partial F_i} = \begin{bmatrix} \partial C / \partial F_x \\ \partial C / \partial F_y \\ \partial C / \partial F_z \end{bmatrix} = \begin{bmatrix} -23.5754 \\ 100.696 \\ -0.01978 \end{bmatrix} \text{ mm.}$$

It should be noted that force in y -direction is negative and therefore an increase of the force is negative, which changes the sign of the sensitivity from negative to positive. The numerical values of the sensitivities given by the optimization tool and the different force variation can be seen in fig. 5 and they are listed in the table 1.

Table 1. Analytical and numerical (using forward differencing) compliance sensitivities w.r.t. to force for varying step sizes for the MBB cantilever with base load of $\underline{F} = [0.0, -1.0, 0.0]^T$ N.

method	step size [N]	compliance sensitivity [mm] w.r.t.		
		x -force	y -force	z -force
analytical	-	-23.5754	-100.696	-0.01978
numerical	0.25	-21.5662	-88.0697	178.9198
	0.1	-23.5443	-87.5041	45.6747
	0.05	-22.9254	-97.8153	9.57258
	0.01	-24.8677	-82.6836	13.5410
	0.001	-23.0390	-83.4930	-221.3520
	0.0001	2.3999	-39.7399	-2784.6800

From the compliance sensitivity, we can then calculate the robustness of compliance w.r.t. a change in the defined load case,

$$\mathcal{R}_{C,F_i} = \begin{bmatrix} \frac{1}{|\partial C / \partial F_x|} \\ \frac{1}{|\partial C / \partial F_y|} \\ \frac{1}{|\partial C / \partial F_z|} \end{bmatrix} = \begin{bmatrix} 0.042417 \\ 0.00993088 \\ 50.5561 \end{bmatrix} \frac{1}{\text{mm}}.$$

From this result and comparing it with fig. 3, we can see the weakness of this method. The compliance sensitivity w.r.t. the out-of-plane force F_z is orders of magnitude smaller than the other forces. In fact, the analytical sensitivity is numerically zero, showing no change. As can be seen in the right graph of fig. 3, this value is correct, though only locally at 0 N. This can be therefore especially problematic in the case, when there is no load present in the direction of the sensitivity. To explore this further, we now look at a second load case for which there are non-zero applied forces for the respective compliance sensitivities.

3.1.2 MBB cantilever under diagonal loading condition

As the lack of out-of-plane loading shows nonlinear relationship when a force is added in this direction, a diagonal load is investigated. The optimized topology of this base load case can be seen in fig. 6. Again a load variation is applied and these results are seen in fig. 7. Although relationship shows some nonlinearity when varying the loads up to $\pm 60\%$ of the baseline, the trend is well represented.

We calculate the compliance sensitivity w.r.t. to the force again based on the displacement.

$$\frac{\partial C}{\partial F_i} = \begin{bmatrix} \partial C / \partial F_x \\ \partial C / \partial F_y \\ \partial C / \partial F_z \end{bmatrix} = \begin{bmatrix} -3.00255 \\ 22.3077 \\ 951.361 \end{bmatrix} \text{mm}.$$




Figure 5. Numerical sensitivity of compliance w.r.t. force with varying step size for the MBB cantilever, base load of $\underline{F} = [0.0, -1.0, 0.0]^T$ N, thin line shows calculated analytical value.




Figure 6. Optimized structure of the MBB cantilever with the diagonal load case: $\underline{F} = [0.5, -0.5, 0.5]^T$ N.

This shows agreeance with the numerical results, cf. fig. 7. Based on the sensitivity, we find the robustness,

$$\mathcal{R}_{C, F_i} = \begin{bmatrix} \frac{1}{|\partial C / \partial F_x|} \\ \frac{1}{|\partial C / \partial F_y|} \\ \frac{1}{|\partial C / \partial F_z|} \end{bmatrix} = \begin{bmatrix} 0.33305 \\ 0.0448277 \\ 0.00105113 \end{bmatrix} \frac{1}{\text{mm}}.$$

We now see that the out-of-plane force is better represented by the analytical value, despite the relatively thin-walled nature of the design space in this direction. As expected, the compliance in out-of-plane load is orders of magnitude more sensitive w.r.t.

215 in-plane force.




Figure 7. Optimized compliance w.r.t. to change in applied force for the MBB cantilever, ● optimization results, — expected from analytical sensitivity, base load of $\underline{F} = [0.5, -0.5, 0.5]^T$ N.

3.1.3 MBB cantilever with variation of the sensitivity filter radius

The filter is used on the sensitivities in order to get a better structure and to avoid i.e. checkerboard patterns (cf. sec. 2.3). The size of the radius defines the area from which surrounding elements are considered (see fig. 1).

The impact of the filter radius is investigated on the optimized compliance and its sensitivities with both the downward and diagonal loading conditions. This was done by optimizing the MBB beam with the different filter radii and comparing the results in terms of geometry, compliance value and compliance sensitivity.

In fig. 8, the impact of the filter radius on the optimized topology is seen for the downward loading condition. With a filter size of 1 mm, equivalent to the element size, a significant checkerboarding effect is seen. As expected, with increasing filter radius, the structure becomes more discrete. Fig. 9(a) shows that this results in a significant increase in compliance. It is further shown in fig. 9(b) that the topologies have growing sensitivity to force change with larger filter radii and the corresponding




Figure 8. Optimized topology w.r.t. to filter radius with base load of $\underline{F} = [0.0, -1.0, 0.0]^T$ N. The optimized structure was postprocessed by which the elements were deleted with density $x_i < 0.2$.

increase in compliance. This leads to the assumption that a more manufacturable and discrete topology is paid for with a less stiff structure. Additionally, the structure possesses a lower robustness w.r.t. changes in the load.

The results for diagonal loading fig. 10 for the diagonal load show similar results. The sensitivity with respect to the out-of-plane load F_z is much higher, as expected.

230 The increasing compliance with the increasing filter radius can be explained as follows: We are paying for a more continuous structure (i.e. lack of checkerboarding) with a higher compliance. With an ever larger filter radius, this phenomenon is further increased. The resulting topology is less branched and more compact. But the price is that the structure loses stiffness.

The above effect can be seen analogously for the sensitivities. As seen in the sec. 2.5, the compliance sensitivity of the structure is computed with the displacement in the degree of freedom of the load in question (or the sum therefore). With less
235 structural stiffness, the point will be further deformed, leading to an increase in its sensitivity.

3.2 Cableway pylon

The investigation of the force variation was extended to the large-scale example of a cableway pylon. Topology optimization of such tower-like structures can be performed via ground structure Dorn et al. (1964) and the above described SIMP approach. The former method has been successfully applied to tower structures, e.g. da Silva Smith (1998); Stromberg et al. (2010);




Figure 9. Influence of filter radius for the MBB cantilever with a base load of $\underline{F} = [0.0, 1.0, 0.0]^T$ N.






Figure 10. Influence of filter radius for the MBB cantilever with a base load of $\underline{F} = [0.5, -0.5, 0.5]^T$ N.



(a) Exemplary pylon structure of Ritten's cableway (South Tyrol, Italy), Photograph: STA/Riller.



(b) Schematic view with the yoke (1) upon which the shoes or sheave assembly (2) are mounted, on which in turn the gondola (3) runs to pass the pylon. The yoke itself is mounted onto the design domain (4). The design domain is shown in light gray.



(c) Quarter model used in topology optimization with design domain shown in gray and loaded surface in red.

Figure 11. Cableway pylon.

de Souza et al. (2016), though dictates a design of lattice like members. The SIMP approach has seen use for tower-like structures Stromberg et al. (2010); Tsavdaridis et al. (2020) and will be used here.

An example of such a cableway pylon is shown in fig. 11(a). The according parts of the cableway pylon can be seen in fig. 11(b). The model was constructed such that the area on the ground is fixed and therefore no displacements in this area are allowed. The design domain allows for the gondola to pass the pylon without any problems. The forces onto the pylon are spread over the area on top of the pylon (see red area in fig. 11(c)), where the design domain is connected with the yoke (see fig. 11(b)). For the investigation of the cableway pylon, steel was used and the Young's modulus was set to 206900 MPa.

Due to different load cases and varying situations (gondola ascent or descent, wind in the driving direction or perpendicular to the driving direction etc.), which can occur within the lifetime of the cableway pylon, the resulting force working onto the structure has components in every direction. A simplified load case was developed, evaluating the different load cases and

250 choosing a worst case (in every direction). These loads were set for the optimization process in order to cover all possible load combinations:

$$F_{\text{applied}} = \begin{bmatrix} 60 \\ 115 \\ -400 \end{bmatrix} \text{ kN.}$$

The symmetry of the loads was recognized and a quarter model is taken for the optimization. The results are shown as a full model by mirroring the results over the axes of symmetry. The resulting quarter model is composed of 97152 hexahedral elements and 106225 nodes. The model consists of hexahedral elements of the size $0.5 \times 0.5 \times 0.5$ m.

The force variation for the investigation is realized by varying the existing forces in the main directions. For this the forces are increased or decreased by 1% or 0.5%.

The variation resulted in different compliance values of the structure. In fig. 12 the resulting changes of the forces can be seen. The numerical results show excellent agreement with the analytical sensitivities. This is the case as we are not assessing the sensitivities at unloaded degrees of freedom as with the MBB cantilever. Further, no dimension can be considered relatively thin-walled, in contrast to the MBB case.

The analytical sensitivities of the optimized cableway pylon can be calculated with the displacement at the nodes where the force is working on the structure. In the case of the pylon, the force is working on 25 nodes spread over the area on the top. For the sensitivity the displacements in the force direction have to be added up and then multiplied by two. This results in the following sensitivities:

$$\frac{\partial C}{\partial F_i} = \begin{bmatrix} \partial C / \partial F_x \\ \partial C / \partial F_y \\ \partial C / \partial F_z \end{bmatrix} = \begin{bmatrix} 0.0197291 \\ 0.0838628 \\ -0.0074453 \end{bmatrix} \text{ m.}$$

In fig. 12 the compliance change calculated with the sensitivities is compared with the analytical results. It can be seen that with an increase in the force, the compliance increases too. This means higher forces lead to a structure with lower stiffness.

The robustness of the compliance w.r.t. loading is the inverse of the compliance sensitivity resulting in

$$270 \quad \mathcal{R}_{C, F_i} = \begin{bmatrix} \frac{1}{|\partial C / \partial F_x|} \\ \frac{1}{|\partial C / \partial F_y|} \\ \frac{1}{|\partial C / \partial F_z|} \end{bmatrix} = \begin{bmatrix} 50.6865 \\ 11.9242 \\ 134.3129 \end{bmatrix} \frac{1}{\text{m}}.$$

Through this assessment we can easily see that the resulting design for the cableway pylon is most robust w.r.t. to a downward load, i.e. an axial load, while it is more sensitive in bending, as one may expect. Therefore, especially these loads must be carefully derived in the planning of such a structure.




Figure 12. Optimized compliance w.r.t. to change in applied force for the cableway pylon, ● optimization results, — expected from analytical sensitivity, base load of $\underline{F} = [60000, 115000, -400000]^T$ N.

4 Conclusions

275 The definition of loads, i.e. the loads that a structure will see in its life, is afflicted by uncertainty. As topology optimization designs a structure based on its loading, the proper definition of load collectives is therefore essential to gain useful results. In this work, we derive a methodology to calculate the sensitivity of the resulting compliance w.r.t. to the change in the load case without any further evaluations. This simple, yet useful method gives the designing engineer feedback to the optimized design and the sensitivity to changes in loading.

280 This method though shows limitation when the structure is relatively thin walled, i.e. one dimension is of a smaller order of magnitude and unloaded in this direction. As is shown with the MBB cantilever, when unloaded, the out-of-plane force shows zero sensitivity. In the numerical studies, a new out-of-plane load greatly changes the resulting optimized topology and the

sensitivity is by no means zeros. With the cableway pylon, this aspect is not a problem, showing that the thin-walled case is a special case and in need of further investigation.

285 The investigation of the filter radius shows that with an increasing filter radius a more manufacturable topology is achieved. The more concrete the structure gets the lower the stiffness will be. Higher compliance sensitivities w.r.t. the load are to be expected with a higher filter radius. This means that even though the structure has an easier topology we lose structural properties. Therefore a compromise has to be made when choosing the filter radius.

This method is not only applicable to compliance-minimizing topology optimization resulting in stiff structures, but to the
290 design of compliant mechanisms, which are designed to have large deformations in certain degrees of freedom (e.g. Sigmund (1997); Reinisch et al. (2021); Achleitner and Wehrle (2022)). With such designs, the design of the force and therefore the compliance sensitivity w.r.t. force is of great concern.

Summarizing, this work provides a method requiring no further computational effort to assess the compliance sensitivity of topology optimized designs. Although, weaknesses exist in regards to compliance sensitivity w.r.t. loads that were not
295 considered, its is meaningful to assess the robustness, to compare sensitivities of different loads and the sensitivity of a structure to loading in general.

Author contributions. For research articles with several authors, a short paragraph specifying their individual contributions must be provided. The following statements should be used “Conceptualization, EW, PH; methodology, EW, PH; software, PH, EW; validation, PH, EW; formal analysis, EW, PH; investigation, PH, EW; writing—original draft preparation, EW, PH; writing—review and editing, EW, PH; visualization,
300 EW, PH; supervision, EW; project administration, EW; funding acquisition, EW. All authors have read and agreed to the published version of the manuscript.

Competing interests. The authors declare no conflict of interest.

Acknowledgements. This work is supported by the project RTD 2020 – TN201Q LighOpt *Lightweight engineering of multibody systems with design optimization* funded by the Free University of Bozen-Bolzano. The authors would like to thank Joseph Reinisch at Leitner AG
305 (Sterzing, South Tyrol, Italy) for providing the load case for the cableway pylon problem.

References

- Aage, N., Andreassen, E., and Lazarov, B. S.: Topology optimization using PETSc: An easy-to-use, fully parallel, open source topology optimization framework, *Structural and Multidisciplinary Optimization*, 51, 565–572, <https://doi.org/10.1007/s00158-014-1157-0>, 2015.
- Achleitner, J. and Wehrle, E.: On material selection for topology optimized compliant mechanisms, *Mechanism and Machine Theory*, 167, 104 474, <https://doi.org/10.1016/j.mechmachtheory.2021.104474>, 2022.
- Andreassen, E., Clausen, A., Schevenels, M., Lazarov, B. S., and Sigmund, O.: Efficient topology optimization in MATLAB using 88 lines of code, *Structural and Multidisciplinary Optimization*, 43, 1–16, <https://doi.org/10.1007/s00158-010-0594-7>, 2011.
- Arvidsson, M. and Gremyr, I.: Principles of robust design methodology, *Quality and Reliability Engineering International*, 24, 23–35, <https://doi.org/10.1002/qre.864>, 2008.
- 315 Bendsoe, M. P.: *Optimization of Structural Topology, Shape, and Material*, Springer, Berlin, Heidelberg, 1995.
- Bendsøe, M. and Sigmund, O.: *Topology optimization: Theory, methods and applications*, Springer, 2003.
- Bendsøe, M. P.: Optimal shape design as a material distribution problem, *Structural Optimization*, 1, 193–202, <https://doi.org/10.1007/bf01650949>, 1989.
- Box, G. and Fung, C. A.: Quality quadaries: Is your robust design procedure robust?, *Quality Engineering*, 6, 503–514, <https://doi.org/10.1080/08982119408918744>, 1994.
- 320 Bulman, S., Sienz, J., and Hinton, E.: Comparisons between algorithms for structural topology optimization using a series of benchmark studies, *Computers & Structures*, 79, 1203–1218, [https://doi.org/10.1016/s0045-7949\(01\)00012-8](https://doi.org/10.1016/s0045-7949(01)00012-8), 2001.
- da Silva Smith, O.: Generation of ground structures for 2D and 3D design domains, *Engineering Computations*, 15, 462–500, <https://doi.org/10.1108/02644409810219820>, 1998.
- 325 de Souza, R. R., Miguel, L. F. F., Lopez, R. H., Miguel, L. F. F., and Torii, A. J.: A procedure for the size, shape and topology optimization of transmission line tower structures, *Engineering Structures*, 111, 162–184, <https://doi.org/10.1016/j.engstruct.2015.12.005>, 2016.
- Dorn, W. S., Gomory, R. E., and Greenberg, H. J.: Automatic design of optimal structures, *Journal de Mécanique*, 3, 25–52, 1964.
- Dunning, P. D., Kim, H. A., and Mullineux, G.: Introducing Loading Uncertainty in Topology Optimization, *AIAA Journal*, 49, 760–768, <https://doi.org/10.2514/1.j050670>, 2011.
- 330 Gonzalez, E.: Three-dimensional topology optimization of arbitrary geometries using open-source general-purpose finite element software, Master’s thesis, Lehrstuhl für Statik, Technische Universität München, 2015.
- Hofer, P.: Large-scale three-dimensional topology optimization for lightweight structures with Kratos Multiphysics, Semesterarbeit, Free University of Bozen-Bolzano and Technical University of Munich, advisor: E. J. Wehrle, F. Sturm, 2021.
- Kemmler, S., Eifler, T., Bertsche, B., and Howard, T. J.: Robust reliability or reliable robustness? Integrated consideration of robustness- and reliability-aspects, in: 27. VDI-Fachtagung Technische Zuverlässigkeit, Universität Stuttgart, <https://doi.org/10.18419/OPUS-4604>, 2015.
- 335 Langelaar, M.: An additive manufacturing filter for topology optimization of print-ready designs, *Structural and Multidisciplinary Optimization*, 55, 871–883, <https://doi.org/10.1007/s00158-016-1522-2>, 2017.
- Lazarov, B. S., Schevenels, M., and Sigmund, O.: Topology optimization with geometric uncertainties by perturbation techniques, *International Journal for Numerical Methods in Engineering*, 90, 1321–1336, <https://doi.org/10.1002/nme.3361>, 2012.
- 340 Malfavon, O.: Development of an open-source tool for 3D topology optimization and its extension towards integrated design and analysis, Master’s thesis, Lehrstuhl für Statik, Technische Universität München, 2016.

- Reinisch, J., Wehrle, E., and Achleitner, J.: Multiresolution topology optimization of large-deformation path-generation compliant mechanisms with stress constraints, *Applied Sciences*, 11, 2479, <https://doi.org/10.3390/app11062479>, 2021.
- Sigmund, O.: On the design of compliant mechanisms using topology optimization, *Mechanics of Structures and Machines*, 25, 493–524, <https://doi.org/10.1080/08905459708945415>, 1997.
- Sigmund, O.: A 99 line topology optimization code written in Matlab, *Structural and Multidisciplinary Optimization*, 21, 120–127, <https://doi.org/10.1007/s001580050176>, 2001.
- Sigmund, O.: Morphology-based black and white filters for topology optimization, *Structural and Multidisciplinary Optimization*, 33, 401–424, <https://doi.org/10.1007/s00158-006-0087-x>, 2007.
- Sigmund, O. and Petersson, J.: Numerical instabilities in topology optimization: A survey on procedures dealing with checkerboards, mesh-dependencies and local minima, *Structural optimization*, 16, 68–75, <https://doi.org/10.1007/bf01214002>, 1998.
- Stromberg, L. L., Beghini, A., Baker, W. F., and Paulino, G. H.: Application of layout and topology optimization using pattern gradation for the conceptual design of buildings, *Structural and Multidisciplinary Optimization*, 43, 165–180, <https://doi.org/10.1007/s00158-010-0563-1>, 2010.
- Taguchi, G.: Introduction to quality engineering: Designing quality into products and processes, Asian Productivity Organization, Tokyo, 1986.
- Tsavaridis, K. D., Nicolaou, A., Mistry, A. D., and Efthymiou, E.: Topology optimisation of lattice telecommunication tower and performance-based design considering wind and ice loads, *Structures*, 27, 2379–2399, <https://doi.org/10.1016/j.istruc.2020.08.010>, 2020.
- Wang, F., Lazarov, B. S., and Sigmund, O.: On projection methods, convergence and robust formulations in topology optimization, *Structural and Multidisciplinary Optimization*, 43, 767–784, <https://doi.org/10.1007/s00158-010-0602-y>, 2010.
- Wehrle, E. and Gufler, V.: Lightweight engineering design of nonlinear dynamic systems with gradient-based structural design optimization, in: *Proceedings of the Munich Symposium on Lightweight Design 2020*, pp. 44–57, Springer Berlin Heidelberg, https://doi.org/10.1007/978-3-662-63143-0_5, 2021.
- Wu, J., Gao, J., Luo, Z., and Brown, T.: Robust topology optimization for structures under interval uncertainty, *Advances in Engineering Software*, 99, 36–48, <https://doi.org/10.1016/j.advengsoft.2016.05.002>, 2016.