Densification and characterization of pressureless sintered ZrB2-20 vol% MoSi2 ultra high temperature ceramic composites

Mainak Saha^{1,2}

Department of Metallurgical and Materials Engineering, National Institute of Technology, Durgapur-713209, India

Department of Metallurgical and Materials Engineering, Indian Institute of Technology, Madras, Chennai-600036, India

Abstract

In recent times, ultra-high temperature ceramic matrix composites (UHTCMCs) comprising of ultra-high temperature ceramics (UHTCs) such as ZrB₂, HfB₂ etc. reinforced with additives such as SiC, MoSi₂ etc. have been reported to offer tremendous potentials in applications such as Hypersonic Re-entry vehicles, solar thermal absorbers, nuclear fuel claddings etc. Porous ceramics are advantageous in the aforementioned applications areas owing to their high melting points combined with high corrosion and wear resistance. Although ZrB₂-SiC UHTCMCs (synthesized using pressureless sintering technique) have been widely investigated for their densification and mechanical properties at both room and elevated temperatures (till 3000°C), there is a very limited information on the densification behaviour and mechanical properties of ZrB₂-MoSi₂ UHTCMCs prepared using the aforementioned sintering technique. To this end, the present study is aimed at investigating the microstructure and correlating the same with the densification behaviour and mechanical properties of porous sintered ZrB₂-20 vol.% MoSi₂ (ZM20) UHTCMC. To this end, the composite was ball milled for 2h followed by compaction at different pressures. The compacted samples were sintered at 1700°C. X-Ray Diffraction (XRD) analysis was performed for the purpose of understanding phase evolution. Subsequent, microstructural investigation was performed under different magnifications in Scanning Electron Microscope (SEM). Moreover, density measurement; hardness and indentation fracture toughness calculations were performed to investigate the room temperature mechanical properties.

Keywords: Ultra-high temperature ceramic matrix composites (UHTCMCs), pressureless sintering, X-ray Diffraction, Scanning Electron Microscopy, Vickers microhardness.

Ultra-high temperature ceramics (UHTCs), such as zirconium diboride (ZrB₂) and hafnium diboride (HfB₂) are a novel class of materials characterized by melting points exceeding 3000°C. ZrB₂-based structural ceramics possess a combination of properties which make them attractive for use in extreme environments [1]. The low electrical resistivity of ZrB₂ (6–23 $\mu\Omega \cdot cm$) contributes to its high thermal conductivity (up to ~130 W/m·K). and low density (6.14 g/cm³), compared to other UHTCs, renders ZrB₂ ceramics as ideal candidates for aerospace components such as engine components and leading edges for hypersonic re-entry vehicles [2]. Other applications include concentrated solar thermal absorbers, nuclear fuel cladding, and neutron absorbers [3]–[6].

Molybdenum disilicide (MoSi₂) has been widely investigated as an additive to ZrB_2 , due to its ability to facilitate densification of ZrB_2 at temperatures as low as 1750 °C with or without application of pressure and to improve oxidation resistance of ZrB_2 up to ~1600 °C by forming a glassy borosilicate (B₂O₃) surface layer [5], [7–9]. Moreover, MoSi₂ has also been reported to enhance the ductility of ZrB_2 at elevated temperatures owing to its brittle-to-ductile transition (BDT) upon heating between 900 and 1300 °C. Common sintering routes of ultra-high temperature ceramic matrix composites (UHTCMCs) include hot pressing (HP), pressure-less sintering (PS), spark plasma sintering (SPS) and reactive hot pressing (RHP) [10]–[12]. Even though PS is an attractive route for the fabrication of parts with a high level of design complexity, hot pressing (HP) still remains as the most preferred route due to the high relative density of the final composite [3], [14]-[16].

Porous composites are manufactured because they enable the ceramic product for use in a number of applications such as filtration of molten steel, hot corrosive gases etc. The decomposition of $MoSi_2$ to Mo_5Si_3 occurs when $MoSi_2$ is heated to temperatures ranging from 1700° to 2000°C under a vacuum level of 10^{-5} mm Hg, leading to structural distortion and subsequent porosity in the microstructure [2],[3]. Porous ceramics are highly advantageous for high-temperature applications due to their high melting point and high corrosion and wear resistance [6]. However, at present, there is limited understanding on the mechanical properties of ZM composites at room temperature. To this end, the present work is aimed at investigating the densification, microstructure, physical and mechanical properties of pressureless sintered porous ZrB₂-20vol.% MoSi₂ UHTCMCs [6].

References

- D. Sciti, M. Brach, and A. Bellosi, "Oxidation behavior of a pressureless sintered ZrB2-MoSi2 ceramic composite," *Journal of Materials Research*, vol. 20, no. 4, pp. 922–930, 2005, doi: 10.1557/JMR.2005.0111.
- [2] D. Sciti, L. Silvestroni, and A. Bellosi, "Fabrication and properties of HfB2-MoSi2 composites produced by hot pressing and spark plasma sintering," *Journal of Materials Research*, vol. 21, no. 6, pp. 1460–1466, Jun. 2006, doi: 10.1557/jmr.2006.0180.
- [3] D. Sciti, L. Silvestroni, and A. Bellosi, "Fabrication and properties of HfB2-MoSi2 composites produced by hot pressing and spark plasma sintering," *Journal of Materials Research*, vol. 21, no. 6, pp. 1460–1466, Jun. 2006, doi: 10.1557/jmr.2006.0180.
- [4] D. Sciti, M. Brach, and A. Bellosi, "Long-term oxidation behavior and mechanical strength degradation of a pressurelessly sintered ZrB2-MoSi2 ceramic," *Scripta Materialia*, vol. 53, no. 11, pp. 1297–1302, Dec. 2005, doi: 10.1016/j.scriptamat.2005.07.026.
- [5] D. Sciti, S. Guicciardi, A. Bellosi, and G. Pezzotti, "Properties of a Pressureless-Sintered ZrB2-MoSi2 Ceramic Composite," *Journal of the American Ceramic Society*, vol. 0, no. 0, pp. 060427083300081-???, Apr. 2006, doi: 10.1111/j.1551-2916.2006.00999.x.
- [6] L. Silvestroni, K. Stricker, D. Sciti, and H. J. Kleebe, "Understanding the oxidation behavior of a ZrB2–MoSi2 composite at ultra-high temperatures," *Acta Materialia*, 2018, doi: 10.1016/j.actamat.2018.03.042.
- [7] L. Silvestroni, K. Stricker, D. Sciti, and H. J. Kleebe, "Understanding the oxidation behavior of a ZrB2–MoSi2 composite at ultra-high temperatures," *Acta Materialia*, vol. 151, pp. 216–228, 2018, doi: 10.1016/j.actamat.2018.03.042.
- [8] L. Silvestroni, K. Stricker, D. Sciti, and H. J. Kleebe, "Understanding the oxidation behavior of a ZrB2–MoSi2 composite at ultra-high temperatures," *Acta Materialia*, vol. 151, pp. 216–228, 2018, doi: 10.1016/j.actamat.2018.03.042.
- [9] D. Sciti, F. Monteverde, S. Guicciardi, G. Pezzotti, and A. Bellosi, "Microstructure and mechanical properties of ZrB2-MoSi2 ceramic composites produced by different sintering techniques," *Materials Science and Engineering A*, vol. 434, no. 1–2, pp. 303–309, Oct. 2006, doi: 10.1016/j.msea.2006.06.112.
- [10] S. Mungiguerra, A. Cecere, R. Savino, F. Saraga, F. Monteverde, and D. Sciti, "Improved aerothermal resistance capabilities of ZrB2-based ceramics in hypersonic environment for increasing SiC content," *Corrosion Science*, vol. 178, Jan. 2021, doi: 10.1016/j.corsci.2020.109067.
- [11] D. oxidation behavior and mechanical strength degradation of a pressurelessly sintered Z.-M. ceramic Sciti, M. Brach, and A. Bellosi, "Long-term oxidation behavior and mechanical strength degradation of a pressurelessly sintered ZrB2-MoSi2 ceramic," *Scripta Materialia*, vol. 53, no. 11, pp. 1297–1302, 2005, doi: 10.1016/j.scriptamat.2005.07.026.
- [12] R. J. Grohsmeyer et al., "ZrB 2 -MoSi 2 ceramics: A comprehensive overview of microstructure and properties relationships. Part II: Mechanical properties," *Journal of the European Ceramic Society*, vol. 39, no. 6, pp. 1948–1954, 2019, doi: 10.1016/j.jeurceramsoc.2019.01.021.
- [13] L. Silvestroni, S. Failla, I. Neshpor, and O. Grigoriev, "Method to improve the oxidation resistance of ZrB2-based ceramics for reusable space systems," *Journal of the European Ceramic Society*, 2018, doi: 10.1016/j.jeurceramsoc.2018.01.025.
- [14] M. Saha, New frontiers in characterising ZrB2- MoSi2 ultra-high temperature ceramics, arXiv:2202.11162.
- [15] M. Saha, Cyclic oxidation behaviour of ZrB2-20 vol.% MoSi2 based ultra-high temperature ceramic matrix composite between 1100 C and 1300 C, engrxiv.org.
- [16] Saha M, Pramanik S, Banik R, Maurya P, Singh S, Raj SV, Madhur DP, Paul TR, Mitra R, Mondal MK, Mallik M. An Insight Into Cyclic Oxidation behavior of ZrB2-20 Vol.% MoSi2 Based Ultrahigh Temperature Ceramic Matrix Composite. InModern Manufacturing Systems (pp. 149-163). Apple AcademicPress.

Electronic copy available at: https://ssrn.com/abstract=4242015