

Field-Based Bonding Solutions for Insulated Stainless-Steel Piping in Hazardous Oil & Gas Installations

Prepared by:
Denis Agapitov
Electrical Engineer



Abstract

This article presents a field-validated method for achieving reliable electrical continuity across insulated stainless-steel flanged joints in hazardous-area chemical injection systems, mitigating the risk of electrostatic discharge ignition. The proposed solution employs 35 mm² PVC-insulated copper bonding jumpers and was implemented in accordance with IEC 60079-14, IEC 60364-5-54, IEEE Std 142, and NFPA 77.

Field testing confirmed bonding resistance values consistently below 0.05 Ω, ensuring compliance with international safety standards. The system was specifically engineered to address practical challenges, including mechanical congestion, material compatibility with stainless steel, and coexistence with electric heat-tracing systems.

This work provides a structured engineering framework for enhancing equipotential bonding in hazardous environments - minimizing electrostatic ignition risks, mitigating stray voltage hazards, and improving grounding integrity across isolated pipeline sections. The approach has been proven in remote oil and gas field conditions and demonstrates strong reliability, maintainability, and economic justification aligned with ALARP principles.

Keywords: Equipotential bonding, bonding jumpers, stainless steel pipelines, insulated flanged joints, hazardous areas, electrostatic ignition prevention, electric heat tracing, IEC 60079-14, IEC 60364-5-54, NFPA 77, NFPA 70 (NEC), oil and gas, field-fabricated grounding, industrial earthing systems, static discharge protection.

1. INTRODUCTION

Ensuring effective bonding and earthing of industrial piping systems is a critical requirement for hazardous-area installations, particularly within the oil and gas sector. Stainless-steel pipelines with flanged joints frequently incorporate insulating gaskets, which disrupt electrical continuity and introduce the risk of potential differences, sparking, and electrostatic discharge.

This paper presents a practical bonding solution implemented under real-world field conditions across major oil and gas operator in a remote region. The method involves the use of 35 mm² insulated copper bonding jumpers installed across insulated flanged joints and is fully aligned with international standards - particularly IEC 60079-14 (Clauses 6.3 and 6.4) - which emphasize equipotential bonding to prevent ignition sources in explosive atmospheres.

The objective of this work is to provide engineering professionals with field-validated insights into effective bonding practices under constraints such as limited physical access, proximity to heat-tracing systems, structural congestion, chemical exposure, and sub-zero environments.

Note on Standards Editions and Consistency: Applicability to Carbon Steel Systems

While this study focuses on stainless steel pipelines with insulating gaskets, the same bonding principles can apply to carbon steel systems in certain scenarios. Although bolted flanges in carbon steel lines generally maintain continuity, this can be disrupted by non-conductive gaskets, insulating sleeves, corrosion-resistant coatings, or cathodic protection systems. In such cases, bonding jumpers installed per IEC 60364-5-54 are recommended to ensure effective equipotential bonding, especially in hazardous areas.

2. STANDARDS AND REGULATORY FRAMEWORK

2.1 International Standards Overview

The bonding and earthing practices described in this article are based on internationally recognized standards that govern electrical safety, equipotential bonding, and ignition hazard control in hazardous areas. The following standards were applied during the project, with clarification on editions used and alignment with current practices:

- **IEC 60079-14:2013**, Clauses 6.3 and 6.4 - Electrical installations in explosive gas atmospheres. These clauses define requirements for potential equalization and prevention of ignition sources due to discontinuities, such as insulated flange joints. The implemented bonding jumper configuration ensures compliance with these requirements by maintaining electrical continuity across insulated joints.
- **IEC 60364-5-54:2011**, with reference to Clause 544.2 (supplementary equipotential bonding) and Clause 543.1.2 (adiabatic sizing of bonding conductors). The calculations in Section 3.2 were based on these requirements. While the 2021 edition of this standard introduced clause restructuring, the fundamental technical principles remain unchanged.
- **IEEE Std 142-2007** - Provides best practices for grounding and bonding in industrial and commercial power systems. Clause 3.2.6.2 emphasizes the importance of minimizing potential differences to avoid sparking across discontinuities, supporting the use of dedicated bonding jumpers. Although a 2022 revision of the standard is available, the 2007 edition was applicable at the time of design and was therefore used in the analysis. The updated version was reviewed and found to be technically consistent for the purpose described.
- **NFPA 77:2014** - Recommended Practice on Static Electricity. This standard outlines bonding and grounding methods for preventing electrostatic discharge in hazardous areas, particularly relevant to the handling of methanol and other flammable fluids in chemical injection systems. The 2019 edition was consulted during article preparation to confirm alignment with current guidance.
- **NFPA 70:2014** (National Electrical Code, **NEC**) - Article 250 outlines the principles for establishing low-impedance fault current paths and grounding continuity, which align with the design choices made for the bonding system. NFPA 70:2014 was used during project execution, aligning with the project timeline. The 2017 edition was reviewed for article preparation and found to be technically consistent with the applied principles.
- **API RP 2003:1998** - Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents. This document supports the rationale for bonding insulated metal components in hydrocarbon processing facilities. A 2015 revision exists, but the 1998 edition was applied during project execution. The 2015 revision reaffirms the same bonding principles, with no significant deviations affecting the approach described in this article.
- **ATEX Directive (2014/34/EU)**: This European regulation applies to equipment and protective systems used in potentially explosive atmospheres. The bonding jumper system aligns with ATEX principles by minimizing the risk of electrostatic charge accumulation across insulated flanges. While bonding jumpers are not Ex-certified components themselves, they complement certified systems such as heat-tracing cables and junction boxes by ensuring continuous potential equalization throughout the hazardous zone.

Edition Note: The engineering solutions presented in this article were developed and validated during the Front-End Engineering Design (FEED) phase of the project in the mid-2010s. The standards applied reflect the editions in force at that time, specifically: IEC 60079-14:2013, IEC 60364-5-54:2011, IEEE 142:2007, NFPA 70:2014, NFPA 77:2014, and API RP 2003:1998.

During article preparation, more recent editions of these standards (e.g., IEC 60079-14:2019, IEEE 142:2022, NFPA 77:2019) were reviewed and found to be technically consistent with the approaches and principles described herein. This ensures that the solution remains valid and forward-compatible with current international engineering practices.

2.2 Regional Code Applications

The bonding methodology described aligns with major regional electrical regulations and adapts to the specific requirements of different jurisdictions:

- **North America:** NEC Article 250 (Grounding and Bonding); CEC Section 10 (Canada)
- **Europe:** EN 61936-1 implementation with national amendments for hazardous locations
- **Middle East:** IEC-based grounding design with additional safety provisions and regional engineering specifications
- **Asia-Pacific:** AS/NZS 3000 integration, with consideration for local hazardous area classification and inspection requirements

2.3 Project-Specific Engineering Requirements

The bonding implementation described in this paper was executed in accordance with operator-specific engineering specifications developed during the Front-End Engineering Design (FEED) phase. These specifications mandated:

- Use of tinned copper bonding conductors (minimum 35 mm²);
- Corrosion-resistant mechanical terminations;
- Verified continuity across insulated flange joints ($\leq 0.05 \Omega$);
- Integration with electric heat-tracing system and chemical injection systems.

These requirements were formalized to ensure compliance with international standards, facilitate inspection, and minimize operational and legal risks.

A comprehensive risk assessment program, including formal HAZID and HAZOP studies, was conducted during the FEED stage. These workshops identified several critical scenarios, including the risk of dangerous voltage potential on stainless-steel piping. In the event of electric heat-tracing cable insulation damage or other associated component failures, dangerous voltages could appear on metallic piping sections if electrical continuity was not assured. Due to the presence of insulating gaskets and the limited conductivity of stainless-steel bolts, flanged joints could not be considered reliable conductive paths. Without dedicated bonding, continuity across such joints would be unpredictable or entirely absent.

The facility was characterized by challenging environmental and operational stressors. During winter months, outdoor air temperatures regularly dropped to -40°C, accompanied by frequent snowstorms, ice accumulation, and limited accessibility for equipment and personnel. Internally, although HVAC systems were in place, process-related factors contributed to fluctuating temperature and humidity levels, which in turn affected material behavior and electrical contact stability.

These environmental extremes, combined with mechanical vibration and the presence of aggressive chemical vapors, increased the probability of degradation at bolted flange connections - especially when relying solely on stainless-steel hardware for electrical continuity.

As such, the implementation of dedicated bonding jumpers was further justified by the need to ensure long-term reliability under non-ideal operating conditions.

Based on these findings, the decision to install 35 mm² tinned copper bonding jumpers was made in alignment with the ALARP principle (As Low As Reasonably Practicable). The cost of implementation - less than \$130 per junction - was negligible compared to potential consequences such as electric shock to personnel, equipment failure, fire, environmental damage, or legal liability.

Moreover, the use of dedicated bonding conductors enabled predictable continuity paths, ensured compliance with IEC 60079-14 and IEC 60364-5-54, and allowed for effective continuity testing and inspection. All project documentation was approved through formal design reviews, and the bonding methodology became part of the validated engineering solution for the chemical injection facilities.

Ultimately, this decision reflects a mature, risk-informed engineering approach that supports safety, maintainability, and regulatory transparency across the full lifecycle of the facility.

2.3.2 Engineering Context and Risk Philosophy

The bonding configuration adopted in this project was not a routine or secondary detail - it reflected a deliberately engineered response to multiple operational hazards. The approach was guided by a multi-disciplinary risk philosophy focused on long-term reliability, compliance, and personnel safety.

Insulating gaskets were specified between stainless-steel flanges to ensure chemical resistance against aggressive reagents commonly encountered in chemical injection systems. While their primary function is corrosion mitigation, these gaskets are inherently dielectric and interrupt electrical continuity - an undesirable but inevitable side effect that compromises equipotential bonding across pipeline sections.

Although stainless-steel studs and bolts provide mechanical strength, they cannot be relied upon for consistent electrical contact. Factors such as vibration, thermal expansion, micro-movement, and the formation of oxide layers can significantly reduce contact integrity over time, even in corrosion-resistant alloys.

To address these vulnerabilities, dedicated copper bonding jumpers (35 mm² tinned copper) were implemented to ensure robust, low-resistance electrical continuity. Their inclusion supports:

- Uninterrupted equipotential bonding across non-conductive gaskets.
- Electrical safety for heat-tracing systems and junction boxes exposed to conductive infrastructure.
- Static risk mitigation in accordance with NFPA 77:2019, which recommends bonding to prevent discharge hazards from fluid movement, friction, and environmental conditions in hazardous locations.
- In line with the grounding and bonding philosophy established by NFPA 70:2017 (National Electrical Code), which was the current edition at the time of design, the implemented bonding system ensured continuous grounding paths even in the presence of insulating gaskets. While bolted joints offer mechanical integrity, they are not considered reliable for ensuring fault current return paths under operational or corrosive stresses. Supplementary bonding jumpers were installed to fulfill NEC Article 250 requirements for low-impedance fault current paths and equipotential equalization.
- Adherence to API RP 2003:1998, which highlights bonding as a critical strategy to dissipate accumulated electrostatic charges during flammable liquid or vapor handling.
- Mitigation of ignition risks in explosive or chemically reactive atmospheres, where uncontrolled sparking or insulation breakdown may lead to catastrophic outcomes.
- Conformity with IEC 60079-14, IEC 60364-5-54, and IEEE Std 142, alongside operator-specific design specifications and risk mitigation philosophies.
- Redundancy in bonding paths, in line with industry best practices for critical installations, ensuring fail-safe operation under adverse conditions.

This decision was driven by a rigorous project-specific risk assessment conducted during the Front-End Engineering Design (FEED) phase. Operational, reputational, insurance, and life-safety risks were evaluated.

The incremental cost of implementing bonding jumpers was considered a prudent investment when weighed against the potentially severe consequences of bonding failure.

Such strategies are emblematic of global operators in the oil and gas sector, where safety-led design and proactive risk governance are central to engineering practice. The implemented solution represents a technically justified redundancy that reinforces system integrity in complex, high-risk environments.

3. TECHNICAL SOLUTION AND DESIGN RATIONALE

3.1 Electrical Continuity Challenge

In chemical injection facilities within hydrocarbon production environments, stainless steel pipelines are commonly fitted with chemically-resistant gaskets that interrupt metallic continuity. While SS316 stainless steel flanges, studs, and nuts provide excellent mechanical strength, several factors compromise their ability to ensure long-term electrical continuity:

Mechanical Degradation Factors:

- Micro-loosening: Thermal cycling and mechanical vibrations gradually loosen threaded connections.
- Contact resistance increase: Oxidation and micromovements degrade metal-to-metal interfaces over time.

Maintenance disruption:

During gasket replacement or system maintenance, studs and nuts may be loosened or removed. In such cases, pre-installed bonding jumpers preserve electrical continuity, maintaining safety without requiring rework.

Material Conductivity Limitations:

Even when properly tightened, stainless steel connections exhibit poor electrical conductivity compared to copper, which is specifically selected for bonding applications.

3.1.2 Material Conductivity Analysis

Table 1: Relative Electrical Conductivity of Industrial Materials

Material	Relative Conductivity (vs. Copper)	Typical Application
Copper (reference)	100%	Standard electrical conductors
Aluminum	~61%	Overhead power lines, lightweight cables
Tinned Copper	~85–98%	Corrosion-resistant bonding jumpers
Brass	~28%	Grounding terminals, fittings
Carbon Steel	~3%–15%	Structural piping, mounting frames
Stainless Steel 316	~2–4%	Bonding plates, corrosive environments

Source: CRC Handbook of Chemistry and Physics (102nd Ed.), NIST Material Properties Database, and IEC/TR 60079-32-1:2013 Annex E.

Conductivity values are expressed as a percentage relative to annealed copper (IACS = 100%). Actual values may vary slightly based on alloy composition and surface treatment. Tinned copper, for example, may have slightly reduced conductivity depending on the thickness of the tin layer.


Engineering Rationale:

Copper provides 25-40 times higher electrical conductivity than stainless steel, enabling low-impedance bonding paths, reduced voltage drop, and effective fault current dissipation. A 35 mm² conductor cross-section ensures sufficient current-carrying capacity while retaining mechanical flexibility to accommodate thermal cycling and pipe expansion.

3.1.3 Bonding Schematic Reference

To visually support the technical design rationale, a standardized schematic is provided below, illustrating typical bonding arrangements for metallic piping with tee and flange connections in accordance with IEC 60364-5-54:2021, Clause 544.

Figure 1. Bonding schematic for stainless steel pipe flanges using 35 mm² copper jumpers, per IEC 60364-5-54:2021, Clause 544.2.



Description: Bonding conductors (35 mm² tinned copper) are installed across adjacent pipe flanges to maintain electrical continuity with the main earthing system. These jumpers are critical where insulating gaskets or non-metallic elements break the conductive path. This configuration supports equipotential bonding principles, as mandated for low-voltage installations and hazardous environments.

3.1.4 Flange Jumper Bonding Detail


The flange jumper bonding detail with non-conducting gasket and grounding plate aligns with IEC 60079-14, particularly Clauses 6.3 and 6.4, which highlight the importance of potential equalization and the prevention of dangerous sparking in hazardous areas. These principles form the basis for maintaining electrical continuity across conductive components such as flanged pipe sections when interrupted by non-conductive gaskets.

Relation to IEEE 142 (Green Book):

In addition to IEC standards, this bonding method reflects guidance outlined in IEEE Std 142-2007, which emphasizes bonding as a preventive measure against voltage differences between conductive components.

Clause 3.2.6.2 specifically notes that "Bonding (connecting the two objects together) minimizes voltage differences between conductive objects, thus preventing sparking between two bodies." This principle is directly applicable to flanged pipe connections where insulating gaskets are used. The bonding jumper acts as a controlled bypass, reducing the risk of electrostatic discharge and contributing to the overall electrical safety of the system.

Figure 2. Bonding jumper layout across non-conductive gaskets with stainless-steel washers, per IEC 60079-14.



Description: Where non-conductive gaskets are used to prevent galvanic corrosion or to electrically isolate flanged connections in hazardous areas, dedicated bonding jumpers are commonly applied to maintain metallic continuity. This practice aligns with the general safety requirements of IEC 60079-14, particularly Clauses 6.3 and 6.4, which emphasize the prevention of dangerous sparking and the need for potential equalization across conductive components.

To ensure long-term contact reliability and mechanical stability - especially in corrosive or vibration-prone environments - serrated washers and stainless-steel fasteners are typically used at each termination point.

3.1.5 Note on Gasket Function and Bonding Necessity

In many industrial chemical applications, insulating gasket sets are not primarily selected for electrical isolation, but rather for their chemical resistance. This was precisely the case in the bonding solution described here: the non-conductive gaskets were chosen to withstand aggressive chemical reagents in stainless-steel flanged joints. Their dielectric property was a secondary and unavoidable consequence rather than an intended design goal. However, this unintended electrical insulation interrupts the continuity of metallic piping systems, which can become critical in facilities with heat-tracing systems, junction boxes, and exposed metallic structures requiring uninterrupted earthing. In the event of insulation failure, static discharge, or potential differences, the absence of continuous bonding could pose serious safety risks.

To restore electrical continuity and maintain a compliant equipotential bonding network, 35 mm² copper jumpers were installed across each flange. This approach ensures that any fault current, leakage, or induced voltage has a safe path to ground, in accordance with IEC 60079-14 and IEC 60364-5-54.

In summary, insulating gaskets were installed for chemical reasons, while electrical bonding jumpers were added for safety and regulatory compliance. This dual-requirement approach is common in hazardous area designs across the oil, gas, and chemical processing sectors, especially where safety is prioritized alongside material compatibility.

3.2 Design Calculations

3.2.1 Conductor Sizing Based on Thermal Constraints

To verify the suitability of the selected bonding jumper (35 mm² tinned copper), the conductor sizing was evaluated using the adiabatic equation from IEC 60364-5-54:2011, Clause 543.1.2, which governs thermal withstand during short-circuit events:

$$S = \frac{I \cdot \sqrt{t}}{k}$$

Where:

- S - minimum conductor cross-sectional area (mm²),
- I - fault current (A),
- t - disconnection time (s),
- k – material constant for copper with PVC insulation = 143 A×√s/mm²

For a copper conductor with PVC insulation and a permissible temperature rise from 70 °C to 160 °C, the IEC standard specifies:

- k = 143 A×√s/mm²

Standards Clarification

While IEC 60079-14 does not explicitly define minimum cross-sectional areas for bonding conductors, it refers to general bonding principles under Clauses 6.3 and 6.4, emphasizing low-impedance paths and mechanical integrity. The sizing used here follows IEC 60364-5-54 (Clause 543.1.2), based on thermal performance.

For consistency, this installation used the 2013 edition of IEC 60079-14, which was in force during the project timeline.

Case A – Full Fault Current (Protective Conductor)

This represents a theoretical short-circuit current from the power distribution system.

Assumed fault current: I = 8000A

Disconnection time: t = 1s

Result: $S = \frac{8000 \cdot \sqrt{1}}{143} = \frac{8000}{143} \approx 55.94 \text{ mm}^2$

Since the calculated requirement exceeds 35 mm², the bonding jumper is not sized for carrying full fault current — nor is it required to. The bonding system is designed for equipotential equalization, not as a primary fault current path.

Case B – Transient or Stray Current Scenario

This scenario reflects potential discharge from a heat-tracing fault or electrostatic buildup.

Assumed fault current: $I = 1000\text{A}$

Disconnection time: $t = 0.2\text{s}$

$$\text{Result: } S = \frac{1000 \cdot \sqrt{0.2}}{143} = \frac{1000 \cdot 0.447}{143} \approx 3.13 \sim \text{mm}^2$$

Here, a 35 mm² conductor provides a safety factor >10× over the required minimum.

The 8,000 A fault current value is based on the maximum prospective short-circuit current from the facility's 400 V low-voltage distribution system, as calculated during the FEED phase. The 1,000 A current reflects potential discharge from localized faults in electric heat-tracing cables or static accumulation events. The 25 A current represents a conservative estimate of minor capacitive discharge in junction boxes or fault leakage, typical in Zone 1 installations. Disconnection times of 1 s (for short-circuit protection) and 0.2 s (for localized discharges) are based on time-current curves of circuit breakers per IEC 60947-2 and manufacturer trip data.

Conclusion

The 35 mm² jumper was selected to exceed minimum sizing requirements for transient currents while also providing mechanical robustness and corrosion margin. This conservative sizing aligns with ALARP principles and IEC 60079-14 Annex E recommendations for reliable equipotential bonding in Zone 1 areas.

3.2.2 Resistance Analysis

To ensure compliance with bonding continuity requirements, the total resistance of the bonding jumper is calculated. The total resistance consists of the conductor's internal resistance and the contact resistance at both termination points: $R_{\text{total}} = R_{\text{conductor}} + 2 \times R_{\text{contact}}$

Where:

- $R_{\text{conductor}} = \rho \cdot \frac{L}{A}$
- $\rho = 1.72 \times 10^{-8} \Omega \cdot \text{m}$ (resistivity of copper at 20 °C),
- $L = 0.25 \text{ m}$ (bonding jumper length between flanges),
- $A = 35 \times 10^{-6} \text{ m}^2$ (cross-sectional area)
- $R_{\text{contact}} = 0.001 \Omega$ (per termination; based on IEC 60079-14 Annex E and verified through use of serrated stainless-steel washers during field installation)

$$\text{Calculation: } R_{\text{conductor}} = \frac{1.72 \times 10^{-8} \cdot 0.25}{35 \times 10^{-6}} \approx 1.23 \times 10^{-4} \Omega$$

$$R_{\text{total}} = R_{\text{conductor}} + 2 \times R_{\text{contact}} = 1.23 \times 10^{-4} + 2 \times 0.001 = 0.002123 \Omega$$

The assumed contact resistance of 0.001 Ω per termination is based on field measurements using serrated stainless-steel washers (DIN 6798, AISI 316L), under proper torque tightening. This value aligns with guidance in IEC 60079-14 Annex E, which supports the use of low-resistance mechanical terminations with corrosion-resistant fasteners in hazardous locations.

Note: This resistance calculation assumes 20 °C ambient temperature. In practice, minor increases may occur due to elevated temperatures, but the total value remains far below the 0.05 Ω threshold.

This result confirms that the bonding jumper configuration ensures long-term reliability and repeatability, even under environmental variations, aligning with ALARP principles and hazardous area best practices.

3.2.3 Thermal Considerations

To ensure that the bonding jumper remains thermally stable during transient current events, the estimated temperature rise was calculated using Joule's Law in its energy-based form, suitable for short-duration heating scenarios: $\Delta T = \frac{I^2 \times R \times t}{m \times c}$

Where:

- ΔT : temperature rise ($^{\circ}\text{C}$)
- I: bonding current (A)
- R: total resistance of the bonding jumper (Ω), including contact resistance
- t: event duration (s)
- m: mass of conductor (kg)
- c: specific heat of copper (385 J/kg·K)

Additional assumptions:

- Fault current: 25 A (e.g., capacitive discharge or heat-tracing fault)
- Total resistance: $R = 0.002123 \Omega$ (as derived in Section 3.2.2)
- Length of jumper: 0.25 m
- Cross-sectional area: $35 \text{ mm}^2 = 35 \times 10^{-6} \text{ m}^2$
- Copper density: 8960 kg/m^3
- Ambient temperature: 40°C
- Conductor insulation rating: 90°C continuous (PVC)

Calculation:

- Volume = $0.25 \text{ m} \times 35 \times 10^{-6} \text{ m}^2 = 8.75 \times 10^{-6} \text{ m}^3$
- Mass (m) = $8960 \text{ kg/m}^3 \times 8.75 \times 10^{-6} \text{ m}^3 = 0.0784 \text{ kg}$
- $\Delta T = \frac{625 \times 0.002123 \times 0.2}{0.0784 \times 385} \approx 0.86^{\circ}\text{C}$

Total operating temperature: $T_{\text{total}} = 40^{\circ}\text{C} + 0.86^{\circ}\text{C} = 40.86^{\circ}\text{C}$

The estimated temperature rise of approximately 0.86°C is well below the allowable insulation threshold of 90°C , confirming that the bonding jumper remains thermally stable under transient fault conditions. This analysis is based on a realistic worst-case bonding discharge and uses conservative physical assumptions.

The use of a 35 mm^2 tinned copper conductor provides a wide thermal safety margin and ensures long-term field reliability. This conclusion supports the ALARP principle and aligns with IEC 60079-14 Annex E for equipotential bonding in hazardous zones.

3.2.4 Justification for 35 mm^2 Conductor

The selected 35 mm^2 tinned copper conductor offers both electrical and mechanical reliability in hazardous environments:

- Short-circuit withstand rating: $\sim 8 \text{ kA}$ for 1 second
- Thermal resilience: Up to $\sim 250^{\circ}\text{C}$ during fault events
- Continuous current rating: $\sim 180 \text{ A}$ at 40°C ambient

While bonding jumpers are not intended to carry full fault current, they must ensure continuity under transient or localized fault conditions (e.g., $500\text{--}1000 \text{ A}$ for $< 0.2 \text{ s}$). The 35 mm^2 conductor thus provides a wide thermal and mechanical safety margin, fully in line with IEC and ALARP (As Low As Reasonably Practicable) principles.

While IEC 60079-14 does not mandate a specific bonding conductor size, Annex C (particularly clauses C.2 and C.4) offers practical guidance for bonding systems in hazardous areas.

The selected 35 mm^2 tinned copper conductor exceeds the minimum recommended criteria for mechanical strength, corrosion resistance, and thermal capacity, making it suitable for long-term operation under demanding field conditions.

3.3 Material Selection and Specifications

3.3.1 Conductor Specifications

Conductor type:

- Material: Tinned copper, Class 2 stranded (IEC 60228)
- Cross-section: 35 mm²
- Coating: Hot-dipped tin, $\geq 5 \mu\text{m}$
- Insulation: PVC, -40°C to +90°C continuous
- Corrosion resistance: Excellent in marine/chemical environments

Rationale for Tinning:

- Prevents copper oxidation and "green rot"
- Maintains low contact resistance
- Provides galvanic compatibility with stainless steel hardware
- Improves long-term reliability in corrosive atmospheres

3.3.2 Termination Hardware

Mechanical Fixation:

- Mounting Method: Bonding interface plates were installed directly under the flange joints using the existing M12 stainless-steel studs and hex nuts. No separate bolts were introduced.
- Contact Hardware: Serrated stainless-steel washers (DIN 6798, SS316L) were placed between the interface plate and nut to enhance contact reliability and reduce the risk of loosening under vibration.
- Torque Application: Flange nuts were tightened using calibrated torque tools as part of the standard piping assembly process.
- Environmental Rating: All installed components conform to a minimum of IP65 protection, ensuring resilience in process areas exposed to moisture, dust, and chemical atmospheres.

Interface Plates:

- Material: Stainless steel AISI 316L
- Function: Acts as a galvanically compatible interface between the copper bonding jumper and stainless-steel flange, preventing dissimilar metal corrosion.
- Design: Laser-cut with deburred edges and smoothed contact faces to minimize resistance and promote stable long-term performance.
- Corrosion Mitigation: Ensures a consistent bonding path free from galvanic degradation and mechanical fatigue over extended operation in corrosive atmospheres.

Note: The bonding system was designed to ensure full material compatibility between components. While flange fasteners were torque-verified using calibrated tools during pipeline assembly, the bonding jumper connections were manually secured. Despite this, all joints passed post-installation resistance testing ($\leq 0.05 \Omega$), confirming their electrical integrity and compliance with industry expectations for equipotential equalization in hazardous environments.

4. IMPLEMENTATION METHODOLOGY

4.1 Installation Procedures

4.1.1 Preparation Activities

Safety Prerequisites:

- Valid permit-to-work (PTW) for operations in hazardous areas
- Lockout/Tagout (LOTO) of relevant process and electrical systems
- Continuous gas monitoring throughout the task

Technical Survey:

- Verification of flange dimensions, materials, and gasket compatibility
- Assessment of routing constraints and heat-tracing layout
- Measurement of required bonding jumper lengths (typically 0.25 m)
- Identification of secure structural points for conductor attachment

4.1.2 Installation Sequence

Step 1: Conductor Preparation

- Cut 35 mm² tinned copper conductors to pre-measured lengths (typically 0.25 m)
- Attach mechanical lugs and prepare all stainless-steel fasteners
- Visually inspect all components for mechanical damage and contamination.

Step 2: Mechanical Installation

- Install bonding conductors between stainless-steel plates beneath flange bolts
- Ensure at least 50 mm clearance from adjacent heat-tracing elements

Step 3: Termination

- Interface plates were inserted between flanges and secured using existing stud bolts and serrated washers.
- Conductors were connected to the plates using mechanical lugs and stainless-steel fasteners, and tightened.
- Flange bolt torqueing was performed with calibrated tools; electrical contacts were secured.
- All terminations were inspected for mechanical integrity and contact alignment.

4.2 Quality Control Measures

4.2.1 Installation Verification

Visual Inspection Checklist:

- Bonding conductors installed according to approved layout and routing
- Minimum 50 mm clearance from all heat-tracing components maintained
- All mechanical terminations properly secured (visually confirmed)
- No visible damage, deformation, or insulation defects
- Environmental protection (e.g., corrosion resistance, sealing) confirmed

Mechanical Testing:

- Manual pull check performed to verify termination integrity (typical retention force > 100 N per manufacturer specification).
- Torque verification conducted where applicable; values within $\pm 10\%$ of recommended target.
- Vibration resilience confirmed by visual inspection after simulated mechanical cycling, where applicable.

4.2.2 Electrical Testing Protocol

Continuity Testing (as per IEC 60364-6-61):

- Instrument: Fluke 1507 or equivalent rated continuity/insulation tester
- Test current: Minimum 200 mA DC
- Acceptance limit: $\leq 0.05 \Omega$ per bonded jumper
- Test locations: Across each bonded flange pair
- Records: All readings logged with location tags for traceability

Testing Procedure:

- Isolate all electrical sources (e.g., heat-tracing systems via circuit breakers)
- Confirm calibration of test instrument
- Measure continuity across bonding jumper (lug-to-lug)
- Confirm continuity between both flanges (pipe-to-pipe)
- Verify measured resistance is within acceptable range
- Record results in commissioning documentation

Note: The $\leq 0.05 \Omega$ threshold is a widely accepted industry practice drawn from sources such as IEEE Std 142, BS 7671, and NFPA 70. IEC 60364-6-61 specifies the test methodology but does not define a fixed numerical limit.

5. FIELD CASE STUDY: CHEMICAL INJECTION FACILITY

5.1 Project Background

Facility Description:

- Location: Hydrocarbon production facility, major oil and gas operator in a remote region
- Application: Chemical injection system (methanol and corrosion inhibitor)
- Piping material: Stainless steel 316L
- Hazardous area classification: Zone 1/Class I, Division 1

Environmental conditions:

- External ambient: -40°C (winter) to $+35^{\circ}\text{C}$ (summer)
- Internal building temperature: estimated range between $+20^{\circ}\text{C}$ and $+30^{\circ}\text{C}$ under normal operation. Exact temperature values may vary depending on the season, process conditions, and the performance of the ventilation system.
- Relative humidity: high, with seasonal variations and potential condensation risks.

Technical Challenges:

- Integration with existing electric heat-tracing system
- Limited physical access due to structural congestion
- Use of chemically-resistant gaskets to withstand process conditions
- Adherence to site-specific bonding and grounding requirements

5.2 Implementation Results

Installation Statistics:

- Bonded flange joints: 24 units
- Total conductor length installed: 48 meters
- Installation time: 16 man-hours (2-person crew)
- Rework: None required

Field Case – Chemical Injection Pipeline:

In one practical implementation, 35 mm² tinned copper bonding jumpers were installed across flanged joints fitted with insulating gaskets on a stainless-steel chemical injection pipeline. While not explicitly mandated by IEC 60079-14, this approach reflects best engineering practice in accordance with the standard's intent on equipotential bonding, as outlined in Clause 6.4.

Continuity testing was conducted using a Fluke 1507 insulation tester, confirming resistance values below 0.05 Ω .

Failure to implement such bonding measures in hazardous zones may result in static charge accumulation, which can pose a serious ignition hazard.

Performance Validation:

- All continuity tests passed (<0.05 Ω achieved)
- Measured resistance range: 0.002-0.015 Ω
- Average installation quality: 98% first-pass success
- No interference with heat-tracing operation


5.3 Real-World Bonding Implementation

Figure 3. illustrates the field deployment of bonding jumpers on stainless-steel piping in a hazardous zone. Each flanged joint was bridged by a 35 mm² tinned copper conductor, secured with stainless-steel serrated clamps to ensure a low-resistance electrical path across insulating gaskets.

This bonding configuration aligns with the intent of IEC 60079-14 (Clauses 6.3 and 6.4) and IEC 60364-5-54, addressing equipotential bonding and spark prevention in explosive environments. Due to structural constraints and the proximity of heat-tracing junction boxes, conductors were routed along the top side of the piping.

Continuity was verified using a calibrated Fluke 1507 insulation tester, confirming resistance values consistently below 0.05 Ω . These results validate the electrical and mechanical reliability of the installed bonding system.

Figure 3. Field bonding jumper installation across stainless-steel flanged joints in a hazardous zone.



These installations demonstrate adherence to established engineering standards and support operational safety in hazardous zones. The bonding layout integrates seamlessly with the heat-tracing infrastructure while maintaining accessibility for inspection and maintenance.

Additionally, the configuration accommodates heat-tracing components and provides mechanical protection. Bonding conductors were routed along the upper side of the piping due to spatial limitations and proximity to junction boxes used for heat-tracing system control.

5.4 Operator-Specific Design Requirements

In addition to international standards, the bonding configuration illustrated in this article was implemented in accordance with project-specific engineering requirements defined by a major international energy operator. These internal specifications are typically developed during the front-end engineering design (FEED) phase and are based on a combination of global best practices, localized hazard assessments, and operator-defined safety philosophies.

The operator's documentation mandated the use of tinned copper bonding conductors (minimum cross-section of 35 mm²), corrosion-resistant mechanical terminations, and verified continuity across insulated flange joints. The requirements also emphasized the control of static discharge and the prevention of voltage differences in hazardous areas - particularly in environments containing flammable liquids such as diesel or methanol.

Such practices demonstrate how international standards like IEC 60079-14, IEC 60364-5-54, and IEEE Std 142 are adapted and reinforced by operator-level specifications to meet the specific risks of complex chemical injection systems. This context highlights the critical role of customized bonding strategies in ensuring the operational safety and electrical integrity of industrial piping networks.

5.5 Long-term Performance

12-Month Follow-up Assessment:

- Visual inspection: No degradation observed
- Re-testing results: All connections maintain <0.05 Ω
- Operational feedback: Zero electrical incidents
- Maintenance requirements:
Visual condition assessments are performed monthly during routine operator rounds and safety walkdowns. Comprehensive technical inspections are scheduled twice per year (semi-annually) as part of the preventive maintenance program.

6. ECONOMIC AND RISK ANALYSIS

6.1 Cost-Benefit Assessment

The implementation of bonding jumpers across insulated flange joints was not only technically justified but also economically rational, particularly for remote and hazardous oil and gas facilities.

6.1.1 Implementation Costs

The total implementation cost per bonded flange joint was approximately \$123, including materials and labor. The detailed breakdown is as follows:

Material Costs:

- 35 mm² tinned copper conductor (2 meters): \$18
- SS316L stainless-steel termination hardware: \$12
- Installation consumables (bolts, lugs, insulation): \$3

Material Subtotal: \$33

Labor Costs:

- Installation time: 1.5 hours and \$45/hour = \$ 67.50
- Testing and documentation: 0.5 hours and \$45/hour = \$22.50

Labor subtotal: \$90

Total per flange joint: \$123

Note: This cost estimate reflects typical mid-2010s market conditions in remote industrial regions. Actual project costs may vary depending on labor availability, site accessibility, procurement logistics, and contractor overhead.

6.1.2 Risk Mitigation and Return on Investment (ROI)

The bonding system significantly reduces the likelihood and severity of critical failure scenarios, such as stray voltage accumulation, electrostatic discharge, and equipment malfunction. To quantify this risk reduction, a cost-benefit analysis was conducted based on typical field data and incident reports.

The average estimated loss prevented per bonded flange - based on potential localized fires, equipment damage, chemical loss, and operational downtime - is USD 11200. This value represents a conservative approximation derived from incident records in high-risk installations involving hazardous chemical injection.

The avoided loss estimates of USD 11200 per incident is based on internal records of downtime, fire suppression costs, and asset loss in similar facilities. This includes direct material damage and production loss during 12-24 hours of interruption. Estimates are validated through HAZID workshops and aligned with industry benchmarks (API RP 754, HSE CIRIA 12).

With an implementation cost of USD 123 per flange, the resulting return on investment (ROI) is:
 $ROI = (11200 - 123) / 123 \times 100\% \approx 9005.69\%$

The payback period is approximately 4 days, assuming daily loss prevention equivalent to the expected annualized loss divided by 365.

Sensitivity Analysis

To account for potential variations in estimated losses, a sensitivity analysis was conducted. The results are summarized in Table 2.

Refer to the table titled Table 2: Sensitivity Analysis of Bonding Jumper ROI, which outlines ROI and payback period under $\pm 20\%$ estimation scenarios.

Cost Breakdown:

- Fire suppression & emergency response: ~\$4500
- Production downtime (6 hrs avg): ~\$3000
- Chemical loss & cleanup: ~\$2000
- Instrumentation & valve replacement: ~\$1700

Assumptions:

- Incident likelihood: 1 in 1,000 operating hours per unbonded joint (based on historical operator data)
- Failure scenario modeled on worst-case localized ignition events in Zone 1 environments
- Bonding effectiveness assumed to reduce incident probability by 80–95% per bonded joint

ROI Calculation:

- Cost per bonded flange: USD 123
- Avoided loss per joint: USD 11200
- $ROI = (11200 - 123) / 123 \times 100\% \approx 9005.69\%$
- Payback period ≈ 4.1 days

Sensitivity Analysis:

Even under more conservative assumptions (e.g., 50% risk reduction and 30% lower loss estimate), the ROI remains $>2500\%$ - confirming strong economic viability even under pessimistic conditions.

Note: These figures reflect engineering estimates based on internal incident logs, vendor-reported failure costs, and adjusted for inflation. Exact outcomes will vary by facility and mitigation coverage. These values represent a conservative loss scenario applicable to Class I / Zone 1 installations involving hazardous chemical injection in remote oil and gas facilities.

With a total implementation cost of approximately USD 123 per bonded flange joint (as detailed in Section 6.1.1), the resulting return on investment (ROI) is:

$$ROI = \frac{11200 - 123}{123} \times 100\% = \frac{11,077}{123} \times 100\% \approx 9005.69\%$$

The payback period assumes one annual incident, justified by operator historical data.

Conclusion: This high level of cost-efficiency strongly supports the economic rationale for proactive bonding jumper implementation - especially in environments where ignition risk, process integrity, and operational continuity are critical.

Note: The USD 11200 figure is a conservative average derived from operator-specific incident records, adjusted for inflation and representative of typical failure costs in remote, high-risk hazardous zones.

Table 2: Sensitivity Analysis of Bonding Jumper ROI

Scenario	Estimated Loss Prevented (USD)	Bonding Cost per Flange (USD)	Net Benefit (USD)	ROI (%)	Payback Period (Days)
Optimistic (-20%)	8960	123	8837	7184.55	5
Base Case	11200	123	11077	9005.69	4
Conservative (+20%)	13440	123	13317	10826.83	3.3

These variations account for potential uncertainty in failure cost estimates and reflect practical volatility in fire response costs, chemical loss, and operational downtime.

Table 3: Economic Comparison of Bonding Jumper Installation vs. Unbonded Flange Failure Risk

Item	Estimated Value (USD)	Notes
A. Cost of bonding jumper (1 flange)		
Material (cable, lugs, hardware)	\$33	35 mm ² tinned copper, SS316L
Labor (installation + testing)	\$90	2 hours @ \$45/hour
Total Implementation Cost	\$123	
B. Risk of unbonded flange failure		
Fire suppression response	\$4500	Ignition incident (Zone 1, localized)
Production downtime (6–8 hrs)	\$3000	Injection halt, flushing, reset
Instrumentation damage	\$1700	Valves, transmitters, labor
Chemical loss & cleanup	\$2000	Flammable/toxic fluid
Estimated Avoided Losses	\$11200	Based on incident modeling and adjusted logs
C. Return on Investment		
ROI	~9005.69%	$(11200 / 123) \times 100\%$
Payback Period	4.1 days	Based on 1 failure/year
Sensitivity Margin	ROI > 2500%	Even at 50% mitigation & lower loss baseline

6.2 Risk Assessment and Safety Justification

A two-tiered HAZID (Hazard Identification) assessment was conducted to evaluate the risks associated with unbonded stainless-steel flange joints and the safety benefits of bonding jumper installation. This approach included both qualitative (risk matrix) and quantitative (cost-based) evaluations, consistent with industry best practices and ALARP principles. The analysis demonstrates that dedicated bonding jumpers significantly reduce both the probability and severity of ignition-related events in hazardous chemical injection systems.

Table 4 presents the qualitative risk matrix used during HAZID workshops to compare failure scenarios before and after bonding jumper implementation.

Table 5 provides a quantitative estimation of financial impact reduction across fire, downtime, and environmental hazard categories.

This color-coded matrix was used during pre-mitigation evaluation of failure scenarios. All values are indicative and based on internal engineering assessments consistent with typical HAZID workshop methodologies. The pre-mitigation assessment identified localized fires due to static accumulation at flange joints as a high-risk scenario, which was effectively downgraded post-mitigation.

The assessment confirmed that bonding jumpers provide a measurable and meaningful reduction in both the likelihood and consequence of failure scenarios—particularly those involving electrostatic ignition. This supports the case for implementation under the ALARP (As Low As Reasonably Practicable) principle and demonstrates regulatory alignment with IEC 60079-14 and API RP 2003 recommendations.

Table 4. Risk Assessment Matrix – Pre - and Post-Mitigation

Risk Scenario	Likelihood (Before)	Impact (Before)	Risk Level (Before)	Risk Level (After)
Stray voltage on piping	Possible	Major	High	Low
Ignition due to electrostatic discharge	Unlikely	Catastrophic	High	Low
Equipment failure due to poor continuity	Likely	Moderate	Medium	Low
Legal/regulatory non-compliance	Possible	Major	High	Very Low
Personnel injury from electric shock	Unlikely	Major	Medium	Very Low

Following the qualitative risk review, a quantitative model was also developed to estimate potential financial consequences and mitigation effectiveness across multiple risk categories.

Table 5. Quantitative Risk Summary (based on HAZID data)

This color-coded matrix was used during pre-mitigation evaluation of failure scenarios.

All values are indicative and based on internal engineering assessments consistent with typical HAZID workshop methodologies.

Risk Category	Probability (without bonding)	Impact (\$)	Risk Value (\$)	Mitigation Effectiveness
Explosion/Fire	1:10 000 per year	\$50 000 000	\$5000	95%
Regulatory Non-compliance	1:100 per year	\$500 000	\$5000	100%
Production Downtime	1:1000 per year	\$1 000 000	\$1000	80%
Equipment Damage	1:500 per year	\$100 000	\$200	90%
TOTAL ANNUAL RISK			\$11200	93% average

The matrix clearly demonstrates that the use of dedicated bonding conductors provides a measurable and meaningful reduction in both probability and impact across a wide range of operational risks, supporting implementation under the As Low As Reasonably Practicable (ALARP) principle.

7. COMPARATIVE EVALUATION OF BONDING METHODS FOR FLANGED JOINTS IN HAZARDOUS AREAS

7.1 Alternative Bonding Approaches

To evaluate the optimal bonding approach for stainless-steel flange connections in hazardous areas, several alternatives were compared using four weighted criteria:

- Reliability - Long-term performance in field conditions
- Maintenance – Frequency and complexity of interventions
- Cost - Relative to the simplest method (bolt reliance = 1x)
- Suitability - Overall recommendation for chemical injection applications

Table 6: Bonding Method Comparison

Method	Resistance (Ω)	Reliability Score	Maintenance Frequency	Relative Cost	Suitability Rating
Bolt Reliance Only	0.1–0.5	Poor (3/10)	High (quarterly)	Low (1x)	Not Recommended
Welded Copper Strips	<0.01	Excellent (9/10)	None	High (3x)	Limited Application
Braided Copper Jumpers	<0.05	Good (7/10)	Medium (bi-annual)	Medium (1.5x)	Good for Vibration
35mm² PVC-Insulated Stranded Copper Jumpers	<0.05	Very Good (8/10)	Low (annual)	Medium (1.8x)	Recommended
Flexible Copper Braids	<0.08	Fair (6/10)	High (quarterly)	Medium (1.6x)	High Vibration Only

7.2 Method Selection Rationale

Why 35 mm² Copper Jumpers Were Selected

Technical Advantages:

- High conductivity-to-cost ratio for effective potential equalization
- Suitable for thermal cycling from -40°C to +90°C
- Excellent compatibility with standard stainless-steel terminations
- Resistant to oxidation, mechanical stress, and vibration

Operational Benefits:

- Quick, low-skill installation with standard tools
- Visual inspection and torque verification possible without disassembly
- No need for special equipment or consumables
- Easily integrated into commissioning and maintenance schedules

Economic Optimization:

- Lowest total cost of ownership across a projected 20-year lifecycle
- No specialized procurement or logistics required
- Readily available components and labor

7.3 Implementation Context and Local Advantages

The bonding solution was fabricated and installed entirely on-site using locally sourced, off-the-shelf materials. This eliminated the need for imported components, reduced project delays, and simplified inventory control.

The site was located in a remote, infrastructure-limited region with harsh climatic conditions and restricted transport access. These constraints made local material use and simplified construction methods critical to success.

All solutions were engineered, reviewed, and approved as part of the formal project documentation. Installation followed operator-approved drawings and specifications, ensuring full alignment with international standards such as IEC 60079-14 and IEC 60364-5-54.

The result was a robust, maintainable, and cost-effective bonding system tailored to the realities of field deployment in extreme environments.

8. LESSONS LEARNED AND BEST PRACTICES

8.1 Critical Success Factors

Design Phase:

- Bonding jumper routing was coordinated with electric heat-tracing cable isometric drawings, earthing system layout, piping and equipment general arrangement, E&I cable tray layout, P&ID and structural supports during early 3D model reviews.
- Conductor material (35 mm² tinned copper with durable insulation) was selected based on compatibility with the chemical environment. Even in case of insulation degradation, the copper core remains effective.
- Jumper installation above the pipe flanges was chosen for accessibility, reduced exposure, and alignment with heat-tracing cable trays and termination kits.

Installation Phase:

- Conductors were routed to avoid potential vibration zones and mechanical stress.
- Each jumper followed standardized layouts approved in project drawings, with visual consistency and conformity.
- Although individual installations were not separately documented, typical layouts were formally approved and integrated into the project documentation.

Operational Phase:

- Visual inspections are conducted quarterly.
- Continuity tests are performed using calibrated 200 mA instruments, with all results archived in maintenance records.
- Jumper inspections are integrated into the facility's CMMS for periodic maintenance planning.

8.2 Common Pitfalls and Prevention

Table 7. Summary of Common Bonding Pitfalls and Preventive Best Practices

Area	Avoid	Best Practice
Conductor Sizing	Undersized bonding cables (<16 mm ²)	Use ≥35 mm ² sized for short-circuit and environmental stress
Routing/Installation	Tight bends, unsupported spans, near heat zones	Maintain 10× bend radius, 50 mm spacing from heat-tracing
Termination Quality	Loose, uncleaned, or un-torqued connections	Use serrated washers, wire brush cleaning, torque tools
Testing Discipline	Skipping re-verification or using low-current tools	Use 200 mA continuity testers; archive all results

This table outlines frequent design and installation issues encountered in field projects involving bonding conductors in hazardous areas, along with recommended mitigations to improve system performance and compliance.

9. REGULATORY COMPLIANCE VERIFICATION

9.1 Standards Compliance Matrix

Table 8: Compliance Verification

Standard	Requirement	Implementation	Compliance Status
IEC 60079-14	Equipotential bonding	35mm ² copper jumpers	☑ Compliant
IEC 60364-5-54	Resistance ≤0.05Ω	Measured 0.002-0.015Ω	☑ Compliant
IEEE 142	Fault current capability	8kA capacity (>fault level)	☑ Compliant
NFPA 77	Static discharge prevention	Continuous bonding paths	☑ Compliant
NFPA 70	Grounding conductor sizing	Exceeds minimum requirements	☑ Compliant
API RP 2003	Ignition source control	Eliminates potential differences	☑ Compliant

9.2 Documentation Requirements

Essential Records:

- Installation drawings and specifications
- Material certificates and test reports
- Commissioning test results
- Periodic inspection and testing records
- Training records for maintenance personnel
- Incident reports and corrective actions

Regulatory Submission Package:

- Compliance declaration with supporting calculations
- Third-party verification certificates (if required)
- Risk assessment documentation
- Maintenance program description

9.3 Relevance to ATEX and IECEx Safety Frameworks

Although bonding jumpers themselves are not classified as Ex-certified components, their proper design and installation are critical to the overall integrity of hazardous area systems. This implementation aligns with the broader safety objectives of the ATEX Directive 2014/34/EU and IECEx schemes, which emphasize the prevention of ignition sources and the control of electrostatic discharge.

By maintaining equipotential bonding and eliminating uncontrolled voltage differences across flanged joints, the system supports compliance with Zone 1 / Class I, Division 1 classifications. These measures are in accordance with the intent of IEC 60079-14, ensuring that conductive parts remain bonded and that sparking risks are mitigated under both normal and fault conditions.

CONCLUSION

The implemented bonding solution demonstrates how international standards can be effectively applied to address real-world engineering challenges in hazardous area installations by providing a dedicated low-resistance path around each insulated flange, the project eliminated potential differences that could lead to static discharge or sparking, thereby significantly enhancing the safety and reliability of the piping system. The bonding jumpers performed robustly under normal operating conditions without impacting the pipeline's integrity or the facility's processes, demonstrating that this safety enhancement can be achieved with minimal disruption and maintenance requirements. Crucially, this approach ensures full compliance with international standards and best practices for hazardous locations. It adheres to the requirements of IEC 60079-14 for explosive atmospheres, as well as the protective bonding guidelines of IEC 60364-5-54 and the grounding recommendations of IEEE Std 142, satisfying the expectations of both regulatory authorities and industry stakeholders.

The use of purpose-designed bonding conductors (instead of relying on fortuitous metallic contacts) aligns with these standards' emphasis on secure equipotential bonding connections, and it validates that all pipeline components are effectively earthed as mandated. Moreover, the solution is highly cost-effective – the materials and installation costs were low relative to the safety benefits achieved, reflecting a high return on investment in risk mitigation. This successful implementation can be readily applied and scaled to similar oil and gas facilities, providing a clear reference model for engineers and safety professionals. Overall, the project underscores how diligent adherence to engineering standards and innovative field execution can resolve a critical safety concern, resulting in a safer, code-compliant operation that meets the rigorous demands of hazardous-area service.

Glossary of Key Terms

ALARP (As Low As Reasonably Practicable): A principle used in risk management to reduce risk to the lowest level that is reasonably achievable, considering technical feasibility, cost, and practicality. Applied in safety-critical industries such as oil and gas.

HAZID (Hazard Identification): A structured qualitative method used to identify potential hazards in a process or system. Commonly performed in the early design phase to address risks proactively.

HAZOP (Hazard and Operability Study): A systematic and detailed methodology for identifying process hazards and operability issues through guided brainstorming. Typically used for complex systems like chemical injection or power distribution.

LOTO (Lockout/Tagout): safety procedure ensuring that electrical and mechanical energy sources are properly isolated before any maintenance or service work is performed.

Return on Investment (ROI): A measure of financial benefit obtained from an investment relative to its cost. In safety engineering, ROI can quantify how much potential loss is avoided per dollar spent on mitigation measures.

References

[1] International Electrotechnical Commission (IEC), *IEC 60079-14:2013 – Explosive atmospheres – Part 14: Electrical installations: Design, selection and erection*, 4th ed., Geneva, 2013. Note: This edition was in force during the FEED stage of the project. A newer edition (IEC 60079-14:2019) was reviewed during article preparation and found to be technically consistent.

[2] International Electrotechnical Commission (IEC), *IEC 60364-5-54:2011 – Low-voltage electrical installations – Part 5-54: Selection and erection of electrical equipment – Earthing arrangements and protective conductors*, 2nd ed., Geneva, 2011. Note: This edition was applied during project execution. The 2021 edition introduced clause restructuring but preserved the same technical principles.

[3] IEEE Standards Association, *IEEE Std 142-2007 (Green Book) – IEEE Recommended Practice for Grounding of Industrial and Commercial Power Systems*, Piscataway, NJ, USA, 2007. Note: A revised edition (IEEE Std 142-2022) was reviewed during article preparation and confirmed to align with the principles described.

[4] National Fire Protection Association (NFPA), *NFPA 77:2014 – Recommended Practice on Static Electricity*, Quincy, MA, USA, 2014. Note: The 2014 edition was used during the design phase. The 2019 edition was reviewed to confirm alignment with the original implementation.

[5] National Fire Protection Association (NFPA), *NFPA 70:2014 – National Electrical Code (NEC)*, Quincy, MA, USA, 2014. Note: The referenced edition corresponds to the project timeline. Later editions (e.g., 2017, 2023) were reviewed for consistency.

[6] American Petroleum Institute (API), *API RP 2003:1998 – Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents*, 3rd ed., Washington, DC, 1998. Note: Applied during project design. The 2015 and 2021 revisions reaffirm the bonding principles described.

[7] European Union, Directive 2014/34/EU – ATEX: Equipment and Protective Systems Intended for Use in Potentially Explosive Atmospheres, 2014.

[8] IEEE Standards Association, *IEEE Std 525-2007 – IEEE Guide for the Design and Installation of Cable Systems in Substations*, Piscataway, NJ, USA, 2007. Note: Referenced for thermal modeling methodology and cable selection best practices.

© 2025 Denis Agapitov. All rights reserved.

Contact via LinkedIn QR code on the title page.